

Revision Number: 003.0 Issue date: 01/04/2023

PRODUCT AND COMPANY IDENTIFICATION

Product name: Loctite® PL300® Foamboard

Construction Adhesive

Product type/use: Water based adhesive Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

IDH number:

Region: **United States**

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

1421930

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING

DIFFICULTIES IF INHALED.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection. In case of inadequate ventilation wear respiratory

protection.

IF ON SKIN: Wash with plenty of water. IF INHALED: If breathing is difficult, remove victim to Response:

fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. If experiencing respiratory symptoms: Call a poison center or physician.

Wash contaminated clothing before reuse.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	40 - 50

IDH number: 1421930 Product name: Loctite® PL300® Foamboard Construction Adhesive

l	Quartz (SiO2), <1% respirable	14808-60-7	0.1 - 1
	dipotassium peroxodisulphate	7727-21-1	0.1 - 1

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: No specific treatment is necessary since material is not likely to be hazardous

by inhalation.

Skin contact: Wash affected area immediately with soap and water.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. If

symptoms develop and persist, get medical attention.

Ingestion: Consult a physician if necessary.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Carbon dioxide, foam, powder Water fog.

Special firefighting procedures: Use water spray to keep fire exposed containers cool and disperse vapors.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Not available.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal.

7. HANDLING AND STORAGE

Handling: Avoid prolonged or repeated skin contact with this material. Keep out of the

reach of children.

Storage: For safe storage, store at or above 0 °C (32°F)

Keep from freezing. Store in a cool, dry area. Keep containers closed when

not in use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	ılable particles. 5 mg/m3 TWA mg/m3 TWA Respirable fraction. None pirable particles. 50 MPPCF TWA g/m3 TWA Total Total dust.		None
Quartz (SiO2), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None
dipotassium peroxodisulphate	0.1 mg/m3 TWA (as persulfate)	None	None	None

Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: No personal respiratory protective equipment normally required.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Suitable protective clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:BlueOdor:mild, acrylicOdor threshold:Not available.pH:7.0 - 7.5

Vapor pressure:15 mm hg (20 °C (68°F))Boiling point/range:100 °C (212°F)

Not available. Melting point/ range: Specific gravity: 1.224 Vapor density: Heavier than air Flash point: Not applicable Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable

Evaporation rate: < 0.6 (Butyl acetate = 1)

Solubility in water: Soluble Partition coefficient (n-octanol/water): Not available.

VOC content: 0.1 %; 35 g/l (by weight, calculated using CARB method; g/L less water, less

exempts calculated using SCAQMD method)

Viscosity: 280,000 - 380,000 mPa.s

Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

Oxides of carbon. Oxides of nitrogen.

Incompatible materials: None

Reactivity: Not available.

Conditions to avoid: Heat. Do not freeze.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin contact

Potential Health Effects/Symptoms

Inhalation: Abrasion of cured material such as by sanding or grinding could release respirable particles of

silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.

Skin contact: May cause slight irritation to skin.

Eye contact: May cause slight irritation to eyes on contact.

Ingestion: Not expected to be harmful by ingestion. Ingestion of large amounts may produce

gastrointestinal disturbances including irritation, nausea, and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Quartz (SiO2), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity
dipotassium peroxodisulphate	Inhalation LC50 (Rat, 4 h) = > 5.1 mg/l Inhalation LC50 (Rat, 4 h) = >= 2.95 mg/l	No Data

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Quartz (SiO2), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes
dipotassium peroxodisulphate	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division:NoneIdentification number:NonePacking group:None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 12 (b) Export Notification:

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

Ammonia, aqueous solution (CAS# 1336-21-6). Hydroquinone (CAS# 123-31-9). Carbon

disulfide (CAS# 75-15-0). Ethylene oxide (CAS# 75-21-8). Acrolein (CAS# 107-02-8).

CERCLA/SARA Section 311/312: Delayed Health

CERCLA/SARA Section 313: None above reporting de minimis.

 California Proposition 65:
 This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2,3,8,11

Prepared by: Product Safety and Regulatory Affairs

Issue date: 01/04/2023

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.