# **Safety Data Sheet**



Revision Number: 003.0 Issue date: 02/10/2020

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Loctite Power Grab All Purpose IDH number: 2031710

Express

Product type/use: Sealant

Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067

e identified Region: United States

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW		
WARNING:	CAUSES SERIOUS EYE IRRITATION.	

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A

# PICTOGRAM(S)

## **Precautionary Statements**

**Prevention:** Wash affected area thoroughly after handling. Wear eye and face protection.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	30 - 40
Quartz (SiO2), <1% respirable	14808-60-7	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

# 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:** Wash affected area immediately with soap and water. If symptoms develop

and persist, get medical attention.

IDH number: 2031710 Product name: Loctite Power Grab All Purpose Express

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: Rinse out mouth. Do not drink. Never give anything by mouth to an

unconscious person. If adverse health effects develop seek medical attention.

Symptoms: See Section 11.

# 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Water may be unsuitable as an extinguishing media, but may be helpful in

keeping adjacent containers cool.

Unusual fire or explosion hazards: This product is an aqueous mixture which will not burn. If evaporated to

dryness, the solid residue may pose a slight fire hazard.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Oxides of nitrogen.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Ventilate area. Do not allow product to enter sewer or waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Wear appropriate protective equipment and clothing during clean-up. Dispose of according to Federal, State and local governmental regulations.

#### 7. HANDLING AND STORAGE

**Handling:** Avoid contact with eyes. Avoid prolonged or repeated skin contact with this

material. Use only with adequate ventilation. Wash hands before breaks and immediately after handling the product. Keep out of the reach of children.

**Storage:** Keep from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Quartz (SiO2), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:**Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Color:

Odor:

Odor threshold:

pH:

Liquid

White

Not available.

Not available.

7.3 - 8.5

Vapor pressure: 17.5 mbar (20 °C (68°F)) no method

Boiling point/range: > 100 °C (> 212°F)

Melting point/ range: Not available.

Specific gravity: 1.3

Vapor density: Heavier than air, (Air = 1)

**Flash point:** > 93.3 °C (> 199.94 °F) no method

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Flammability:

Flammability:

Evaporation rate:

Not available.

Not available.

Not applicable

0.3 (Butyl acetate = 1)

Solubility in water: Soluble Partition coefficient (n-octanol/water): Not available.

VOC content: 0.1 %; 14 g/l (by weight, calculated using CARB method; g/L less water, less

exempts calculated using SCAQMD method)

Viscosity: 0 - 1,000,000 cp Decomposition temperature: Not available.

# 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 2031710

Carbon dioxide. Carbon monoxide. Oxides of nitrogen. Hydrocarbons.

**Incompatible materials:** This product may react with strong acids, bases and oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Freezing conditions.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Eyes, Skin, Inhalation

#### Potential Health Effects/Symptoms

**Inhalation:** May cause respiratory tract irritation. Abrasion of cured material such as by sanding or grinding

could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of

this product causes no such release.

**Skin contact:** May cause mild skin irritation.

**Eye contact:** Contact with uncured product may irritate the eyes.

**Ingestion:** Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal

irritation and disturbances.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Quartz (SiO2), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Quartz (SiO2), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

#### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

**Hazardous waste number:** It is the responsibility of the user to determine if an item is hazardous as

defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
Delayed Health, Immediate Health
None above reporting de minimis.

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm. This product contains a chemical known in the State of California

to cause cancer.

Canada Regulatory Information

IDH number: 2031710

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

# 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2, 3, 11, 15

Prepared by: Regulatory Affairs

**Issue date:** 02/10/2020

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.