Yellow Guard™

POLYETHYLENE TAPE

Husky™ Yellow Guard™ Tape is made with a cast polyethylene film coated with high-tack natural rubber adhesive. Recommended for splicing heavy duty polyethylene, polyethylene patching, and protective masking, the tape is flexible, strong, and moisture and UV resistant.

Specifications quoted are averages only and may vary within industry tolerances. The final user must assure product suitability for the application and assumes all risks and liabilities.

Contact Poly-America's Sales Department for pricing and availability.

TECHNICAL DATA

Backing	Cast Polyethylene Film
Thickness	9.0 mils
Adhesion	70 oz/in
Tensile Strength	26 lbs/in
Elongation at Break	96.25%
Application Temperature	41°F – 122°F
Temperature Resistance	176°F for 30 min.
Roll Width	3.75 in
Roll Length	180 ft

Poly-America

2000 W. Marshall Dr. • Grand Prairie, TX 75051

800-527-3322 ext. 7610 • Fax 972-337-7016 • www.yellowguard.com • yellowguard@poly-america.com

The information provided herein has been compiled by Poly-America, L.P. and to the best of our knowledge accurately represents Poly-America's products at the time of publication. This publication is offered "as is," for preliminary planning purposes only, without any warranties of any kind. Final determination of suitability of this information or these products for the use contemplated and its manner of use are the sole responsibility of the end user. Poly-America, L.P. assumes no liability in connection with the use of this information and this product. This information is subject to change without notice.

57-023-0105B Rev 06/19