


Yellow Guard®

POLYETHYLENE TAPE



Husky® Yellow Guard® Tape is made with polyethylene film coated with high-tack pressure-sensitive rubber adhesive. Husky® Yellow Guard® Tape is conformable and flexible with excellent durability and is an excellent choice for splicing, seaming, and patching of Yellow Guard® Vapor Retarder/Barriers.

All areas to be taped must be clean and dry prior to sealing in accordance with ASTM E1643 — Standard Practice for Selection, Design, Installation, and Inspection of Water Vapor Retarders Used in Contact with Earth or Granular Fill Under Concrete Slabs.

TECHNICAL DATA

Total Thickness (ASTM D1000)	9.0 mils
Adhesion to Steel (PSTC 101)	134 oz/in
Tensile Strength (ASTM D1000)	33 lb/in
Permeance (ASTM F1249)	0.09 US Perms
WVTR (ASTM F1249)	0.22 g/(100 in² • day)
Application Temperature	30 to 160°F
Recommended Storage Conditions	60-80°F at 40-60% RH
Roll Size	3.75 in x 180 ft

All values are typical test values.

CONTACT POLY-AMERICA'S SALES DEPARTMENT WITH QUESTIONS OR FOR PRICING AND LOCAL DISTRIBUTION OPTIONS.

Poly-America

2000 W. Marshall Dr. • Grand Prairie, TX 75051
800-527-3322 ext. 7610 • Fax 972-337-7016 • www.yellowguard.com • yellowguard@poly-america.com

The information provided herein has been compiled by Poly-America, L.P. and to the best of our knowledge accurately represents Poly-America's products at the time of publication. This publication is offered "as is," for preliminary planning purposes only, without any warranties of any kind. Final determination of suitability of this information or these products for the use contemplated and its manner of use are the sole responsibility of the end user. Poly-America, L.P. assumes no liability in connection with the use of this information and this product. This information is subject to change without notice.

57-023-0105B Rev 05/21