






## EYELAGS - SHARP POINT

Interior ceiling systems into Wood. Primarily used for hanging suspended ceiling grid into wood joists. Longer length for drywall (or insulation) into Wood.



### Product Specifications



| Part # | Dia. | Length | TPI | Bulk Qty | Hole Dia. | Point | Finish |
|--------|------|--------|-----|----------|-----------|-------|--------|
| EL3    | 1/4" | 3"     | 10  | 1M       | 3/16"     | Sharp | None   |
| EL4    | 1/4" | 4"     | 10  | 1M       | 3/16"     | Sharp | None   |
| EL5    | 1/4" | 5"     | 10  | 1M       | 3/16"     | Sharp | None   |

| Nominal Screw Dia. (in) | Wood Type | Tension (Pull Out) Lbs |
|-------------------------|-----------|------------------------|
| 1/4"                    | Redwood   | 482                    |
|                         | Fir       | 503                    |

#### Ultimate Value Chart

Eyelags were driven into wood then pulled out with testing machine.

Note that all results were obtained in strict adherence to ASTM test protocol. These ultimate figures are offered only as a guide and are not guaranteed in any way by PrimeSource Building Products.

A 4:1 safety ratio is recommended.

ALL PRIMESOURCE FASTENERS ARE MANUFACTURED IN AN ISO 9002 AND ISO 14001 CERTIFIED AND APPROVED FACTORY TO PRIMESOURCE PERFORMANCE SPECIFICATIONS AND PRINT DRAWINGS.