





**HEX WASHER HEAD (5/16") SELF- PIERCING**

For sheet metal from 0.0209" to 0.0358". Recommended for H.V.A.C., electrical, plumbing, framing, and sheet metal.



5/16" HWH slotted

**Product Specifications**



| Part #   | Dia. | Length | TPI | Bulk Qty | Finish | Corrosion         | Washer Diameter | Thread      | Point        |
|----------|------|--------|-----|----------|--------|-------------------|-----------------|-------------|--------------|
| HW51012  | 10   | 1/2    | 13  | 8M       | Zinc   | 24 hr. min. B-117 | 8.18mm~ 8.84mm  | Double lead | Piercing 28° |
| HW51034  | 10   | 3/4    | 13  | 6M       | Zinc   | 24 hr. min. B-117 | 8.18mm~ 8.84mm  | Double lead | Piercing 28° |
| HW510100 | 10   | 1      | 13  | 5M       | Zinc   | 24 hr. min. B-117 | 8.18mm~ 8.84mm  | Double lead | Piercing 28° |
| HW510112 | 10   | 1-1/2  | 13  | 3M       | Zinc   | 24 hr. min. B-117 | 8.18mm~ 8.84mm  | Double lead | Piercing 28° |
| HW510200 | 10   | 2      | 13  | 2M       | Zinc   | 24 hr. min. B-117 | 8.18mm~ 8.84mm  | Double lead | Piercing 28° |

**Pro-Twist sheet metal screws meet or exceed ASTM C-1002 and/or ASTM C-1513**

| Dia. | Metal Gauge/1lb | Tension (Pull) Lbs. 1 Pc. | Shear Lbs. Metal to Metal | Minimum Torsional Strength (Lb) |
|------|-----------------|---------------------------|---------------------------|---------------------------------|
| 7    | 25              | 172                       | 412                       | 30                              |
|      | 22              | 260                       | 625                       |                                 |
|      | 20              | 346                       | 628                       |                                 |
| 8    | 25              | 149                       | 337                       | 39                              |
|      | 22              | 196                       | 591                       |                                 |
|      | 20              | 363                       | 829                       |                                 |
| 10   | 25              | 173                       | 363                       | 56                              |
|      | 20              | 412                       | 1755                      |                                 |

Ultimate Value Charts

Steel - Screws driven into steel were driven with three exposed threads on the off side of the connection, then pulled out with testing machine.

Note that all results were obtained in strict adherence to ASTM test protocol. These ultimate figures are offered only as a guide and are not guaranteed in any way by PrimeSource Building Products. A 4:1 safety ratio is recommended.

Installation Guidelines

0-2500rpm Screwgun with torque adjustment - Overdriving may result in fastener failure or stripout of the work surface

The fastener is fully seated when the head's bearing surface is flush with the steel.  
The fastener must penetrate beyond the metal a minimum of three threads to comply with the code

**ALL PRIMESOURCE FASTENERS ARE MANUFACTURED IN AN ISO 9002 AND ISO 14001 CERTIFIED AND APPROVED FACTORY TO PRIMESOURCE PERFORMANCE SPECIFICATIONS AND PRINT DRAWINGS.**