






**MODIFIED TRUSS HEAD SELF- PIERCING  
SHEET METAL SCREW**  
Expanded wire to wood or 25-20 gauge steel



Meets  
ASTM C-1002  
Reduced #2 Phillips

**Product Specifications**



Part #	Dia.	Length	TPI	Bulk Qty	Finish	Corrosion	Head Diameter	Thread	Point
MT812	8	1/2	15	10M	Zinc	24 hr. min. B-117	10.8mm~ 11.4mm	Double lead	Piercing 25°
MT834	8	3/4	15	8M	Zinc	24 hr. min. B-117	10.8mm~ 11.4mm	Double lead	Piercing 25°
MT100	8	1	15	5M	Zinc	24 hr. min. B-117	10.8mm~ 11.4mm	Double lead	Piercing 25°
MT114	8	1-1/4	15	5M	Zinc	24 hr. min. B-117	10.8mm~ 11.4mm	Double lead	Piercing 25°
MT158	8	1-5/8	15	5M	Zinc	24 hr. min. B-117	10.8mm~ 11.4mm	Double lead	Piercing 25°
MT178	8	1-7/8	15	4M	Zinc	24 hr. min. B-117	10.8mm~ 11.4mm	Double lead	Piercing 25°
MT200	8	2	15	2.5M	Zinc	24 hr. min. B-117	10.8mm~ 11.4mm	Double lead	Piercing 25°
MT212	8	2-1/2	15	2M	Zinc	24 hr. min. B-117	10.8mm~ 11.4mm	Double lead	Piercing 25°
MT300	8	3	15	1.5M	Zinc	24 hr. min. B-117	10.8mm~ 11.4mm	Double lead	Piercing 25°

**Pro-Twist sheet metal screws meet or exceed ASTM C-1002 and/or ASTM C-1513**

Dia.	Metal Gauge/1lb	Tension (Pull) Lbs. 1 Pc.	Shear Lbs. Metal to Metal	Minimum Torsional Strength (Lb)
8	25	149	337	39
	22	196	591	
	20	574	829	

Dia.	Wood	Withdrawal Value (Pull out)
8	redwood	206
	3/4" partical board	266
	2x4 fir	398

**Ultimate Value Charts**

Steel - Screws driven into steel were driven with three exposed threads on the off side of the connection, then pulled out with testing machine.

Wood - Screws driven 3/4" into the wood material, then pulled out the testing machine.

Note that all results were obtained in strict adherence to ASTM test protocol. These ultimate figures are offered only as a guide and are not guaranteed in any way by PrimeSource Building Products. A 4:1 safety ratio is recommended.

**Installation Guidelines**

0-2500rpm Screwgun with torque adjustment - Overdriving may result in fastener failure or stripout of the work surface

The fastener is fully seated when the head's bearing surface is flush with the steel.  
The fastener must penetrate beyond the metal a minimum of three threads to comply with the code

NOT Recommended for use with treated wood.

**ALL PRIMESOURCE FASTENERS ARE MANUFACTURED IN AN ISO 9002 AND ISO 14001 CERTIFIED AND APPROVED FACTORY TO PRIMESOURCE PERFORMANCE SPECIFICATIONS AND PRINT DRAWINGS.**