



 PROSOCO®

R-Guard®

AIR & WATER BARRIERS

**SEAMLESS
APPLICATION**

VAPOR PERMEABLE

**CAN BE EXPOSED
TO RAIN**

SELF-SEALING AROUND FASTENERS

ASTM 2112 PERFORMANCE

NFPA 285 TESTED
(National Fire Protection Association)

LIVING BUILDING CHALLENGE COMPLIANCE

**PHTHALATE
PLASTICIZERS FREE?**

EASY APPLICATION

**HIGH SOLIDS
CONTENT**

VOC COMPLIANT

WIDE APPLICATION TEMPERATURE RANGE

UV EXPOSURE

EASY FIELD REPAIR

R-GUARD

PEEL AND STICK FLASHING

 Seamless with uniform adhesion so no water/air migration paths	
 Allows for vapor diffusion so that substrate can dry and avoid condensation	
 Will not wash off wall. Rain will not require replacement or harm curing or bonding of material	
 Creates gasket condition at fasteners for water tightness ASTM D-1970	
 Air and Water-tight window rough openings	
 Code compliant wall assemblies	
 No Red List Ingredients & Health Product Declaration documents available.	
 No Environmental Concerns	
 No special tools, equipment or skills required to apply	
 No shrinkage	
 No odor or solvents.	
 Application surface temps from 32°F to 110°F	
 Can be exposed to UV up to 12 months. Accommodates schedule delays.	
 Repair by over coating. Saves cost in the event of recoating	