



PROSOCO®

# Enviro Klean®

NEXT GENERATION CLEANERS

## Klean 'N Release Cleaner

Enviro Klean® Klean 'N Release is a fragrance-free, all-purpose cleaner and degreaser for use on soiled stone, tile, masonry, EIFS, stucco and metal panels. It is safe enough for use on historic preservation and restoration projects yet strong enough for new construction and in food-processing facilities. Easy-to-use Klean 'N Release is dilutable with up to 10 parts water to offer an economical and effective concentrate solution.

Klean 'N Release can also be used on windows, bathroom tub and tile, counter tops and more.

Klean 'N Release is a US EPA Safer Choice certified cleaner that meets the Safer Choice direct release criteria. Formulated to be safer for workers and the environment by using readily biodegradable ingredients, Klean 'N Release contains no phosphates or hazardous solvents. The solution also offers more positive environmental and human health characteristics than conventional cleaning formulations. Klean 'N Release was intentionally designed to be safer for use around people, plants, lawns, pets or wildlife.



### ADVANTAGES

- **US EPA Safer Choice certified cleaner. Meets Safer Choice direct release criteria.**
- **Meets the US EPA's Safer Choice criteria for outdoor use.**
- **Cleans and degreases light-to-heavily soiled stone, tile, masonry, EIFS, stucco and much more.**
- **Dilutable for jobs around the home.**
- **Appropriate for use in food processing facilities.**
- **Replaces a host of individual cleaning agents.**
- **Contains no phosphates, hazardous solvents, or environmentally harmful surfactants.**
- **Fragrance free. Colorant free.**
- **Flexible dilution with up to 10 parts water.**
- **Ideal for unpolished natural stone – from limestone to granite.**
- **Works on an enormous variety of surfaces.**
- **Effective cleaner for windows, bathroom tub and tile, counter tops and more.**
- **Easy-to-use and water-rinsable.**

### SAFETY INFORMATION

Always read full label and SDS for precautionary instructions before use. Use appropriate safety equipment and job-site site controls during application and handling.

**24-Hour Emergency Information:**  
**INFOTRAC at 800-535-5053**

### REGULATORY COMPLIANCE

#### VOC Compliance

Enviro Klean® Klean 'N Release Cleaner is compliant with all national, state, district, consumer and institutional product VOC regulations.



Nonfood Compounds  
Program Listed A1 and A4  
Registration #159235

# Product Data Sheet

## Enviro Klean® Klean 'N Release Cleaner

### TYPICAL TECHNICAL DATA

FORM	Clear liquid, mild odor
SPECIFIC GRAVITY	1.05
pH	10.90
WT/GAL	8.70 lbs
ACTIVE CONTENT	not applicable
TOTAL SOLIDS	not applicable
VOC CONTENT	0
FLASH POINT	>212° F (>100° C) ASTM D3278
FREEZE POINT	32° F (0° C)
SHELF LIFE	2 years in tightly sealed, unopened container

### PREPARATION

Before use, test all substrates not intended to be cleaned with Klean 'N Release. If testing indicates adverse effects, the substrate must be protected before full scale application. Best practices are to protect people, vehicles, property, metal, painted surfaces, plants and other non-target materials from product, splash, residue, wind drift and fumes.

### Surface and Air Temperatures

Best air and surface temperatures for cleaning are 50° F (10° C) or above. Cleaning when temperatures are below freezing or will be overnight may harm masonry. If freezing conditions exist before application, allow masonry to thaw before application.

### Equipment

Apply with low-pressure sprayer, brush or heavy nap roller. Scrub heavily soiled surfaces with a nonabrasive brush or synthetic scrubbing pad.

Rinse with enough water and pressure to flush spent cleaner and dissolved soiling from the masonry surface and surface pores without damage. Masonry-washing equipment generating 400–1000 psi with a water flow rate of 6–8 gpm is the best water/pressure combination for rinsing porous masonry. Use a 15–45° fan spray tip. Heated water (150–180°F; 65–82°C) may improve cleaning efficiency.

Use adjustable equipment for reducing water flow rates and rinsing pressure for sensitive surfaces. Rinsing pressures greater than 1000 psi and fan spray tips smaller than 15° may permanently damage sensitive masonry. Water flow rates less than 6 gpm may reduce cleaning productivity and contribute to uneven cleaning results.

### Storage and Handling

Store in a cool, dry place. Always seal container after dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperature of 45–100°F (7–38°C). If product freezes, allow to thaw and mix well. Do not double stack pallets. For unused material, dispose of in accordance with local, state and federal regulations.

### APPLICATION

Read “Preparation” and the Safety Data Sheet before use. **ALWAYS TEST** a small area of each surface to confirm suitability, coverage rate and desired results before beginning overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application. Let surface dry thoroughly before inspection.

### Dilution & Mixing

Do not alter or use for purposes other than specified. Dilute with up to 10 parts fresh water. Use in concentrate to remove heavy soiling. Always test to final dilution producing desired cleaning results.

### Application Instructions

1. Working from the bottom to the top, prewet the surface with clean water.
2. Apply the cleaner to the surface using a brush or low-pressure spray.
3. Let the cleaner dwell on the surface 1–10 minutes, based on testing. Gently scrub heavily soiled areas. **NOTE:** Do not let the cleaner dry on the surface. If drying occurs, lightly wet surfaces with fresh water and reapply in a gentle scrubbing manner.
4. Working from the bottom to the top, always rinse the surface thoroughly with clean, fresh water. Rinsing is required in food processing areas.
5. Repeat steps 1 through 4 if necessary.

### Cleanup

Clean tools and equipment with fresh water.

# Product Data Sheet

## Enviro Klean® Klean 'N Release Cleaner

---

### WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

### CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care – technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our website at [prosoco.com](http://prosoco.com), for the name of the PROSOCO representative in your area.

