

SAFETY DATA SHEET



PROSOCO
Revision Number 3.02

Issuing Date 05-Jan-2015

Revision date 09-Oct-2025

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Sure Klean® Weather Seal Paver Enhancer

Other means of identification

Product Code(s) 56070

UN number UN1866

Recommended use of the chemical and restrictions on use

Recommended use Restricted to professional users.

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

PROSOCO, Inc.
3741 Greenway Circle
Lawrence, Kansas 66046

Emergency telephone number

8:00 AM – 5:00 PM CST Monday-Friday

785-865-4200

NON-BUSINESS HOURS (INFOTRAC)

800-535-5053

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Carcinogenicity	Category 2
Reproductive toxicity	Category 1B
Aspiration hazard	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Danger

Hazard statements

Causes skin irritation

Suspected of causing cancer

May damage fertility or the unborn child

May be fatal if swallowed and enters airways

Flammable liquid and vapor



Appearance clear	Physical state Liquid	Odor Petroleum
-------------------------	------------------------------	-----------------------

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/ /lighting equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
If skin irritation occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

- May be harmful if swallowed
 - May be harmful in contact with skin
- 20% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%	Trade Secret
Distillates, Petroleum, Hydrotreated Light	64742-48-9	40 - 70	*
Stoddard Solvent	8052-41-3	3 - 7	*
Proprietary - Acrylic Polymer	Undisclosed	3 - 7	*
Isobutyl trimethoxysilane	18395-30-7	1 - 5	*
Proprietary methoxyfunctional silanes	Undisclosed	1 - 5	*
Toluene	108-88-3	0.1 - 1	*
Ethylbenzene	100-41-4	0.1 - 1	*
Dibutyltin Dilaurate	77-58-7	0.1 - 1	*

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures****General advice**

In case of accident or unwellness, seek medical advice (show directions for use or safety data sheet if possible).

Eye contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

	continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a physician.
Ingestion	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms Causes skin irritation. May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO₂). Water spray (fog). Alcohol resistant foam.

Unsuitable Extinguishing Media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Keep away from heat. Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Use only non-sparking tools. Ground and bond containers when transferring material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). When using do not smoke. Use spark-proof tools and explosion-proof equipment. Use personal protective equipment as required. Avoid breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers. Keep away from heat. Keep out of the reach of children.

Incompatible materials

Incompatible with oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Stoddard Solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Dibutyltin Dilaurate 77-58-7	STEL: 0.2 mg/m ³ Sn TWA: 0.1 mg/m ³ Sn S*	TWA: 0.1 mg/m ³ Sn (vacated) TWA: 0.1 mg/m ³ Sn (vacated) S*	IDLH: 25 mg/m ³ Sn TWA: 0.1 mg/m ³ except Cyhexatin Sn

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Petroleum
Appearance	clear	Odor threshold	No information available
Color	Caramel		
Property	Values	Remarks • Method	
pH	Not Applicable		
Melting point / freezing point °F	-30 °C / -22 °F		
Boiling point / boiling range	No information available		
Flash point	39 °C / 102 °F	ASTM D 5095	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limit in Air			
Upper flammability limit:	No information available		
Lower flammability limit:	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Specific gravity	0.871		
Water solubility	negligible		
Solubility in other solvents	No information available		
Partition coefficient	No information available		
Autoignition temperature	No information available		
Decomposition temperature	No information available		
Kinematic viscosity	No information available		
Dynamic viscosity	No information available		

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Incompatible with oxidizing agents.

Hazardous decomposition products

Carbon oxides. Unidentified organic compounds.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information May be fatal if swallowed and enters airways

Inhalation	Avoid breathing vapors or mists.
Eye contact	Avoid contact with eyes.
Skin Contact	Avoid contact with skin.
Ingestion	Do not taste or swallow.

Component Information

Chemical name	LD50/Oral	LD50/Dermal	Inhalation LC50
Distillates, Petroleum, Hydrotreated Light 64742-48-9	> 6000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	> 8500 mg/m ³ (Rat) 4 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Dibutyltin Dilaurate 77-58-7	= 45 mg/kg (Rat)	= 630 mg/kg (Rabbit)	

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May be fatal if swallowed and enters airways. Causes skin irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3	-	Group 3	-	-
Ethylbenzene 100-41-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity May damage fertility or the unborn child.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown acute toxicity 20% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 3404 mg/kg
ATEmix (dermal) 3273 mg/kg mg/l
ATEmix (inhalation-dust/mist) 11.1 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Distillates, Petroleum, Hydrotreated Light 64742-48-9	-	2200: 96 h Pimephales promelas mg/L LC50	-	-
Toluene 108-88-3	12.5: 72 h Pseudokirchneriella	11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50	-	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static

	subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50	static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 12.6: 96 h Pimephales promelas mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 54: 96 h Oryzias latipes mg/L LC50 static		11.5: 48 h Daphnia magna mg/L EC50
Ethylbenzene 100-41-4	1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 9.6: 96 h Poecilia reticulata mg/L LC50 static	-	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Toluene 108-88-3	2.7
Ethylbenzene 100-41-4	3.2

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container.

US EPA Waste Number

D001

14. TRANSPORT INFORMATION

DOT	Not regulated (If shipped in NON BULK packaging by ground transport)
UN number	UN1866
UN proper shipping name	Resin Solution
Transport hazard class(es)	3
Packing group	III

IATA	
UN number	UN1866
UN proper shipping name	Resin Solution
Transport hazard class(es)	3
Packing group	III

IMDG	
UN number	UN1866
UN proper shipping name	Resin Solution
Transport hazard class(es)	3
Packing group	III

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
1,2,4-trimethylbenzene - 95-63-6	95-63-6	1 - 5	1.0
Xylene - 1330-20-7	1330-20-7	1 - 5	1.0
Ethylbenzene - 100-41-4	100-41-4	0.1 - 1	0.1

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	X	X
Ethylbenzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Toluene 108-88-3	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
Ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product is not available in California

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Stoddard Solvent 8052-41-3	X	X	X
1,2,4-trimethylbenzene 95-63-6	X	X	X
Xylene 1330-20-7	X	X	X
Cumene 98-82-8	X	X	X
Ethylbenzene 100-41-4	X	X	X

16. OTHER INFORMATION

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and chemical properties -
HMIS	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection X

Prepared By Regulatory Department

Issuing Date 05-Jan-2015

Revision date 09-Oct-2025

Revision Note

SDS sections updated 3 6 7 11

Disclaimer

The information contained on the Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

End of Safety Data Sheet