



PROSOCO®

Enviro Klean®

NEXT GENERATION CLEANERS

ReVive

Enviro Klean® ReVive removes mold and mildew staining and atmospheric staining that disfigures and degrades many types of construction materials. ReVive is a highly efficient alternative to aggressive cleaners traditionally used on interior and exterior masonry, stone and tile surfaces.

Simply dilute with clean water as directed, and apply ReVive to the surface. A short contact time, gentle scrubbing and a water rinse are normally enough to remove light-to-moderate soiling and staining typically encountered on building surfaces and monuments. Enviro Klean® ReVive can also be applied safely to non masonry substrates such as wood, painted surfaces, metal, plastic and glass.

ADVANTAGES

- Safe for landscape plantings and grass.
- Safe for interior use in occupied buildings.
- Effective on all types of stone, concrete and brick masonry.
- Non-fuming, low-odor formulation.
- Needs no substrate neutralization.
- Minimal precautions required for handling and storage.
- Easy to apply with brush, roller or coarse spray.
- Biodegradable.
- Concentrated for economy.
- Safe and effective on wood, painted surfaces, metal, glass and plastic.

Limitations

- For removal of heavy biological or atmospheric soiling, consult your PROSOCO representative, or call Customer Care toll-free at (800) 255-4255.

REGULATORY COMPLIANCE

VOC Compliance

Enviro Klean® ReVive is compliant with all national, state and district VOC regulations.

TYPICAL TECHNICAL DATA

FORM	Clear, slight amber liquid Low odor
SPECIFIC GRAVITY	1.00
pH	5.5–6.5
WT/GAL	8.34 lbs
FREEZE POINT	32° F (0° C)
SHELF LIFE	3 years in tightly sealed, unopened container
SOLUBILITY IN WATER	Complete

SAFETY INFORMATION

Always read full label and SDS for precautionary instructions before use. Use appropriate safety equipment and job site controls during application and handling.

24-Hour Emergency Information:
INFOTRAC at 800-535-5053

PREPARATION

Protect people, vehicles, property and all surfaces not set for cleaning from product, splash, rinse, residue, fumes and wind drift. Protect and/or divert traffic if needed.

Drain water from architectural structures (such as fountains) before application. Carefully brush or scrape loose surface debris, and heavy growths of moss, ivy, or other contaminants from the dry surface.

Fragile or Deteriorated Surfaces

Fragile or deteriorated stone may require reduced rinsing pressure, or even stone consolidation to avoid further damage.

Severely deteriorated limestone and marble may be strengthened enough for thorough cleaning by treatment with PROSOCO's HCT. HCT also prolongs the service life of acid-soluble stone by dramatically increasing its resistance to acid rain. Consult your

Product Data Sheet

Enviro Klean® ReVive

PROSOCO representative, or call Customer Care toll-free at (800) 255-4255 for more information on use of HCT in conjunction with ReVive.

Surface and Air Temperatures

Cleaning effectiveness is reduced when surface and air temperatures fall below 50°F (10°C). Do not apply at temperatures below 40°F (4°C). If freezing conditions exist before application, let masonry thaw.

Equipment

Apply using a soft-bristled brush, roller or coarse spray. Rinse with enough water and pressure to flush spent cleaner and dissolved soiling from the masonry surface and surface pores without damage. Inadequate rinsing leaves residues which may stain the cleaned surface.

Masonry-washing equipment generating 400–1000 psi with a water flow rate of 6–8 gallons per minute is the best water/pressure combination for rinsing porous masonry. Use a 15–45° fan spray tip. Heater water (150–180°F; 65–82°C) may improve cleaning efficiency.

Use adjustable equipment for reducing water flow rates and rinsing pressure as needed for sensitive surfaces. Rinsing pressures greater than 1000 psi and fan spray tips smaller than 15° may permanently damage sensitive masonry. Water flow rates less than 6 gpm may reduce cleaning productivity and contribute to uneven cleaning results.

Storage and Handling

Store in a cool, dry place. Always seal container after dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperature of 45–100°F (7–38°C). Keep from freezing. Do not double stack pallets. Dispose of in accordance with local, state and federal regulations.

APPLICATION

Read Preparation and the Safety Data Sheet before use.

ALWAYS TEST a small area of each surface to confirm suitability, coverage rate and desired results before beginning overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application. Let surface dry thoroughly before inspection.

NOTE: Many types of biological soiling change color when exposed to ReVive. Most surface discoloration will disappear soon after thorough water rinsing and weathering.

Dilution & Mixing

Adjust dilution rate based on testing. Always pour cold water into empty bucket first, then carefully add product.

Type of Soiling *Concentrate : Water*

- Light biological staining 1:10
- Moderate biological staining 1:5
- Heavy biological staining use in concentrate

Typical Coverage Rates

Coverage rates vary based on surface texture, weather conditions at time of application and the severity of soiling.

- 1-gallon of diluted ReVive treats 80–240 sq.ft.
- 1-gallon of diluted ReVive treats 7–22 sq.m.

Application Instructions

1. Working from the bottom to the top, apply generously to dry surface until surface is thoroughly wet.
2. Leave on the surface for 2–3 minutes. If needed, apply more to keep the surface wet.
3. Mist treated surfaces with water and gently scrub with a non-metallic, short-fibered scrub brush to loosen biological soiling.
4. Working from the bottom to the top, rinse thoroughly with clean water. Reduce rinsing pressure as needed for fragile or deteriorated stone. See Fragile or Deteriorated Surfaces in Preparation section.
5. If used on food-contact surfaces (such as, but not limited to picnic benches or bench-table combos, food-stand counters, eating- or food-preparation surfaces, etc.) a potable water rinse must follow cleaning.

It may take several days for the full cleaning effect to be realized. When practical, allow two or more weeks for biological soiling to disappear. Repeat as necessary to remove remaining biological soiling.

Cleanup

Clean tools and equipment with fresh water.

Product Data Sheet

Enviro Klean® ReVive

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability

for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care – technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Field visits by PROSOCO personnel are for the purpose of making technical recommendations only. **PROSOCO is not responsible for providing job-site supervision or quality control.** Proper application is the responsibility of the applicator. Call Customer Care at 800-255-4255, or visit our website at prosoco.com, for the name of the PROSOCO representative in your area.