

CEMENT & CONCRETE PRODUCTS™

BLACKTOP CRACK SEAL

PRODUCT NOS. 8640-05

PRODUCT DESCRIPTION

QUIKRETE® Blacktop Crack Seal is uniformly blended latex e formulated to fill cracks in horizontal asphalt surfaces.

PRODUCT USE

QUIKRETE® Blacktop Crack Seal is formulated to fill cracks on any horizontal asphalt surface. Blacktop Crack Seal will also bond to concrete. There is nothing to add. Just shake the ready-to-use product and pour directly from the container. The product blends in with the natural charcoal color of aged blacktop.



• QUIKRETE® Blacktop Crack Seal is available in 5.5 ounce (163 ml) squeeze tubes, one quart (946 ml) and one gallon (3.8 L) plastic bottles.

YIELD

• One quart (946 ml) bottle will fill a 1/4" x 1/2" (6 x 12 mm) crack 38' (11.6 M) long

INSTALLATION

SURFACE PREPARATION

Shake well before using. Clean all loose dirt, dust and gravel from the crack. Surfaces to receive Blacktop Crack Seal should be free of oil and grease. Cleaning with QUIKRETE® Concrete & Asphalt Cleaner (#8601) is recommended to insure the best bond. If the crack is deeper than ½" (6 mm), use backer rod or sand to fill the crack to within ½" (6 mm) of the surface.

APPLICATION

Cut the tip of the spout to make a ¼" (6 mm) to 3/8" (9 mm) hole. Squeeze Blacktop Crack Seal into the crack, over-filling slightly to allow for shrinkage. A second coat can be applied after 24 hours as needed to provide a uniform finished surface.



PRECAUTIONS

• Do not apply in cracks wider than ½" (12 mm). Temperature should be between 45°F and 100°F (7°C and 38°C). Keep product from freezing. Do not apply if rain is expected within 24 hours. Do not apply to surfaces which will later be coated with anything other than acrylic water-based paint.

WARRANTY

NOTICE: Obtain the applicable LIMITED WARRANTY: at

www.quikrete.com/product-warranty or send a written request to The Quikrete Companies, LLC, Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of The Quikrete Companies, LLC. © 2018 Quikrete International, Inc.

DIVISION 32

Flexible Pavement Repair 32 01 17

^{*} Refer to www.quikrete.com for the most current technical data, MSDS, and guide specifical