



## 2-PART EPOXY KIT

# GARAGE FLOOR COATING

PRODUCT NOS. 0703-57 GRAY, 0703-58 TAN

### PRODUCT DESCRIPTION

QUIKRETE® 2-Part Epoxy Kit Garage Floor Coating is an advanced formula, water-based epoxy for long lasting performance as a garage floor coating.

- Showroom high-gloss finish with exceptional durability.
- Superior adhesion eliminates hot-tire pick up.
- Ready to use immediately after mixing.

### PRODUCT USE

QUIKRETE® 2-Part Epoxy Kit Garage Floor Coating beautifies and protects:

- Garage floors
- Basement floors
- Indoor floors
- Bare concrete
- Painted concrete (if paint is secure and is not oil based).

QUIKRETE® 2-Part Epoxy Kit Garage Floor Coating is available in Gray (-57) and Tan (-58). Each 2-Part Epoxy Kit contains Part A (Activator), Part B (Resin), QUIKRETE® Cleaner, Etcher & Degreaser (No. 8675), and QUIKRETE® 2-Part Epoxy Kit Garage Floor Coating Color Flakes (No. 6200).

### COVERAGE

One kit (Net 120 fl.oz. (3.55 L)) will cover a one-car garage, 220-280 sq.ft. (20-26 M<sup>2</sup>) depending on surface porosity. Typically, a one-car garage is 240 sq.ft. (22 M<sup>2</sup>) and a two-car garage is 420 sq.ft. (39 M<sup>2</sup>).

### DRY TIMES

Light foot traffic and the return of light items to garage is acceptable next day. Drive on time is 3 days. It is recommended to observe the effect of placing the first items before proceeding, because times will be longer at lower temperatures and higher humidity.

### REQUIRED OR RECOMMENDED EQUIPMENT

Plastic bucket, plastic watering can, water hose, plastic drop cloth, paint tape, acid resistant nitrile or neoprene gloves, rubber boots, goggles, long handled brush with uncolored polypropylene or natural fibers, long handled squeegee, putty knife, paint tray, paint tray liner, 1/4" nap mohair (NOT foam) paint roller with extension handle, 2 to 4 inch wide quality paint brush, and a variable speed electric drill with paint mixer attachment (recommended). Consider having sand or cat litter available for control of a spill of the QUIKRETE® Cleaner, Etcher & Degreaser or the epoxy. Other materials may be required for special application situations and are described in the instruction booklet.

## DIVISION 3

Concrete Coating  
03 36 00  
High Performance  
Coating  
09 96 00  
Coatings for Concrete &  
Masonry  
09 98 00



Pretreat oil stains on uncoated concrete with QUIKRETE® Concrete Oil Stain Remover (No. 8670-06.)

QUIKRETE® 2-Part Epoxy Kit Epoxy High Gloss Coating (No. 0703-55) may be coated over the Garage Floor Coating for a showroom finish.

### STORAGE AND DISPOSAL

Do not freeze. If frozen do not use. Keep containers closed when not in use. Store between 40°F and 90°F (4°C and 32°C). In case of spill, absorb with inert material such as sand or kitty litter. Dispose of used absorbent, container and unused contents in accordance with local, state and federal regulations.

VOC for Part A, Part B and combined Epoxy product each contain less than 50 g/L of VOC less water and less exempt compounds. VOC for Cleaner, Etcher & Degreaser = 0.55 g/L per EPA Method 24; Vapor Pressure of VOC < 2.7 mm Hg @ 20°C. Meets VOC requirements in all locations.

### INSTRUCTIONS PROVIDED

A detailed instruction booklet is included in each kit, which is also available at [www.quikrete.com](http://www.quikrete.com) along with Safety Data Sheets. Read the complete application and safety instructions before beginning project. Instructions provide information for a variety of topics:

- Coating over existing paint
- Dealing with existing sealers
- Dealing with oil stains
- Tips for best results

### GENERAL INSTRUCTIONS

- Wear nitrile gloves and clean up while wet.
- Apply between 50 and 90°F (10 and 32°C).

- Do not apply if rain, heavy dew, or temperatures outside of 50 to 90°F (10 to 32°C) are expected within 24 hours.
- Do not apply where water is passing up through the concrete
- Epoxy coatings are not recommended for outdoor applications, such as driveways.
- Concrete and concrete repairs must be cured for 30 days before the application of epoxy.
- Oil based paints are not recommended for concrete and epoxy should not be applied over oil based paints.
- QUIKRETE® Cleaner, Etcher & Degreaser (No. 8675) is included in the 2-Part Epoxy Kit. It provides heavy-duty surface preparation and requires wearing gloves and boots and taking other safety precautions.
- Care of Finished Coating: Test any solvents or cleaners, especially cleaners containing pine or citrus, in a small area before using; they may affect appearance.
- Read complete instructions including safety before beginning project.

**KEEP OUT OF REACH OF CHILDREN**

**WARNING:** Eye and skin irritant. Possible sensitizer to skin.

**Contains Cleaner, Etcher & Degreaser for surface preparation:  
DANGER! CORROSIVE! CAN CAUSE SERIOUS INJURY TO SKIN  
AND EYES.**

For more information, refer to Safety Data Sheets (SDS) online at [www.quikrete.com](http://www.quikrete.com). Detailed safety instructions are also printed in the Instruction Brochure included in every kit.

**WARRANTY**

The QUIKRETE® Companies, Inc. warrant this product to be of merchantable quality when used or applied in accordance with the instructions hereon. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is LIMITED to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing at One Securities Centre, 3490 Piedmont Rd., Suite 1300, Atlanta, GA 30305. THIS WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESS WARRANTIES AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES.