

Stucco Selector Guide

Stucco Products

One Coat Fiberglass Reinforced Stucco
(No. 1200-80)



Base Coat Pump Grade
(No. 1139-86)



Scratch & Brown Base Coat
(No. 1139-80)



Scratch & Brown Base Coat with Fibers
(No. 1139-78)



Foam Coating
(No. 1219-82) White
(No. 1219-81) Gray



Finish Coat
(No. 1201-80) White
(No. 1202-80) Gray



	Fiberglass Reinforced One Coat System	Pumpable Scratch Scratch & Brown Coat	Scratch & Brown Coat	Fiberglass Reinforced Scratch & Brown Coat	Polymer Modified	Color & Texture Finish Coat
Application	One Coat application per IAPMO ER-455 Minimum 3/8 in thickness Scratch & Brown Coats in a traditional Three Coat application Trowel or Spray applied	Minimum 3/8 in thickness Trowel or Spray applied Use for Scratch and Brown Coats in a Three Coat Application Use for Base Coat in a Two Coat Application	Minimum 3/8 in thickness Use for Scratch & Brown Coats in a Three Coat Application Use for Base Coat in a Two Coat application	Minimum 3/8 in thickness Use for Scratch and Brown Coats in a Three Coat application. Use for Base Coat in a Two Coat application	Base Coat: Minimum 1/4 in thick Crack Isolation System: 1/16 in thick	Finish Coat: Minimum 1/8 in thickness
Attributes	<ul style="list-style-type: none"> Alkali Resistant Fiberglass Reinforced 1 Hour Fire Rating over EPS Foam & Plywood When Applied per IAPMO ES ER-455 Factory Pre-blended Mix Concentrated version available Meets ASTM C926 	<ul style="list-style-type: none"> Alkali Resistant Fiberglass Reinforced Factory Pre-blended Mix Meets ASTM C926 	<ul style="list-style-type: none"> Alkali Resistant Fiberglass Reinforced Can be Trowel or Spray Applied Meets ASTM C926 	<ul style="list-style-type: none"> Alkali Resistant Fiberglass Reinforced Can be Trowel or Spray Applied Low Sag Factory Pre-blended Mix Meets ASTM C926 	<ul style="list-style-type: none"> Polymer Modified to Bond Directly to Foam Panels Without Wire Reinforcement or Fiberglass Fabric Can be trowel or spray applied Factory Pre-blended Mix Colors: Gray & White 	<ul style="list-style-type: none"> Color & Texture Coat Integral Color Can be Added to Mix Factory Pre-Blended Mix Colors: Gray & White Meets ASTM C926
Coverage (per 80 lb (36.2 kg) bag)	20 ft ² to 24 ft ² (1.8 m ² to 2.2 m ²) at 3/8 in (9.5 mm) 15 ft ² to 18 ft ² (1.4 m ² to 1.7 m ²) at 1/2 in (13 mm)	20 ft ² to 24 ft ² (1.8 m ² to 2.2 m ²) at 3/8 in (9.5 mm) 15 ft ² to 18 ft ² (1.4 m ² to 1.7 m ²) at 1/2 in (13 mm)	20 ft ² to 24 ft ² (1.8 m ² to 2.2 m ²) at 3/8 in (9.5 mm) 15 ft ² to 18 ft ² (1.4 m ² to 1.7 m ²) at 1/2 in (13 mm)	20 ft ² to 24 ft ² (1.8 m ² to 2.2 m ²) at 3/8 in (9.5 mm) 15 ft ² to 18 ft ² (1.4 m ² to 1.7 m ²) at 1/2 in (13 mm)	100 ft ² to 103 ft ² (9.3 m ² to 9.5 m ²) at 1/16 in (1.6 mm) thick 24 ft ² to 27 ft ² (2.2 m ² to 2.5 m ²) at 1/4 in (6.3 mm) thick	70 ft ² (6.5 m ²) at 1/8 in (3.2 mm) thick

Application						
Scratch Coat	•	•	•	•		
Brown Coat	•	•	•	•		
Apply Directly to Masonry Walls	•	•	•	•	•	
Finish Coating						•
Apply Directly to Concrete	•	•	•	•	•	
Crack Isolation					•	

For Data Sheets and Guide Specification documents for our Commercial Grade products, please visit our "FOR THE PRO" section at www.quikrete.com