

SUBMITTAL SHEET Tech Support: 305.634.0012

PRODUCT CATEGORY: STRUCTURAL TRACK

COATING: G60/G90 Available

PHYSICAL PROPERTIES

PRODUCT NUMBER:

 WEB DEPTH:
 3.625 IN

 FLANGE HEIGHT:
 2.000 IN

 DESIGN THICKNESS:
 0.0346 IN

 YIELD:
 33 KSI

 WEIGHT:
 0.9 LB/LET



**EFFECTIVE SECTION PROPERTIES** 

# **GROSS SECTION PROPERTIES**

# CROSS SECTIONAL AREA (A): 0.264 $\,$ IN $^2$ MOMENT OF INERTIA (IX): $\frac{0.464}{\,$ IN $^4$ MOMENT OF INERTIA (IX): 0.619 $\,$ IN $^4$ SECTION MODULUS (SX): 0.19 $\,$ IN $^3$ SECTION MODULUS ABOUT X-X AXIS (STRONG AXIS) (SX): 0.329 $\,$ IN $^3$ ALLOWABLE BENDING MOMENT (Ma): $\frac{0.464}{\,}$ IN $^4$ SECTION MODULUS (SX): $\frac{0.464}{\,}$ IN $^4$ SECTION MODULUS (SX): $\frac{0.329}{\,}$ IN $^3$ ALLOWABLE BENDING MOMENT (Ma): $\frac{0.464}{\,}$ IN $^4$ SECTION MODULUS (SX): $\frac{0.464}{\,}$ IN $^4$ SECTION MODULUS (SX): $\frac{0.464}{\,}$ IN $^4$ IN $^$

362T200-33

RADIUS OF GYRATION (Rx): 1.533 IN GROSS MOMENT OF INERTIA (Iy): 0.11  $\,$  IN $^4$  GROSS RADIUS OF GYRATION (Ry): 0.645  $\,$  IN

### TORSIONAL PROPERTIES

ST VENANT TORSION CONSTANT (J x 1000):	0.1052 IN <sup>4</sup>
WARPING CONSTANT (Cw):	0.269 IN <sup>6</sup>
DISTANCE FROM SHEAR CENTER TO NEUTRAL AXIS (X0):	-1.27 IN
RADII OF GYRATION (Ro):	2.092 IN
TORSIONAL FLEXURAL CONSTANT (B):	0.631

## SECTION PROPERTIES TABLE NOTES:

- 1. CALCULATED PROPERTIES ARE BASED ON AISI S100-16, NORTH AMERICAN SPECIFICATION FOR DESIGN OF COLD-FORMED STEEL STRUCTURAL MEMBERS.
- 2. THE CENTERLINE BEND RADIUS IS BASED ON INSIDE CORNER RADII SHOWN IN THICKNESS CHART.
- 3. EFFECTIVE PROPERTIES INCORPORATE THE STRENGTH INCREASE FROM THE COLD WORK OF FORMING AS APPLICABLE PER AISI A3.3.2.
- 4. TABULATED GROSS PROPERTIES ARE BASED ON FULL-UNREDUCED CROSS SECTION OF THE STUDS, AWAY FROM PUNCHOUTS.
- 5. FOR DEFLECTION CALCULATIONS, USE THE EFFECTIVE MOMENT OF INERTIA.
- 6. ALLOWABLE MOMENT INCLUDES COLD-WORK OF FORMING.
- 7. FOR THE STEELS THAT HAVE BOTH 33 AND 50 KSI LISTING, IF THE DESIGN IS BASED ON 50 KSI, THE 50 KSI STEEL NEEDS TO BE SPECIFIED. Example.362S162-54 (50KSI)
- 8. WEB DEPTH FOR TRACK SECTIONS IS EQUAL TO THE NOMINAL HEIGHT PLUS 2 TIMES THE DESIGN THICKNESS PLUS THE BEND RADIUS. HEMS ON NONSTRUCTURAL RACK SECTIONS ARE IGNORED.

# LEED:

- COMPLIES WITH ASTM C955
- LEED CREDITS MR 2: CONSTRUCTION WASTE MATERIAL-RAM STEEL FRAMING IS 100% RECYCLEABLE
- LEED CREDITS MR 4: RAM STEEL FRAMING IS FORMED WITH A MINIMUM 25.5% POST CONSUMER AND 14.4% PRE-CONSUMER CONTENT
- LEED CREDITS MR 5: REGIONAL MATERIALS MAY APPLY