

PRODUCT CATEGORY: ProTRAK
PRODUCT NUMBER: 600PDT125-18
COATING: G40 (G60/G90 Available)



PHYSICAL PROPERTIES

WEB DEPTH: 6.000 IN
FLANGE HEIGHT: 1.250 IN
DESIGN THICKNESS: 0.019 IN
YIELD: 50 KSI
WEIGHT: 0.55 LB/LFT

GROSS SECTION PROPERTIES

CROSS SECTIONAL AREA (A): 0.161 IN²
MOMENT OF INERTIA (Ix): 0.778 IN⁴
RADIUS OF GYRATION (Rx): 2.195 IN
GROSS MOMENT OF INERTIA (Iy): 0.019 IN⁴
GROSS RADIUS OF GYRATION (Ry): 0.342 IN

EFFECTIVE SECTION PROPERTIES

EFFECTIVE AREA (Ae): 0.029 IN²
MOMENT OF INERTIA (Ix): 0.469 IN⁴
SECTION MODULUS (Sx): 0.083 IN³
ALLOWABLE BENDING MOMENT (Ma): 2473 IN-LBS
ALLOWABLE SHEAR FORCE (Vag): 102 LB

TORSIONAL PROPERTIES

ST VENANT TORSION CONSTANT (J x 1000): 0.01943 IN⁴
WARPING CONSTANT (Cw): 0.13 IN⁶
DISTANCE FROM SHEAR CENTER TO NEUTRAL AXIS (Xo): -0.523 IN
RADI OF GYRATION (Ro): 2.282 IN
TORSIONAL FLEXURAL CONSTANT (B): 0.947

SECTION PROPERTIES TABLE NOTES:

- CALCULATED PROPERTIES ARE BASED ON AISI S100-12, NORTH AMERICAN SPECIFICATION FOR DESIGN OF COLD-FORMED STEEL STRUCTURAL MEMBERS AND AISI S220-15, NORTH AMERICAN STANDARD FOR COLD-FORMED STEEL FRAMING&ldquoNONSTRUCTURAL MEMBERS.
- EFFECTIVE PROPERTIES INCORPORATE THE STRENGTH INCREASE FROM THE COLD WORK OF FORMING AS APPLICABLE PER AISI A7.2.
- TABULATED GROSS PROPERTIES, INCLUDING TORSIONAL PROPERTIES, ARE BASED ON FULL-UNREDUCED CROSS SECTION OF THE STUDS, AWAY FROM PUNCHOUTS
- TABULATED GROSS PROPERTIES, INCLUDING TORSIONAL PROPERTIES, ARE BASED ON FULL-UNREDUCED CROSS SECTION OF THE TRACKS.
- FOR DEFLECTION CALCULATIONS, USE THE EFFECTIVE MOMENT OF INERTIA.
- ALLOWABLE MOMENT INCLUDES COLD WORK OF FORMING.
- ALLOWABLE MOMENT IS TAKEN AS THE LOWEST VALUE BASED ON LOCAL OR DISTORTIONAL BUCKLING. DISTORTIONAL BUCKLING STRENGTH IS BASED ON A K-PHI = 0.
- WEB DEPTH FOR TRACK SECTIONS IS EQUAL TO THE NOMINAL HEIGHT PLUS TWO TIMES THE DESIGN THICKNESS PLUS THE BEND RADIUS. HEMS ON NONSTRUCTURAL TRACK SECTIONS ARE IGNORED

LEED:

- COMPLIES WITH ASTM C955
- LEED CREDITS MR 2: CONSTRUCTION WASTE MATERIAL-RAM STEEL FRAMING IS 100% RECYCLEABLE
- LEED CREDITS MR 4: RAM STEEL FRAMING IS FORMED WITH A MINIMUM 25.5% POST CONSUMER AND 14.4% PRE-CONSUMER CONTENT
- LEED CREDITS MR 5: REGIONAL MATERIALS MAY APPLY