



A CSW Industrials Company

# RECTORSEAL® COLD GALVANIZING

Zinc metal coating

## Description

RectorSeal® Cold Galvanizing Spray provides the protection of hot-dip galvanizing plus the convenience of on the job aerosol application.

RectorSeal Cold Galvanizing Spray contains 95% pure zinc and forms a tough, durable, and flexible zinc metal coating that bonds electrochemically with the base metal to protect against rust and corrosion.

## Characteristics | Features

- 95% pur zinc
- Quick Drying
- Use indoor and outdoors
- Permanent, flexible
- Electrochemcial bond
- Stops rust and corrosion on any iron or steel surface
- Minimal surface preparation

RectorSeal® Cold Galvanizing Spray is in full compliance with the following Military Specifications:  
MIL-P-26915C (USAF)   MIL-P-46105 (MR)   MIL-P-21035B (Navy)

## Applications

Excellent for use on HVAC units to protect exposed sheet metal edges after cutting and installing of duct work and equipment.

May be used indoors or outdoors to prevent and retard rust and corrosion on welded joints, fencing, storage tanks, pipe lines, metal buildings, marine and other similar applications.

## Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet per Case
86625	16 ounce aerosol	12	17	0.632

## Instructions

### READ ALL DIRECTIONS, SDS AND WARNINGS ON LABEL BEFORE USING

1. Surfaces to be coated must be clean, dry and free of severe rust and loose scale.
2. Shake can well for 1 to 2 minutes before spraying. Repeat often during application.
3. Wear protective eyewear when spraying and point spray nozzle away from face.
4. Hold spray can upright about 10" to 12" from surface and apply thin, even coats with consistent back and forth motion. Allow 15 minutes to dry between coats and 6 hours to dry before top coating.
5. After use, or if spray spatters, turn can upside down and spray to clear nozzle.
6. Protect surrounding surfaces from overspray.

For additional technical information, call Toll Free 1-800-231-3345

# COLD GALVANIZING

## Precautions

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,  
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

**DANGER!**  
**EXTREMELY FLAMMABLE**  
**CONTENTS UNDER PRESSURE.**  
**VAPOR HARMFUL – KEEP OUT OF REACH OF CHILDREN**  
**READ BACK PANEL CAREFULLY.**

**CONTAINS: Zinc Dust, Xylene, Propane & Toluene.** Vapors may ignite explosively. Prevent build-up of vapors. Keep from sparks, heat, flame or other heat sources. Do not smoke. Turn off pilot lights, stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection or leave area. Avoid contact with skin or eyes. **FIRST AID:** In case of exposure, contact physician immediately. **Eyes** – Hold eyes open and rinse gently with water for 15 minutes. **Skin** – Remove contaminated clothing immediately. Rinse skin with plenty of water for 15 minutes. **Ingestion** – DO NOT INDUCE VOMITING. Only if conscious, give large amounts of water. **Inhalation** – Remove to Fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. **Use With Adequate Ventilation. KEEP OUT OF REACH OF CHILDREN.**



**WARNING:** This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects and other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**For additional information, refer to Safety Data Sheet.**

## Specifications

Flash Point SETA CC	None
Color	Colorless
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

## Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by  
**RectorSeal, LLC**  
2601 Spenwick Drive • Houston, TX 77055 USA  
713-263-8001 • Fax 713-263-7577  
Toll-free 800-231-3345 • Fax 800-441-0051

RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice.