



A CSW Industrials Company

PRODUCT DATA SHEET

RECTORSEAL® COLD GALVANIZING Zinc metal coating

Description

RectorSeal® Cold Galvanizing Spray provides the protection of hot-dip galvanizing plus the convenience of on the job aerosol application.

RectorSeal Cold Galvanizing Spray contains 95% pure zinc and forms a tough, durable, and flexible zinc metal coating that bonds electrochemically with the base metal to protect against rust and corrosion.

Applications

Excellent for use on HVAC units to protect exposed sheet metal edges after cutting and installing of duct work and equipment.

May be used indoors or outdoors to prevent and retard rust and corrosion on welded joints, fencing, storage tanks, pipe lines, metal buildings, marine and other similar applications.

Instructions

READ ALL DIRECTIONS, SDS AND WARNINGS ON LABEL BEFORE USING

1. Surfaces to be coated must be clean, dry and free of severe rust and loose scale.
2. Shake can well for 1 to 2 minutes before spraying. Repeat often during application.
3. Wear protective eyewear when spraying and point spray nozzle away from face.
4. Hold spray can upright about 10" to 12" from surface and apply thin, even coats with consistent back and forth motion. Allow 15 minutes to dry between coats and 6 hours to dry before top coating.
5. After use, or if spray spatters, turn can upside down and spray to clear nozzle.
6. Protect surrounding surfaces from overspray.

For additional technical information, call Toll Free 1-800-231-3345



Characteristics | Features

- 95% pur zinc
- Quick Drying
- Use indoor and outdoors
- Permanent, flexible
- Electrochemical bond
- Stops rust and corrosion on any iron or steel surface
- Minimal surface preparation

RectorSeal® Cold Galvanizing Spray is in full compliance with the following Military Specifications:

- MIL-P-26915C (USAF)
- MIL-P-46105 (MR)
- MIL-P-21035B (Navy)

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
86625	16 ounce aerosol	12	17	0.63

RECTORSEAL® COLD GALVANIZING

Zinc metal coating

Specifications

Flash Point SETA CC	None
Color	Colorless
Shelf Life	1 year

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.


Precautionary Statements

Refer to Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

For additional Technical Information Call Toll Free 1-800-231-3345

 **WARNING:** This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects and other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Limited Warranty



For more information on our product limited warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2025 RectorSeal. All rights reserved. R50192-0125