



A CSW Industrials Company

PRODUCT DATA SHEET

CON-COIL™

Max strength, high foam condenser coil cleaner

Description

Con-Coil is an acid-based foaming brightener and cleaner that lifts obstructing contaminants such as bugs, cottonwood, grass, lint, dirt and oxides from coils, pushes contaminants and grease out of areas of the coil which are normally inaccessible, to where they can be rinsed away with low pressure water. Leaves aluminum surfaces clean in less than five minutes. Suitable for air cooled condenser coils and can be used for cleaning electronic air filters. Con-Coil not only leaves the aluminum surfaces of electronic air filters bright and shiny, but also completely clean and insulation-free within five minutes.

READ ALL SDS, DIRECTIONS AND WARNINGS ON LABEL BEFORE USE



Directions for Use:

1. Appropriately dilute with water for economic use.
Extremely dirty coils - 1 part CON-COIL to 3 parts water.
Moderately dirty coils - 1 part CON-COIL to 4 parts water.
Lightly dirty coils - 1 part CON-COIL to 6 parts water.
2. Shut off system.
3. Spray the diluted Con-Coil™ on accessible areas. Use a low pressure all plastic sprayer.
4. Wait 30 seconds and spray again.
5. To penetrate a multi-bank coil spray again in 2 minutes.
6. Allow 5 minutes for full cleaning action.
7. Rinse coils and surrounding area off with water.

Characteristics | Features

- Commercial strength
- Acid-based
- Biodegradable*
- High foaming action
- Brightens and degreases
- Concentrated – dilute with water for economical use
- Leaves aluminum surfaces not only bright and shiny, but completely clean and free of particulate matter in less than 5 minutes
- Will not harm copper or aluminum

*Contains the best available biodegradable surfactants and detergents

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet
82651	Gallon (3.8 L)	4 Bottles	45	1.21

Specifications

Wt/Gal @ 77°F 9.34 lbs./gal.

Flash Point None

Color Pink

Shelf Life 3 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances

Precautionary Statements

Refer to Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

For additional Technical Information Call Toll Free 1-800-231-3345

Limited WarrantyFor more information on our product limited warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC**2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com****3255 Wyandotte St. East • Windsor, ON N8Y 1E9, Canada • 519-966-4901**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2023 RectorSeal. All rights reserved. R50400-0323