



Heating Service Products

Protective maintenance for steam and hot water systems.



RECTORSEAL

HEATING CHEMICALS

Performance. Efficiency. Protection.

Burner



Boiler



Fuel Oil



3YR
LIMITED WARRANTY

Protection for
today's high efficiency
heating systems.

Extended life of older
systems.



Action videos and full details @ rectorseal.com/heating



FUEL OIL DEODORIZERS & ABSORBENTS

Odorgon™ Powder

Code	Description	Qty
68512	1 lb.	12

FEATURES

- Leaves pleasant scent
- Non-explosive / non-flammable

Kills odors and absorbs oil

APPLICATION • Handy for cleaning up after fuel oil spills and leaks • Sifter top for controlled economical usage and clean storage

RECOMMENDED FOR

- Eliminating fuel oil odor and stains on floors and horizontal surfaces



Odorgon™ Spray

Code	Description	Qty
68516	14 oz. aerosol	12

FEATURES

- Non-lingering, mild scent
- Non-flammable

WARNING: This product can expose you to chemicals including Methyl Isobutyl Ketone (MIBK), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Kills odors and absorbs oil

APPLICATION • Kills fuel oil odor in hard to reach corners and vertical surfaces

RECOMMENDED FOR

- Neutralizing fuel oil odor remaining after leak or spill cleanup





BOILER TREATMENTS

Water treatments & sealants for steam and hot water systems

Surgex™

Inhibits scale and corrosion

Code	Description	Qty
68752	1-½ oz.	20
FEATURES • Economical • Concentrated • Sure-cure color indicator		

APPLICATION • Stops active surging in steam and hot water boilers.

• Sure-cure color indicator tints boiler water to take the guesswork out of treatment dosage • Pour into boiler access point.

RECOMMENDED FOR

• Steam and hot water systems



Surgemaster™

Boiler water treatment

Code	Description	Qty
68742	5.3 oz.	12
FEATURES • Will not damage seals and gaskets • Inhibits corrosion • No petroleum distillates • Sure-cure color indicator		

WARNING: This product can expose you to chemicals including Silica, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

APPLICATION • Prevents priming and surging in steam heating systems

• Precipitates impurities and promotes efficiency • Sure-cure color indicator tints boiler water to take the guesswork out of treatment dosage • Pour into boiler access point.

RECOMMENDED FOR

• Steam heating systems





BOILER TREATMENTS

Water treatments & sealants for steam and hot water systems

8-Way™

Water treatment for steam & hot water systems

Code	Description	Qty
68712	1 qt.	12
68714	1 gal.	4

FEATURES

- Will not damage seals and gaskets
- Non-chromate; biodegradable*
- No petroleum distillates
- Sure-cure color indicator

* Contains the best available biodegradable surfactants and detergents.

WARNING: Not compatible with aluminum

APPLICATION • Builds alkalinity • Controls pH
 • Removes sludge • Removes rust scale • Inhibits boiler corrosion • Inhibits steam line corrosion • Prevents oxygen pitting • Inhibits lime scale • Prevents surging and foaming
 • Sure-cure color indicator tints boiler water to take the guesswork out of treatment dosage • Pour directly into boiler or pump into drain valve using force pump.

RECOMMENDED FOR

- Protective maintenance for steam and hot water systems.



▲ Force pump drain line injection





LEAK LOCATORS

Better Bubble™

Code	Description	Qty
65554	8 oz. - dauber top	12
65432	32 oz. - trigger spray	12
65273	1 gal.	4

FEATURES

- Fast acting
- Long lasting
- Easy to see bubbles
- Continuous bubbling

Gas leak locator

APPLICATION • Thick formula pinpoints the smallest natural gas, LPG and A/C refrigerant leaks with well defined elastic bubbles that stand up under pressure and windy conditions • Use on surface temperatures from 20°F to 250°F

RECOMMENDED FOR • All types of pipe, tubing, valves, tanks, pressure vessels, condenser / evaporator coils, refrigeration coils, and many other similar applications



RectorSeek™ Low-Temp

Code	Description	Qty
61273	1 gal.	4

FEATURES

- Longer bubbling action
- Spray application
- Easy to apply

Low temperature leak locator

APPLICATION • Leak locator for use on pipes or tanks containing gases at low temperatures • Effective from -35°F to 200°F

RECOMMENDED FOR • All types of pipe (except CPVC), tubing, valves, cylinders, tanks, pressure vessels, condenser / evaporator coils, refrigeration coils and many other similar applications



RectorSeek™ Mid-Temp

Code	Description	Qty
60273	1 gal.	4

FEATURES

- Longer bubbling action
- spray application
- Easy to apply

Mid temperature leak locator

APPLICATION • Leak locator for use at normal temperature on pipe or tanks that contain gases • Can be used on oxygen, air or gas at temperatures between 40°F to 200°F

RECOMMENDED FOR • All types of pipe, tubing, valves, cylinders, tanks, pressure vessels, condenser / evaporator coils, refrigeration coils and many other similar applications





TANKLESS WATER HEATER FLUSH

Calci-free™

Code	Description	Qty
68708	Flush 1.2 lbs.	12



FEATURES

- Restores circulation in 20 minutes
- More effective than vinegar
- Easy to use with no strong odor
- Cleans heat exchanger fast
- Biodegradable*

Tankless water heater flush

APPLICATION • Economical chemical cleaner to restore circulation and pressure in commercial and residential tankless water heaters • Unique combination of organic, inorganic and corrosion inhibiting components

RECOMMENDED FOR • Routine cleaning to remove calcium and other solid deposits from heating coils in tankless water heaters



Calci-free™ Kit

Code	Description	Qty
68711	Kit with 1.2 lbs. flush	1

FEATURES

- A complete cleaning system
- Cleans in only 20 minutes
- Heavy duty, chemical resistant utility pump
- Biodegradable*

Complete tankless water heater flush kit

APPLICATION

• Restores circulation and pressure in commercial and residential tankless water heaters • Cleans heater coils thoroughly

RECOMMENDED FOR • Routine cleaning to remove calcium and other solid deposits from heating coils in tankless water heaters



* Contains the best available biodegradable surfactants and detergents.



STANDARD WATER HEATER FLUSH

Calci-flush™

Standard tank water heater flush

Code	Description	Qty
68707	1 gallon	4



FEATURES

- Removes tank sediment
- Restores water temperature
- More effective than vinegar
- Easy to use with no strong odor
- Biodegradable*

WARNING: This product can expose you to chemicals including Methyl Methanesulfonate, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

APPLICATION • Highly effective chemical cleaner to dissolve and flush standard water heaters and heat exchangers • Unique combination of cleaning and corrosion inhibiting components

RECOMMENDED FOR • Routine cleaning to remove calcium and other solid deposits from tanked water heaters

Adapter allows secure connection and quick application.



* Contains the best available biodegradable surfactants and detergents.

MISCELLANEOUS

EP-200 & 400

Epoxy putty

Code	Description	Qty
97600	2 oz. EP-200 with display	24
97601	2 oz. EP-200 refill	24
97602	2 oz. EP-200 on blister card	12
97606	4 oz. EP-400 boxed	12



FEATURES

- Mixes like putty
- Hardens in minutes
- Can be drilled, tapped, filed, machined, sanded and painted

APPLICATION • Pre-measured, high-grade epoxy and hardener formulated together in one stick
• Break off the amount needed for each repair
• Bonds to most surfaces

RECOMMENDED FOR • Bonding and filling metals and a variety of other materials



Magne-Patch™

Instantly stops small leaks in steel tanks

Code	Description	Qty
68442	Blister card	12

FEATURES

- Provides temporary repair
- Saves time
- Helps avoid serious spills

APPLICATION • A powerful, permanent magnet holds a flexible plug against the hole and against existing pressure
• Quickest tank repair available • Reusable
• Blister packed

RECOMMENDED FOR • For steel tanks holding oil, gasoline, water, and chemicals



blister card ►



Pipe Repair Kit

Quick-fix pipe repair system

Code	Description	Qty
82112	Pipe repair kit	12

FEATURES

- Easy to use, fast setting, durable repair
- Reduces repair cost
- Withstands pressure up to 450 PSI

APPLICATION • Stops leaks on all rigid pipes • Consists of a 2" x 4' knitted fiberglass cloth coated with a water-activated polyurethane resin that adheres to all metal, plastic, fiberglass and concrete piping

RECOMMENDED FOR • Plumbing • Pool
• Spa • Irrigation • HVAC applications





RECTORSEAL PIPE THREAD SEALANTS

RectorSeal No. 5®

● Yellow - multi-purpose pipe thread sealant

Code	Description	Qty
25790	1-¾ oz.	24
25631	¼ pt.	24
25551	½ pt.	24
25431	1 pt.	12
25300	1 qt.	12
25271	1 gal.	4
Canada		
25001	¼ pt.	12
25002	½ pt.	8
25433	1 pt.	12



NSF pipe-dry-seal



US



CLASSIFIED



FEATURES

- Non-hardening / Slow drying
- Lead free
- Smooth application
- 2 year shelf life
- Certified to NSF/ANSI/CAN 61

APPLICATION • Lubricates and protects threaded pipe and fittings • Can be pressurized immediately up to 100 psi for piping up to 2" diameter • Ideal for a wide variety of fluids and gases including potable water

RECOMMENDED FOR

- Galvanized Steel • Iron • Brass • Copper • Aluminum
- Stainless Steel • Polyethylene • RTRP • PVC



RECTORSEAL PIPE THREAD SEALANTS

Continued

RectorSeal T Plus 2®

● White - PTFE enriched pipe thread sealant

Code	Description	Qty
23710	1-¾ oz.	24
23631	¼ pt.	24
23551	½ pt.	24
23431	1 pt.	12
23391	1 qt.	12
Canada		
23001	¼ pt.	12
23002	½ pt.	8
23435	1 pt.	12



FEATURES

- Non-hardening
- Lead free
- 2 year shelf life
- Certified to NSF/ANSI/CAN 61

APPLICATION • Contains PTFE & synthetic fibers for superior performance • Can be pressurized immediately following application

RECOMMENDED FOR

- Galvanized Steel • Iron • Brass • Copper • Aluminum
- Stainless Steel • Polyethylene • RTRP • PVC
- CPVC • ABS



FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® piping systems and products made with TempRite® Technology. The FBC System Compatible Logo, FBC™, FlowGuard Gold®, BlazeMaster®, Corzan® and TempRite® are trademarks of Lubrizol Advanced Materials, Inc. or its affiliates.



A CSW Industrials Company

Extended heating service product information can be found at: rectorseal.com/heating

RECTORSEAL HVAC DIVISION

RectorSeal provides industry-leading digital and print support materials for its extensive chemical and mechanical solutions that include:

- Technical Product Information
- Marketing Support Materials
- Engaging Product Demonstration Videos
- Informative SDS and Product Data Sheets
- On-demand and Live Training and Webinars
- Learning Management System (LMS) support via RectorSeal Academy
- Informative Distributor and Sales Representative Tools
- Industry-related Tradeshow and Events Information

For complete details, visit [**www.rectorseal.com**](https://www.rectorseal.com)

For the latest product enhancements, news, and updated information, please follow RectorSeal's social media channels.

 facebook.com/rectorseal

 linkedin.com/company/rectorseal

 x.com/rectorseal

 instagram/rectorseal

 youtube.com/rectorsealcorp

All information is believed to be current at the time of printing, but our policy is one of continuous development. RectorSeal makes no warranties, express or implied, as to its accuracy. RectorSeal reserves the right to discontinue, update or change the information at any time without notice or without incurring obligations.

RectorSeal® • 2601 Spenwick Drive, Houston, TX 77055, USA • 713-263-8001 • rectorseal.com

RectorSeal®, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2024 RectorSeal. All rights reserved. R50490 08/24