

SIKA® RMAX® PRO SELECT POLYISO INSULATION BOARD

INSULATION FOR THE BUILDING ENVELOPE

PRODUCT DESCRIPTION

Rmax R-Matte® Plus-3 is an energy-efficient thermal insulation board composed of a closed-cell polyisocyanurate (polyiso) foam core bonded to reinforced aluminum facers on each side. While one side of the board has a reflective surface, the other side has been coated to have a non-reflective white matte surface. Boards can be installed with either the silver or white side out. For additional radiant barrier properties, install silver side against air space if one exists.

COMPLIANCES

- ASTM C1289 Type I, Class 1 and 2
- International Building Code (IBC) Section 2603, Foam Plastic
- ASHRAE 90.1
- California Code of Regulations, Title 24 (BHFTI License T1523)
- Miami-Dade County Product Control Approved
- Tested per NFPA 286 (ICC-ES AC12 Appendix B)

NOTE: For details, requirements and/or limitations, refer to Third-Party Evaluation Reports

APPLICATIONS

Stud walls; cavity walls; masonry walls; exterior stucco; re-siding; vaulted ceilings; attics and crawl spaces; limited roofing applications

THERMAL PROPERTIES / PRODUCT DATA

"R" means resistance to heat flow. The higher the R-value, the greater the insulating power.

| NOMINAL THICKNESS | THERMAL R-VALUE ¹ |
|-------------------|------------------------------|
| Inches | °F•ft ² •hr/Btu |
| 0.50 | 3.2 |
| 0.75 | 5.0 |
| 1.00 | 6.0 |
| 1.10 | 6.7 |
| 1.25 | 7.8 |
| 1.50 | 9.6 |
| 1.75 | 11.4 |
| 2.00 | 13.1 |
| 2.10 | 13.9 |
| 2.30 | 15.3 |
| 2.50 | 16.7 |
| 2.90 | 19.6 |
| 3.00 | 20.3 |
| 3.50 | 23.9 |
| 3.70 | 25.3 |
| 4.00 | 27.4 |
| 4.50 | 31.0 |

¹Thermal values are determined by using ASTM C518 test method at 75°F mean temperature on material conditioned according to PIMA Technical Bulletin No. 101.

TYPICAL PHYSICAL PROPERTIES

Physical properties shown are based on data obtained under controlled conditions and are subject to normal manufacturing tolerances.

| PROPERTY | TEST METHOD | RESULTS |
|---|-------------|------------------------------|
| Density, Overall, Nominal | ASTM D1622 | 2.0 pcf |
| Compressive Strength | ASTM D1621 | 20 psi ¹ |
| Flexural Strength | ASTM C203 | 60 psi |
| Flame Spread, Core ² | ASTM E84 | 75 or Less |
| Smoke Developed, Core ² | ASTM E84 | < 450 |
| Air Permeance | ASTM E2178 | < 0.02 L/(s•m ²) |
| Water Vapor Permeance | ASTM E96 | < 0.1 perm |
| Water Absorption | ASTM C209 | < 0.2% Vol. |
| Dimensional Stability, Length and Width | ASTM D2126 | < 1% Linear Change |
| Mold Resistance | ASTM D3273 | 10, no defacement |
| Service Temperatures | | 250°F max |

¹Less than 1" is standard at 16 psi.

²Flame spread and smoke numbers are shown for comparison purposes only and are not intended to represent the performance of R-Matte® Plus-3 and related components under actual fire conditions.

R-Matte® Plus-3 is shipped in bundles that are approximately 48" high and wrapped in plastic for easy handling. Visit www.rmax.com for a complete list of thicknesses and packaging information.

APPLICATION / INSTALLATION

General – R-Matte® Plus-3 shall be installed vertically or horizontally with all edges tightly butted. Vertical joints must be backed by framing or structural sheathing. Taping the joints is acceptable, although not required. Rmax recommends using a pressure sensitive tape such as R-SEAL Construction Tape, R-SEAL 3000, or equivalent.

Securement – Rmax recommends a minimum of eight fasteners per 4'x8' board. Additional fasteners may be required in locations expected to experience additional loading (heavy wind drafts/gusts, accelerated wear and tear, etc.) prior to attachment of covering material (cladding, furring, thermal barrier, etc.) or when not being covered. Exact number of fasteners also depends on the type being used and the capacity, consult fastener manufacturer. Fasten to wood framing using washers with roofing nails or bugle head screws, cap nails, or staples. The fasteners shall be long enough to penetrate wood framing a minimum of 1". Fasten to metal framing using self-taping screws and plastic washers. The fasteners shall be long enough to penetrate metal framing a minimum of four threads. Secure to concrete surfaces using plastic masonry fasteners with washer or a quality grade construction adhesive. TRUFAST Walls fasteners, sold by Rmax, are a great option for fastening R-Matte® Plus-3 to wood, steel and concrete substrates. Refer to the Rmax/TRUFAST Walls Fastener List and Installation Guide for more details.

LIMITATIONS

R-Matte® Plus-3 is not recommended, nor warranted, for use as a commercial roof insulation. Consult Rmax Sales for suitable commercial roof insulation products.

R-Matte® Plus-3 is not a structural panel; stud walls insulated with R-Matte® Plus-3 must be properly braced for lateral loads according to the requirements of local Building Codes.

WARNING

Polyiso is an organic material which will burn when exposed to an ignition source of sufficient heat and intensity and may contribute to flames spreading.

Installations utilizing R-Matte® Plus-3 must be fully protected on the inhabited side of the building by a thermal barrier such as a minimum of 1/2" gypsum wallboard. Consult local building codes and insurance authorities regarding special applications or details required when using R-Matte® Plus-3 as an exposed product in uninhabited spaces.

Per the IBC, a WRB is required behind the exterior wall veneer. The code also has provisions regarding vapor retarders, type and location, based on the assembly, climate zone and the amount of continuous insulation. It is up to the design professional to specify an assembly that will perform adequately and meet these requirements.

WARRANTY

See Rmax "Sales Policy" for terms and conditions. Rmax does not assume any responsibility or liability for the performance of any products other than those manufactured by Rmax.

NOTE: Factory packaging should not be relied upon as protection at job sites or other outdoor storage locations. When short-term outdoor storage is necessary, take the following precautions: Store flat above ground on raised pallets, place bundles on finished surfaces, cover with a breathable tarpaulin and secure cover to prevent wind displacement.



RMAX SALES OFFICES / PLANT

Central

13524 Welch Road
Dallas, TX 75244
(P) 972-387-4500
(F) 972-387-4673

East

1649 South Batesville Road
Greer, SC 29650
(P) 864-297-1382
(F) 864-234-7548

West

210 Lyon Drive
Fernley, NV 89408
(P) 775-575-4849
(F) 775-575-5035

rmax@rmax.com / www.rmax.com



BUILDING TRUST



PRODUCT DATA SHEET
SIKA® RMAX® PRO SELECT
R-MATTE® PLUS-3
Revision.08-07-2023

2 / 2