



Rmax Re-Cover Board-3

Insulation for Recovering Existing Roofs

Rmax Re-Cover Board-3 is an energy efficient thermal insulation board composed of a closed cell polyisocyanurate (polyiso) foam core bonded to facers on both sides. Standard Re-Cover Board-3 (GRF) has glass fiber/organic mat facers, but it is also available as Re-Cover Board-3 (CGF) with inorganic, polymer coated glass fiber mat facers.

This insulation is suitable for use in recover roofing system constructions utilizing built-up roof (BUR), modified bitumen or single ply membranes. Re-Cover Board-3 may be used in recover type applications where the existing roof system, including the deck below, is still sound and firmly attached.

Rmax Re-Cover Board-3 provides improved energy efficiency in an easy-to-install re-roofing insulation product.

Rmax Re-Cover Board-3 Benefits

- Durable glass fiber/organic mat or coated glass fiber facers
- Easy to install
- Saves on energy dollars
- Reduces material and labor costs
- Contributes towards LEED® credits
- Offers tax credits, where applicable



Rmax Re-Cover Board-3 is an easy solution for retrofit re-cover applications.



For warranties, limitations and conditions refer to Rmax Sales Policy and applicable warranties. All documents are located at www.rmax.com. For technical support, email technical@rmax.com. For sales support, pricing and availability, email rmax@rmax.com or call (800) 527-0890.

Proudly Made and Engineered in the U.S.A.



Rmax Sales Offices and Plant Locations

Central:

13524 Welch Road
Dallas, Texas 75244

Phone: 972-387-4500
Fax: 972-387-4673
Toll Free: 1-800-527-0890

East:

1649 South Batesville Road
Greer, South Carolina 29650

Phone: 864-297-1382
Fax: 864-234-7548
Toll Free: 1-800-845-4455

West:

210 Lyon Drive
Fernley, Nevada 89408

Phone: 775-575-4849
Fax: 775-575-5035
Toll Free: 1-800-762-9462

E-mail us at rmax@rmax.com or visit our website www.rmax.com

