

Section 1: Identification

Product identifier:

Product Name

Tapered Thermaroof®-3

Relevant identified uses of the substance or mixture and uses advised against

Recommended use Insulation Board

Details of the supplier of the safety data sheet Manufacturer

Rmax Operating, LLC 13524 Welch Road Dallas, TX 75244

United States www.rmax.com Rmax@rmax.com

Telephone (General) 972-387-4500

Emergency telephone number only:

Call CHEMTREC

Day or Night within USA and Canada:

1-800-424-9300

Section 2: Hazard Identification

United States (US)

Classification of the substance or mixture
OSHA HCS 2012 Not classified

Label elements OSHA HCS 2012

Hazard statements No label element(s)

Other hazards

OSHA HCS 2012 This product is not considered hazardous under U.S. OSHA 29 CFR 1910.1200 -

Hazard Communication Standard.

Substances Material does not meet the criteria of a substance.

Section 3 - Composition/Information on Ingredients

Mixtures

Composition (varies with product thickness)				
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/ Directive
Polyisocyanurate Foam	None	99%	No data available	OSHA HCS 2012: Not Classified
Pentane	CAS:109-66-0	0% to 5%	Inhalation-Rat LC50 364 g/m³ 4 Hour(s); Ingestion/Oral- Rat LD50 > 2000 mg/kg	OSHA HCS 2012: Flam. Liq. 1; STOT SE 3: Narc.; Asp. Tox. 1
Glass, oxide, chemicals	CAS:65997-17-3	0.01%	No data available	OSHA HCS 2012: Exposure limits
Cellulose	CAS:9004-34-6	0% to 0.85%	Ingestion/Oral- Rat LD50 >5 g/kg; Inhalation- Rat LC50 >5800mg/m³ 4 Hour(s); Skin- Rabbit LD50 >2 g/kg	OSHA HCS 2012: Comb. Dust
Carbon Black	CAS:1333-86-4	0.001%	Ingestion/Oral-Rat LD50 >15400 mg/kg; Skin- Rabbit LD50 >3 g/kg	OSHA HCS 2012: Exposure limits

Revision Date: 11/29/2016 Page 1 of 6



Section 4: First-Aid Measures

Description of first aid measures

Inhalation First aid is not expected to be necessary if materials used under ordinary conditions and as

recommended. If signs/symptoms develop, get medical attention.

Skin First aid is not expected to be necessary if materials used under ordinary conditions and as

recommended. If signs/symptoms develop, get medical attention.

Eye In case of contact with substance, immediately flush eyes with running water for at least 20

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If signs/

symptoms develop, get medical attention.

Ingestion First aid is not expected to be necessary if materials used under ordinary conditions and as

recommended.

Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Immediate medical attention after exposure to this material not expected to be necessary. No

special treatment indicated related to exposure to this material.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media LARGE FIRE: Water spray, fog or regular foam.

SMALL FIRES: Dry chemical, CO2, water spray or regular foam.

Unsuitable Extinguishing Media None known

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards Polyisocyanurate foam is combustible

Hazardous Combustion Products No data available.

Advice for fire fighters Fire fighters should wear complete protective clothing including self-contained

breathing apparatus. Structural fire fighters' protective clothing will only provide

limited protection.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions No special precautions expected to be necessary if materials used under ordinary

conditions and as recommended.

Emergency Procedures No emergency procedures are expected to be necessary if materials used under

ordinary conditions as recommended.

Environmental precautions No special environmental precautions necessary.

Revision Date: 11/29/2016 Page 2 of 6



Section 7 - Handling and Storage

Methods and material for containment and cleaning up

Containment/Clean-up Measures Pick up pieces and vacuum clean dusts. If sweeping is necessary, use a dust

suppressant.

Precautions for safe handling

Handling

Use only with adequate ventilation. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Avoid breathing dusts generated during use of this material. Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling and before ceting, dripling, or using tabages.

before eating, drinking, or using tobacco.

Conditions for safe storage, including any incompatibilities

Storage Keep away from heat, sparks, and flame. Keep away from incompatible materials.

Store in a cool, dry place.

Section 8 - Exposure Controls/Personal Protection

Control parameters

	Result	ACGIH	NIOSH	OSHA
Pentane (109-66-0)	TWAs	1000 ppm TWA (listed under Pentane, all isomers)	120 ppm TWA; 350 mg/m3 TWA	1000 ppm TWA; 2950 mg/m3 TWA
	Ceilings		610 ppm Ceiling (15 min); 1800 mg/m3 Ceiling (15 min)	Not established
Glass, oxide, chemicals as Glass wool fiber	TWAs	1 fiber/cm3 TWA (respirable fibers: length >5 μm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase- contrast illumination, listed under Synthetic vitreous fibers), as Glass wool fiber	3 fiber/cm3 TWA (fibers <= 3.5 μm in diameter and >= 10 μm in length); 5 mg/m3 TWA (total), as Glass wool fiber	Not established
Cellulose (9004-34-6)	TWAs	10 mg/m3 TWA	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
Carbon Black (1333-86-4)	TWAs	3.5 mg/m3 TWA [CMP]	3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as PAH)	3.5 mg/m3 TWA

Exposure controls

Engineering Measures/Controls Adequate ventilation systems as needed to control concentrations of airborne

contaminants below applicable threshold limit values.

Personal Protective Equipment

Respiratory In case of insufficient ventilation, wear suitable respiratory equipment.

Eye/Face Wear safety glasses or goggles

Skin/Body No skin protection is ordinarily required under normal conditions of use. Protective

 $puncture\mbox{-resistant gloves and/or sleeves for handling rough\mbox{-cut edges}.}$

Environmental Exposure Controls Follow best practice for site management and disposal of waste.

Key to abbreviations

NIOSH = National Institute of Occupational Safety and Health
OSHA = Occupational Safety and Health Administration
TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures
TWAEV = Time-Weighted Average Exposure Value

Revision Date: 11/29/2016 Page 3 of 6



Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description					
Physical Form	Solid	Appearance/ Description	Rigid foam board with foil facers - various thicknesses.		
Color	White/cream foam	Odor	Odorless		
	General Properties				
Boiling Point	Not relevant	Melting Point	No data available		
Decomposition Temperature	No data available	рН	Not relevant		
Specific Gravity/Relative Density	= 0.03 Water=1	Water Solubility	Not relevant		
	Volatility				
Vapor Pressure	No data available	Vapor Density	No data available		
Evaporation Rate	No data available				
Flammability					
Flash Point	Not relevant	UEL	Not relevant		
LEL	Not relevant	Auto ignition	No data available		
Flammability (solid, gas)	No data available				

Section 10: Stability and Reactivity

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability Stable under normal temperatures and pressures.

Possibility of hazardous reactions Hazardous polymerization will not occur.

Conditions to avoid Sources of flame and ignition.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Under normal conditions, hazardous decomposition will not occur. Thermal decomposition may emit fumes or gases, such as carbon monoxide, carbon dioxide.

Section 11 - Toxicological Information

Information on toxicological effects

Components			
Pentane (0% to 5%)	109-66-0	Acute Toxicity: Ingestion/ Oral-Rat LD50 >2000 mg/kg; Inhalation-Rat LC50 364 g/m ³ 4 Hour(s)	
Cellulose (0% to 0.85%)	9004-34-6	Acute Toxicity: Ingestion/ Oral-Rat LD50 >5 g/kg; Inhalation-Rat LC50 >5800 mg/m³ 4 Hour(s); Skin-Rabbit LD50 >2 g/kg	

Potential Health Effects

Inhalation

Acute (Immediate) Exposure to dust may cause irritation.

Skin

Acute (Immediate) Causes mild skin irritation.

Eye

Acute (Immediate) Exposure to dust may cause mechanical irritation.

Ingestion

Acute (Immediate) Excessive concentrations of nuisance dust in the workplace may cause mechanical

irritation to mucous membranes.

Revision Date: 11/29/2016 Page 4 of 6



Carcinogenic Effects

Carcinogenic Effects				
	CAS	IARC	NTP	
Glass, oxide, chemicals as Glass wool fiber	None	Not Listed	Reasonably Anticipated to be Human Carcinogen	
Carbon Black	1333-86-4	Group 2B-Possible Carcinogen	Not Listed	

Key to abbreviations
LC = Lethal Concentration
LD = Lethal Dose

Section 12 - Ecological Information

Toxicity and ecological dataNo information available.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste Dispose of content and/or container in accordance with local, regional, national,

and/or international regulations.

Packaging waste Dispose of content and/or container in accordance with local, regional, national,

and/or international regulations.

Section 14 - Transport Information

DOT, TDG, IMO/IMDG, IATA/ICAO Not regulated.

Special precautions for user None specified.

Transport in bulk according to Annex II of MARPO73/78 and the IBC CodeNo data available

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications

None

State Right To Know				Inventory	
Component	CAS	MA	NJ	PA	TSCA
Polyisocyanurate Foam	None	No	No	No	Yes
Pentane	109-66-0	Yes	Yes	Yes	Yes
Glass, oxide, chemicals	65997-17-3	No	No	No	Yes
Cellulose	9004-34-6	Yes	Yes	Yes	Yes
Carbon Black	1333-86-4	Yes	Yes	Yes	Yes

OSHA - Process Safety Management, Highly Hazardous Chemicals
OSHA - Specifically Regulated Chemicals
Clean Air Act (CAA) - 1990 Hazardous Air Pollutants
Not Listed
CERCLA/SARA
Not Listed

California - Proposition 65

Carbon Black - 1333-86-4 Carcinogen, airborne, unbound particles of respirable size. List date 2/21/03

Revision Date: 11/29/2016 Page 5 of 6



Section 16 - Other Information

Preparation Date: 05/29/2015 **Last Revision Date:** 11/29/2016

Disclaimer/Statement of Liability

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any representation or warranty, express or implied, regarding its accuracy or correctness. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of the product.

Revision Date: 11/29/2016 Page 6 of 6