



2018-02

		Packaging Details – Tapered Thermarroof-3									
Slope	Panel ID	Nominal Thickness (inches)		Bundle		Truckload		Weight			
				Pieces	SqFt ¹	Pieces	SqFt ¹	Lbs per Bdl ¹	Lbs per Sqft	Lbs per Piece ¹	
1/16	NN	0.50	-	0.75	76	1,216	3,648	58,368	244	0.20	3.2
	N	0.75	-	1.00	54	864	2,592	41,472	209	0.24	3.9
	OO	1.00	-	1.25	42	672	2,016	32,256	191	0.28	4.5
	O	1.25	-	1.50	34	544	1,632	26,112	177	0.33	5.2
	PP	1.50	-	1.75	28	448	1,344	21,504	165	0.37	5.9
	P	1.75	-	2.00	24	384	1,152	18,432	157	0.41	6.5
	RR	2.00	-	2.25	22	352	1,056	16,896	159	0.45	7.2
	R	2.25	-	2.50	20	320	960	15,360	158	0.49	7.9
1/8	AA	0.50	-	1.00	64	1,024	3,072	49,152	227	0.22	3.5
	A	1.00	-	1.50	38	608	1,824	29,184	185	0.30	4.9
	B	1.50	-	2.00	26	416	1,248	19,968	161	0.39	6.2
	C	2.00	-	2.50	20	320	960	15,360	151	0.47	7.5
	D	2.50	-	3.00	16	256	768	12,288	142	0.55	8.9
	E	3.00	-	3.50	14	224	672	10,752	143	0.64	10.2
	F	3.50	-	4.00	12	192	576	9,216	139	0.72	11.5
3/16	JJ	0.50	-	1.25	54	864	2,592	41,472	209	0.24	3.9
	J	1.00	-	1.75	34	544	1,632	26,112	177	0.33	5.2
	KK	1.25	-	2.00	28	448	1,344	21,504	165	0.37	5.9
	K	1.75	-	2.50	22	352	1,056	16,896	159	0.45	7.2
	LL	2.00	-	2.75	20	320	960	15,360	158	0.49	7.9
	L	2.50	-	3.25	16	256	768	12,288	147	0.58	9.2
	MM	2.75	-	3.50	14	224	672	10,752	138	0.62	9.9
	M	3.25	-	4.00	12	192	576	9,216	135	0.70	11.2
1/4	X	0.50	-	1.50	48	768	2,304	36,864	202	0.26	4.2
	G	1.00	-	2.00	32	512	1,536	24,576	177	0.35	5.5
	Y	1.50	-	2.50	24	384	1,152	18,432	165	0.43	6.9
	H	2.00	-	3.00	18	288	864	13,824	148	0.51	8.2
	Z	2.50	-	3.50	16	256	768	12,288	153	0.60	9.5
	I	3.00	-	4.00	12	192	576	9,216	131	0.68	10.9
	ZZ	3.50	-	4.50	12	192	576	9,216	147	0.76	12.2
3/8	SS	0.50	-	2.00	38	608	1,824	29,184	185	0.30	4.9
	S	1.00	-	2.50	26	416	1,248	19,968	161	0.39	6.2
	TT	2.00	-	3.50	16	256	768	12,288	142	0.55	8.9
1/2	Q	0.50	-	2.50	32	512	1,536	24,576	177	0.35	5.5
	XX	1.00	-	3.00	24	384	1,152	18,432	165	0.43	6.9
	QQ	2.50	-	4.50	12	192	576	9,216	131	0.68	10.9

¹Data is based on 48" x 48" pieces.