



Rmax Ultra-Max® HD

1/2" High Density CoverBoard

Rmax Ultra-Max® HD is a 1/2" thick high density roof cover board composed of closed-cell polyisocyanurate (polyiso) foam core bonded to inorganic polymer coated glass fiber mat facers on both sides.

Ultra-Max® HD has a Grade 1 (80 psi) compressive strength adding superior protection and long-term performance to the roofing system. This lightweight, easy to install, durable polyiso cover board offers additional energy-saving value.

Ultra-Max® HD is suitable for single ply membrane systems.



Rmax Ultra-Max® HD is applied above the roof deck and insulation layer to provide a suitable substrate for roofing membranes as well as suitable protection for underlying insulation.

Why Ultra-Max® HD?

- Closed-cell polyiso foam core
- Delivers an industry leading 2.5 R-value
- Superior water resistance
- Mold resistant material per ASTM D3273
- Lightweight for installation efficiencies
- Easy to cut, no special tools required
- Saves on energy dollars
- Excellent impact resistance from foot traffic, storms and hail (Approved FM Hail Rating)
- Utilizes a blowing agent that has zero Ozone Depletion Potential (ODP)



For warranties, limitations and conditions refer to Rmax Sales Policy and applicable warranties. All documents are located at www.rmax.com. For technical support, email technical@rmax.com. For sales support, pricing and availability, email rmax@rmax.com or call (800) 527-0890.

Proudly Made and Engineered in the U.S.A.



Rmax Sales Offices and Plant Locations

Central:

13524 Welch Road
Dallas, Texas 75244

Phone: 972-387-4500
Fax: 972-387-4673
Toll Free: 1-800-527-0890

East:

1649 South Batesville Road
Greer, South Carolina 29650

Phone: 864-297-1382
Fax: 864-234-7548
Toll Free: 1-800-845-4455

West:

210 Lyon Drive
Fernley, Nevada 89408

Phone: 775-575-4849
Fax: 775-575-5035
Toll Free: 1-800-762-9462

E-mail us at rmax@rmax.com or visit our website www.rmax.com

