



Rmax Ultra-Max® Insulation for Above the Deck

Rmax Ultra-Max® is an energy reducing thermal insulation board composed of a closed-cell polyisocyanurate (polyiso) foam core bonded to moisture resistant inorganic polymer coated glass mat facers on both sides.

This insulation is suitable for use in insulated roofing system constructions utilizing built-up roof (BUR), modified bitumen or single ply membranes and metal panel roofing systems. Ultra-Max® is approved for use in new roofing constructions and limited retrofit/recover roofing constructions over steel, wood, non-combustible and certain types of nailable roof deck.

Rmax Ultra-Max® Benefits

- Moisture resistant coated glass fiber facers
- Delivers highest R-values - inch for inch
- Saves on energy dollars
- No thermal barrier required
- 25 psi compressive strength available
- Reduces material and labor costs
- Contributes toward LEED® credits
- Offers tax credit, where applicable



Rmax Ultra-Max® is an excellent choice for metal panel roofing systems.



For warranties, limitations and conditions refer to Rmax Sales Policy and applicable warranties. All documents are located at www.rmax.com. For technical support, email technical@rmax.com. For sales support, pricing and availability, email rmax@rmax.com or call (800) 527-0890.

Proudly Made and Engineered in the U.S.A.



Rmax Sales Offices and Plant Locations

Central:

13524 Welch Road
Dallas, Texas 75244

Phone: 972-387-4500
Fax: 972-387-4673
Toll Free: 1-800-527-0890

East:

1649 South Batesville Road
Greer, South Carolina 29650

Phone: 864-297-1382
Fax: 864-234-7548
Toll Free: 1-800-845-4455

West:

210 Lyon Drive
Fernley, Nevada 89408

Phone: 775-575-4849
Fax: 775-575-5035
Toll Free: 1-800-762-9462

E-mail us at rmax@rmax.com or visit our website www.rmax.com

