



Safety Data Sheet 10 Minute Concrete Mender – Part B

Version: 2.2

Revision Date: 01/JUNE/2023

Page: 1 of 7


1. PRODUCT AND COMPANY IDENTIFICATION

Product Name : 10 Minute Concrete Mender – Part B
 Recommended use : Part of rapid concrete repair system
 Company : Roadware Incorporated
 Address : 381 Bridgepoint Way
 South Saint Paul, MN 55075
 Phone : 651-457-6122
 Emergency Telephone Numbers : Chem-Tel: 800-255-3924
 Restrictions on use : For professional or industrial use only

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids	4
Skin irritation	2
Eye irritation	2A
Specific organ toxicity – single exposure	3
Aspiration hazard	1



Hazard Statements

H227	Combustible liquid.
H304	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements:

Obtain special instructions before use.
 Do not handle until all safety instructions have been read and understood.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Wash skin thoroughly after handling.
 Keep away from flames and hot surfaces. No smoking.
 Avoid breathing dust, fume, gas, vapors or spray. Use outdoors or only in well ventilated area. In case of inadequate ventilation wear respiratory protection.

Response statements:

If swallowed: Rinse mouth. Call a poison center or doctor/physician if you feel unwell.
If on skin: Rinse skin with plenty of water. If skin irritation occurs: Get medical attention.
Take off contaminated clothing and wash before reuse.



Safety Data Sheet

10 Minute Concrete Mender – Part B

Version: 2.2

Revision Date: 01/JUNE/2023

Page: 2 of 7

If inhaled: If breathing is difficult, remove person to fresh air and keep at rest in a comfortable position for breathing. Call a poison center or doctor/physician if you feel unwell.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
Storage: Store in a well-ventilated place. Keep cool.
Disposal: Dispose of contents and container in accordance with existing federal, state and local environmental control laws.

Section 3. Composition / Information on Ingredients

This product is a mixture.

Hazardous Components

CAS Number	Chemical Name	Concentration
64742-94-5	Solvent naphtha, heavy	25-50%
91-20-3	Naphthalene	0-5%
95-63-6	1,2,4-trimethylbenzene	0-2%
	Additional NON-Hazardous ingredients not subject to reporting and do not violate Korean law.	43% or less.

Specific chemical identities and exact percentages may have been withheld as a trade secret or CBI in compliance with 29 CFR 1910.1200 (i).

4. First Aid Measures

General Advice	Take proper precautions to ensure your own health and safety before attempting rescue or administering first aid. Wear protective clothing and gloves. See section 8 for recommendations. Remove contaminated clothing. Move to a well ventilated area or outdoors.
Skin Contact	After contact with skin, wash immediately with plenty of soap and water. Get medical attention if irritation or rash develops. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye Contact	Immediately flush eye(s) with plenty of water. Remove contact lenses. If eye irritation persists get medical advise/attention
Inhalation	If inhaled, move affected persons to fresh air. If not breathing, give artificial respiration. Get medical attention immediately. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, qualified personnel should administer oxygen.
Ingestion	If swallowed, get medical attention immediately. Wash out mouth with water. DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
Most important symptoms and effects (acute and delayed)	Most important symptoms and effects are described in section 2 and/or section 11. <i>Exposure to high vapor concentrations of heavy aromatic solvents can cause central nervous system depression, dizziness, light headedness, headache, nausea, and loss of coordination.</i>
Notes to Physician	Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours. Symptoms of poisoning may appear several hours later. Potential for chemical pneumonitis, treat appropriately.

5. Firefighting Measures

Suitable Extinguishing Media	Dry chemical, Carbon Dioxide (CO2), alcohol resistant foam, water fog.
Not Suitable Extinguishing Media	Avoid high volume water jet, may spread fire.
Special exposure hazards	In a fire or if heated, a pressure increase will occur and the container may burst. Produces oxides of carbon and nitrogen as well as isocyanates. Combustion products may be toxic and/or irritating. Avoid smoke.



Safety Data Sheet

10 Minute Concrete Mender – Part B

Version: 2.2

Revision Date: 01/JUNE/2023

Page: 3 of 7

Special protective equipment for fire-fighters	Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.
Special remarks on explosion hazards	Due to reaction with water producing CO ₂ gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed. Containers may burst if overheated.

6. Accidental Release Measures

Personal protection	Immediately contact emergency personnel. Isolate the area. Keep upwind avoiding inhalation of vapors. Clean up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection. Use suitable protective equipment (see section 8).
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Methods for cleaning up	Contain and adsorb large spillages onto an inert, non-flammable adsorbent carrier (such as earth, vermiculite or sand). Shovel into open-top drums or plastic bags for further decontamination if necessary.

7. Handling and Storage

Handling	Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material. Keep tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Storage	Keep container in a cool, well-ventilated area. Keep container tightly closed.
Safe storage temperature 60 - 100° F	

8. Exposure Controls / Personal Protection

Exposure Limits

CAS Number	Component	Value type	Limit / Standard	Notes	Source
64742-94-5	Solvent naphtha, heavy	TWA	500 ppm 2000 mg/m ³		OSHA Z1
64742-94-5	Solvent naphtha, heavy	TWA	200 mg/m ³	Total hydrocarbons	ACGIH
64742-94-5	Solvent naphtha, heavy	TWA	400 ppm 1600 mg/m ³		OSHA P0
91-20-3	Naphthalene	TWA	10 ppm		ACGIH
91-20-3	Naphthalene	STEL	15 ppm		ACGIH
91-20-3	Naphthalene	TWA	10 ppm 50 mg/m ³		NIOSH REL
91-20-3	Naphthalene	ST	15 ppm 75 mg/m ³		NIOSH REL
91-20-3	Naphthalene	TWA	10 ppm 50 mg/m ³		OSHA Z1
91-20-3	Naphthalene	TWA	10 ppm 50 mg/m ³		OSHA P0



Safety Data Sheet

10 Minute Concrete Mender – Part B

Version: 2.2

Revision Date: 01/JUNE/2023

Page: 4 of 7

91-20-3	Naphthalene	STEL	15 ppm 75 mg/m3		OSHA P0
526-73-8	Benzene, 1,2,5-trimethyl-	TWA	25 ppm 125 mg/m3		NIOSH REL
95-63-6	1,2,4-trimethylbenzene	TWA	25 ppm 125 mg/m3		NIOSH REL

Preventive Measures	Conditions of use, adequacy of engineering or other control measures and actual exposures will dictate the need for specific protective devices at your workplace.
Engineering Controls	Use local exhaust ventilation to maintain airborne concentrations below the TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it. For guidance on engineering control measures refer to publications such as the ACGIH current edition of 'Industrial Ventilation, a manual of Recommended Practice.'
Personal Protection	
Eyes	Chemical safety goggles. If there is a potential for splashing, use a full face shield.
Skin	Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.
Respiratory	When the product is sprayed or heated without adequate ventilation, an approved MSHA/NIOSH positive pressure, supplied-air respirator may be required. Air purifying respirators equipped with organic vapor cartridges and a HEPA (P100) particulate filter may be used under certain conditions when a cartridge change-out schedule has been developed in accordance with OSHA respiratory protection standard (29 CFR 1910.134).
Hands	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products. Nitrile rubber has shown good results. Thin latex or vinyl disposable gloves should be avoided. Consult with producers of protective gloves for suitability.
Other Protection	Consult your supervisor or S.O.P. for special handling instructions.

9. Physical and Chemical Properties

<u>General Information</u>	
Physical state	Liquid
Color	Black
Odor	Hydrocarbon like
Odor Threshold	Not available
pH	Not available
Boiling point	> 350 °F
Melting point	Not available
Flash point	> 145 °F PMCC
Explosive properties	Non-explosive in the presence of the following materials or conditions: Open flames, sparks, static discharge, shocks and mechanical impacts.
Auto-ignition temperature	> 840 °F
Evaporation Rate	Very slow
Relative density	0.95
Vapor pressure	Not available
Vapor density	Not Available
Viscosity	5 – 15 cps
VOC content	Not Available

10. Stability and Reactivity

Stability and reactivity	Stable at room temperature.
Conditions of instability	Avoid high temperatures.



Safety Data Sheet

10 Minute Concrete Mender – Part B

Version: 2.2

Revision Date: 01/JUNE/2023

Page: 5 of 7

Incompatibility with various substances	Strong oxidizing agents, unintended isocyanates .
Hazardous polymerization	Polymerization may occur with incompatible reactants, especially strong oxidizers.
Hazardous decomposition products	Combustion products may include: carbon oxides (CO, CO ₂), nitrogen oxides (NO, NO ₂ ...), hydrocarbons and other undetermined components.

11. Toxicological Information

No product specific toxicological information is available. Data obtained on components are summarized below.

Component	
64742-94-5	Solvent naphtha, heavy Likely routes of exposure: Skin contact, inhalation, eye contact
Acute Toxicity	<i>Inhalation:</i> Minimally toxic. Exposure to levels exceeding the TLV or PEL may result in central nervous system depression. Symptoms include drowsiness, dizziness and loss of coordination. <i>Oral:</i> Minimally toxic. May cause gastro-intestinal pain, coughing, headache, dizziness, diarrhea, nausea, vomiting and unconsciousness. <i>Dermal:</i> Minimally toxic. May cause dryness leading to itching and dermatitis. Toxicity estimates: Inhalation: LC50, rat, male/female > 4600 mg/m ³ / 4 hrs Oral: LD50, rat, male/female: > 5000 mg/kg Dermal: LD50, rabbit, > 3000 mg/kg
Skin Corrosion Skin Irritation	Causes skin irritation, redness, dryness or roughness. Not considered a skin corrosive
Eye Damage Eye Irritation	Irritating to eyes. Not expected to cause serious eye damage
Respiratory or Skin sensitization	Not expected to be a skin sensitizer. Did not cause sensitization in laboratory animals.
Carcinogenicity	Solvent Naphtha, heavy, is not considered a human carcinogen as defined by the IARC, NTP, OSHA.
Germ Cell Mutagenicity	Negative
Reproductive toxicity	No reproductive effects. No teratogenic effects on fetal development.
Target Organ Systematic Toxicity – Single Exposure	Inhalation: Central nervous system, May cause drowsiness and/or dizziness. Possible narcotic effects including nausea and vomiting when over exposed to levels beyond the TLV or PEL.
Target Organ Systematic Toxicity – Repeated Exposure	Not expected to cause organ damage from prolonged or repeated exposure. Based on the physical-chemical properties of this material when compared with test data from similar compounds
Aspiration Toxicity	Aspiration into the lungs if swallowed or when vomiting may cause chemical pneumonitis which can be fatal.
91-20-3 95-63-6	Naphthalene 1,2,4-trimethylbenzene Likely routes of exposure: Skin contact, inhalation, eye contact
Acute Toxicity	No data available
Skin Corrosion Skin Irritation	No data available
Eye Damage Eye Irritation	No data available
Respiratory or Skin sensitization	No data available
Carcinogenicity	Naphthalene



Safety Data Sheet

10 Minute Concrete Mender – Part B

Version: 2.2

Revision Date: 01/JUNE/2023

Page: 6 of 7

	IARC 2B - 2B, possible human carcinogen. ACGIH – No component of this product is identified as a carcinogen by ACGIH NTP – Reasonably anticipated to be a human carcinogen. OSHA - No component of this product is identified as a carcinogen by OSHA
Germ Cell Mutagenicity	No data available
Reproductive toxicity	No data available
Target Organ Systematic Toxicity – Single Exposure	No data available
Target Organ Systematic Toxicity – Repeated Exposure	No data available
Aspiration Toxicity	No data available

12. Ecological Information

No product specific ecological information is available. Data obtained on components are summarized below.

Component	
64742-94-5	Solvent naphtha, heavy
Persistence and degradability	In aquatic environments this component does not readily biodegrade. Readily biodegrades into the atmosphere, soils.
Mobility	No data available
Bioaccumulation	Not likely to bioaccumulate
Ecotoxicity effects	No data available
Aquatic toxicity	Very toxic to aquatic life

Very toxic to aquatic life with long lasting effects. Avoid dispersal of spilled material and runoff from contact with soil, waterways, drains and sewers. Improper or unprofessional handling or disposal can create an environmental hazard.

13. Disposal Considerations

Waste disposal	The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-product should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Contaminated containers should be emptied. Do not reuse containers. Do not burn or use a cutting torch on empty containers.
U.S. EPA RCRA	EPA resource recovery act (RCRA) composite list of hazardous wastes and Appendix VIII Hazardous constituents (40 CFR 261): Under RCRA, it is the responsibility of the person who generates a solid waste to determine if that waste is a hazardous waste as defined by 40 CFR 261.2.

14. Transportation Information

Regulatory Information	UN Number	Proper Shipping Name	Class	PG*	Label	Additional information
DOT Classification	Not regulated					
TDG Classification	Not regulated					
IMDG Class	Not regulated					
IATA-DGR Class	Not regulated					

15. Regulatory Information

United States Federal Regulations	
U.S. Toxic Substances Control Act (TSCA 8b)	All components are listed or exempted.



Safety Data Sheet
10 Minute Concrete Mender – Part B

Version: 2.2

Revision Date: 01/JUNE/2023

Page: 7 of 7

CERCLA – reportable quantity, calculated	3000 lbs. (380 gallons), Naphthalene, 91-20-3,
SARA 304 Extremely Hazardous Substances RQ	Does not contain any components subject to 304 EHS RQ
SARA 311 / 312	Acute health hazard Chronic health hazard
EPA Community Right To Know Act (EPCRA) SARA Title III Section 313, components requiring notification.	CAS 91-20-3, Naphthalene
Clean Air Act, Components listed as HAP	CAS 91-20-3, Naphthalene
Clean Water Act, Section 311, Table 116.4A	CAS 91-20-3, Naphthalene
Clean Water Act, Section 311, Table 117.3	CAS 91-20-3, Naphthalene
Clean Water Act, Section 307	CAS 91-20-3, Naphthalene
California Prop 65	This product contains a chemical known to the State of California to cause cancer. CAS 91-20-3, Naphthalene.
DRC Conflict materials	Based upon information from our suppliers this product is “DRC Conflict Free” as defined by the SEC Conflict Minerals Final Rule.

Canadian Regulations	
WHMIS (Canada)	CAS 64742-94-5 Solvent Naphtha Class B3, D-2B CAS 91-20-3 Naphthalene Class B4, D-2B
CEPA (DSL)	Canada inventory: All components are listed or exempted.

16. Other Information

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, *NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.*

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Disclaimer:

The data set forth in this sheet is based on information provided by the suppliers of raw materials and chemicals used in the manufacture of the aforementioned product. Roadware Incorporated makes no warranty with respect to the accuracy of the information provided by their suppliers, and disclaims all liability of reliance thereof.