

LEED Submittal Guide

ROCKWOOL provides project-specific LEED Certificates for LEED submission purposes. To generate a project-specific LEED Certificate, please use the [ROCKWOOL LEED Calculator](#). Simply fill out the form by selecting the ROCKWOOL product being installed and adding the project location. The LEED Calculator will automatically generate a certificate for the following information:

Recycled and Regional Contents	
Recycled content:	• Pre-consumer recycled content • Post-consumer recycled content
Regional content:	• Distance from extraction locations to manufacturing location • Distance from extraction locations to project site • Distance from extraction locations to manufacturing location

Other information and supporting documentation pertaining to the LEED certification program can be found at rockwool.com on the [Product Transparency page](#). However, to assist you in completing a submittal form, refer to the commonly requested information below about ROCKWOOL products.

Sourcing of Raw Materials	
Recycled content	Yes
Post-consumer recycled content	0%
Pre-consumer recycled content	Dependent on manufacturing location and product. Refer to ROCKWOOL LEED Calculator
Material reuse (% salvage, refurbished, reused)	No
Extended producer responsibility program	No

Environmental Impacts	
Environmental product declaration (EPD)	Yes
Life cycle assessment	Yes
EPD product-specific	Yes
EPD third-party verified, type iii	Yes
Program operator	UL Environment
Cradle to cradle	No

Material Ingredient Disclosure	
Health product declarations (HPDs)	Yes – Version: 2.2 Disclosure Level: 100ppm
DECLARE labels	Yes Disclosure Level: 100ppm
Bio-based materials (USDA BioPreferred® Program, as per ASTM D6866)	AFB® evo: 72% AFB®: 25% Comfortbatt®: 25% Safe'n'Sound®: 25%

Indoor Environmental Quality	
Compliance with CDPH Standard Method v1.2-2017	
Classroom scenario	AFB®, AFB® evo, Comfortbatt®, Safe'n'Sound®, Curtainrock®, Curtainrock® 40, Curtainrock® 80, Roxul Safe®
Office scenario	AFB® evo
Total VOCs after 14 days (336 hours)	0.5 mg/m3 or less
Third party certificate	UL GREENGUARD Gold
Manufacturer's declaration Only applicable for products without a GREENGUARD Gold certificate being installed on the interior side of the water-resistive barrier	VOC Emissions Technical Bulletin
Inherently non-emitting source	No

Sustainability Links

Product Transparency:

www.rockwool.com/north-america/about-us/sustainability/product-transparency/

ROCKWOOL LEED Calculator

www.rockwool.com/north-america/resources-and-tools/tools/leed-calculator/

LEED Solutions:

www.rockwool.com/north-america/about-us/sustainability/leed-solutions-guide/