




Insulation Solutions That Drive Building Performance



Products	Standard Thickness	Dimensions (WxL)	Density pcf (Kg/m3)	R-value Per Inch	Fire		Acoustic (at 3" Thickness)		Corrosive Resistance	Compliance				
Interior Wall					ASTM E 136 & CAN/ULC S114	ASTM E 84 (UL 723)	ASTM C 423 250Hz 500Hz 1000Hz 2000Hz		ASTM C 423 NRC	ASTM C 665	ASTM C 665	CAN/ULC S702	ASTM C 553	UL Design Nos.
AFB®	1"-4", 0.5" increments, 5", 6"	16"x48", 24"x48"	2.5 (40) >= 3", 2.8 (45) < 3"	N/A	Non-combustible	Complies	0.96 1.18 1.07 1.05	1.05	Pass	Type 1, Complies	Type 1, Complies	Type 7, Complies	Consult UL/ULC Listings	
AFB evo™	1"-4", 0.5" increments, 5", 6"	16"x48", 24"x48"	2.5(40) >= 3", 2.8 (45) < 3"	N/A	Non-combustible	Complies	0.96 1.18 1.07 1.05	1.05	Pass	Type 1, Complies	Type 1, Complies	Type 7, Complies	Consult UL/ULC Listings	
Exterior Wall Batt					ASTM E 136 & CAN/ULC S114	ASTM E 84 (UL 723)	ASTM C 423 250Hz 500Hz 1000Hz 2000Hz		ASTM C 423 NRC	ASTM C 665	ASTM C 665	CAN/ULC S702	ASTM C 553	UL Design Nos.
COMFORTBATT™ Steel Stud	2.5", 3.5", 6" (CAN) 2.5", 3.5", 6", 7.25" (USA)	16.25"x48", 24.25"x48"	>2 (>32)	R10-R24 (CAN) R10-R30 (USA)	Non-combustible	Complies	N/A	N/A	Pass	Type 1, Complies	Type 1, Complies	N/A	N/A	
COMFORTBATT™ Wood Stud	3.5", 5.5", 7.25", 8" (CAN) 3.5", 5.5", 7.25" (USA)	15.25"x47", 23"x47"	>2 (>32)	R14-R32 (CAN) R15-R30 (USA)	Non-combustible	Complies	N/A	N/A	N/A	Type 1, Complies	Type 1, Complies	N/A	N/A	
Exterior Wall Rainscreen & Cavity Wall					ASTM E 136 & CAN/ULC S114	ASTM E 84 (UL 723)	ASTM C 423 250Hz 500Hz 1000Hz 2000Hz		ASTM C 423 NRC	ASTM C 665	ASTM C 1104	ASTM C 1338	ASTM E 96	ASTM C 612
CAVITYROCK®	1" - 4", 0.5" increments, 5", 6"	16"x48", 24"x48"	6.2 / 4.1 (100 / 65) 5.3 (85) 1"-1.5", 4.4 (70) 2"	4.3	Non-combustible	Complies	0.93 0.88 0.84 0.90	0.90	Pass	0.03%	Zero Growth	27 perms	Type IVB, Complies	
Insulated Sheathing for Continuous Insulation					ASTM E 136 & CAN/ULC S114	ASTM E 84 (UL 723)	ASTM C 423 250Hz 500Hz 1000Hz 2000Hz		ASTM C 423 NRC	ASTM C 665	ASTM C 1104	ASTM C 165 @10% @25%	ASTM E 96	ASTM C 612
COMFORTBOARD™ 110	1", 1.25", 2", 2.5", 3"	24"x48", 48"x72"	11 (176)	4	Non-combustible*	Complies	0.71 0.85 0.90 0.96	0.85	Pass	0.28%	584 1566	35 perm	Type IVB, Complies	
COMFORTBOARD™ 80	1.25", 1.5", 2", 2.5", 3"	48"x24", 48"x36", 48"x72", 48"x96"	8 (128)	4	Non-combustible*	Complies	0.78 0.90 0.97 0.97	0.90	Pass	0.05%	439 1065	31 perm	Type IVB, Complies	
Curtain Wall Systems					ASTM E 136 & CAN/ULC S114	ASTM E 84 (UL 723)	ASTM C 423 250Hz 500Hz 1000Hz 2000Hz		ASTM C 423 NRC	ASTM C 665	ASTM C 1104	UL/ULC Design Nos.		ASTM C 612
CURTAINROCK®	1", 1.5", 2", 3", 4", 5"	24"x48"	3.5 (56)	4.2	Non-combustible	Complies	0.95 1.14 1.01 1.03	1.05	Pass	0.01%	Consult UL/ULC Listings		Type IVB, Complies	
CURTAINROCK® 40	2", 3", 4"	24"x48", 48"x72"	4 (64) Nominal	4.3	Non-combustible	Complies	N/A	N/A	Pass	0.01%	Consult UL/ULC Listings		Type IVB, Complies	
CURTAINROCK® 80	1", 2", 3", 4"	24"x48", 48"x72"	8 (128) Nominal	4.3	Non-combustible	Complies	N/A	N/A	Pass	0.04%	Consult UL/ULC Listings		Type IVB, Complies	
ROXUL SAFE™	2", 3", 4"	24"x48"	4.5 (72)	N/A	Non-combustible	Complies	N/A	N/A	Pass	0.04%	Consult UL/ULC Listings		Type IVA, Complies	
Multi-Purpose Boards					ASTM E 136 & CAN/ULC S114	ASTM E 84 (UL 723)	ASTM C 423 250Hz 500Hz 1000Hz 2000Hz		ASTM C 423 NRC	ASTM C 665	ASTM C 1104	Alternative Solutions		Compliance
ROCKBOARD® 40	2", 2.5", 3", 4"	24"x48"	4 (64)	4.2	Non-combustible	Complies	0.95 1.14 1.01 1.03	1.05	Pass	0.03%	Facing Options		ASTM C 612	
ROCKBOARD® 60	2", 3", 3.5", 4"	24"x48"	6 (96)	4.3	Non-combustible*	Complies	0.89 1.04 1.09 1.01	1.00	Pass	0.07%	Foil Faced, Black Mat		Type IVB, Complies	
ROCKBOARD® 80	1", 1.5", 2", 3", 4"	24"x48"	8 (128)	4	Non-combustible*	Complies	0.82 0.89 0.94 1.00	0.90	Pass	0.05%	Foil Faced, Black Mat		Type IVB, Complies	
Metal Building					ASTM E 136 & CAN/ULC S114	ASTM E 84 (UL 723)	ASTM C 665	ASTM C 1104	UL Design Nos.		ASTM C 612	ASTM C 553	DISCLAIMER AND LIMITATION OF LIABILITY: The statements and data contained in this brochure are for general information purposes ONLY. They are NOT specific technical recommendations as to any particular design or application and the ultimate determination as to product suitability is the sole responsibility of the installer or end user. Although the information contained herein, including ROCKWOOL product descriptions, is believed to be correct at the time of publication, accuracy cannot be guaranteed. ROCKWOOL fully reserves the right to make product specification changes, without notice or obligation, and to modify or discontinue any of its products at any time. In no event shall ROCKWOOL be liable for any direct, indirect, or consequential damages of any kind arising from information contained in this brochure, including, but not limited to, claims for loss of profits, business interruption, or damages to business reputation. This limitation of liability shall apply to all claims whether those claims are based in contract, tort, or any legal cause of action.	
ROXUL SAFE™ 65	3"	24"x48", 31.5"x48", 32"x48"	6 (96) Nominal	4.2	Non-combustible	Complies	Pass	0.04%	Consult UL/ULC Listings		Type IVB, Complies	N/A		
ROXUL SAFE™ 55	4"	24"x48", 31.5"x48", 32"x48"	4.5 (72) Nominal	4.2	Non-combustible	Complies	Pass	0.04%	Consult UL/ULC Listings		Type IVB, Complies	N/A		
ROCKWOOL PLUS™ MB	2"-4", 0.5" increments, 5", 6"	24"x48"	2 (32)	4	Non-combustible	Complies	Pass	0.03%	N/A		N/A	Type I, II, III		

*Applies to CAN/ULC S114 only.