

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 2023-10-06

Revision date: 2023-10-06

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Article
Product name : Exterior Grade – Marine Grade, Exterior Core, and Sheathing

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Building and construction work

1.3. Supplier

Manufacturer

Roseburg Forest Products
3660 Gateway St.
Springfield, Oregon 97477 - USA
T 541.658.6117 (non-emergency)
www.roseburg.com

Distributor

Roseburg Forest Products
777 Fibreboard Drive
Pembroke, ON K8A 6W4 – Canada
T 613-732-3939
www.roseburg.com

1.4. Emergency telephone number

Emergency number : In the event of a situation not covered in SECTION 4: First-aid Measures - 1(800) 222-1222 (Available 24/7)
Emergency contact : Poison control center

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Manufactured Article: GHS classification and labelling not applicable. This product is exempt from classification and labelling as per C.F.R. 1910.1200(b)(6)(v) and the Hazardous Products Act, Paragraph 12(i). The hazards indicated in this document apply only when this product is cut, drilled, or modified in such a way that dust particles are released.

GHS classification

Skin Sens. 1
Carc. 1A
Comb. Dust

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

May form combustible dust concentrations in air
May cause an allergic skin reaction.
May cause cancer.

Precautionary statements (GHS) :

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.

Exterior Grade – Marine Grade, Exterior Core, and Sheathing

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

If exposed or concerned: Get medical advice/attention.
If on skin: Wash with plenty of water.
Wash contaminated clothing before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Wood dust, all soft and hard woods	Wood dust, all soft and hard woods Wood dust / Wood dust, all soft and hard woods, except western red cedar / Wood dust, nonallergenic / Wood dust, hard and soft / Wood dust (non-allergenic) / Wood dust, softwoods and hardwoods, except western red cedar / Wood / Wood dusts / Wood dusts (all other species) / Wood dust, all soft and hard woods, except red cedar / WOOD POWDER	CAS-No.: Not applicable	80 - 100
Phenol-formaldehyde polymer	Phenol-formaldehyde polymer Formaldehyde, oligomeric reaction products with phenol / Phenol, polymer with formaldehyde / Resin, phenol formaldehyde / Phenol-formaldehyde resins / Phenol/formaldehyde polymer / Phenol/formaldehyde resin / Phenol-formaldehyde resin / Phenol-formaldehyde copolymer / T-77 / Phenolic formaldehyde resins / Phenol resin / Phenoplasts / Bakelite / Phenol-formaldehyde condensations products / Phenolic resin / Phenol/formaldehyde copolymer, novolak type / Polymer of formaldehyde/phenol	CAS-No.: 9003-35-4	1 - 5

Exterior Grade – Marine Grade, Exterior Core, and Sheathing

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
Bisphenol A-epichlorohydrin polymer	Bisphenol A-epichlorohydrin polymer 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane / 4,4'-(1-Methylethylidene)bisphenol polymer with (chloromethyl)oxirane / Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane / Epichlorohydrin-4,4'-isopropylidenediphenol resin / Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane / Epichlorohydrin-bisphenol A resin / 4,4'-Isopropylidenediphenol-epichlorohydrin polymer / Diphenylolpropane-epichlorohydrin resin / Polymer of 4,4'-isopropylidenediphenol and 1-chloro-2,3-epoxypropane / 2,2-Bis(4-hydroxyphenyl)propane-epichlorohydrin copolymer / Poly(bisphenol A/epichlorohydrin) / Bisphenol A-epichlorohydrin, reaction product / 4,4'-ISOPROPYLIDENEDIPHENOL/EPICHLOROHYDRIN COPOLYMER / UP 5-207 / Epoxy adhesive UP 5-207 / Poly[2-(chloromethyl)oxirane-alt-4,4'-(propane-2,2-diyl)diphenol] / (Chloromethyl)oxirane, 4,4'-(1-methylethylidene)bisphenol copolymer / Epichlorohydrin/bisphenol A copolymer / Polymer mainly composed of epichlorohydrin/bisphenol A / Reaction product: bisphenol A-epichlorohydrin / 4,4'-Isopropylidenediphenol/epichlorohydrin copolymer	CAS-No.: 25068-38-6	0.1 < 1
Glass, oxide, chemicals	Glass, oxide, chemicals Glass, oxide / Glass / Sodium calcium polyphosphate / Glass powder / Calcium sodium polyphosphate / Sodium calcium polyphosphate silicate / Sodium zinc potassium polyphosphate / Glass flake / Calcium aluminum borosilicate / Glass dust / GLASS / Fiberglass / CALCIUM ALUMINUM BOROSILICATE / Calcium sodium borosilicate	CAS-No.: 65997-17-3	0.1 - 1
Pentaerythritol tetraacrylate	Pentaerythritol tetraacrylate 2-Propenoic acid, 2,2-bis[[(1-oxo-2-propenyl)oxy]methyl]-1,3-propanediyl ester / 2,2-Bis[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate / 2-Propenoic acid, 1,1'-[2,2-bis[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester / 2,2-Bis(hydroxymethyl)-1,3-propanediol, tetra(2-propenoyl) ester / 2,2-Bis[(acryloyloxy)methyl]propane-1,3-diyl diacrylate / PENTAERYTHRITYL TETRAACRYLATE / Tetraester of acrylic acid with pentaerythritol / Pentaerythrityl tetraacrylate	CAS-No.: 4986-89-4	0.1 < 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

- | | |
|-------------------------------------|--|
| First-aid measures general | : IF exposed or concerned: Get medical advice/attention. |
| First-aid measures after inhalation | : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. |

Exterior Grade – Marine Grade, Exterior Core, and Sheathing

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Dust may cause respiratory tract irritation.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Dust may cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause cancer by inhalation.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible dust. Products of combustion may include, and are not limited to: oxides of carbon. Toxic fumes. Nitrogen oxides. Oxides of sulfur. Aldehydes.
Explosion hazard	: Airborne dust in sufficient concentrations when confined and exposed to a sufficient ignition source can explode.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Use only non-sparking tools.
------------------	--

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

Exterior Grade – Marine Grade, Exterior Core, and Sheathing

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.3. Methods and material for containment and cleaning up

- For containment : Contain spill, then place in a suitable container. Minimize dust generation. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin and eyes. Avoid generating and breathing dust. Do not swallow. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Use only in well ventilated areas. Handling this product may result in electrostatic accumulation. Use proper grounding procedures.
- Hygiene measures : Wash contaminated clothing before reuse. Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep away from sources of ignition. Keep out of the reach of children. Store in a dry, cool and well-ventilated place. Store locked up. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exterior Grade – Marine Grade, Exterior Core, and Sheathing	
No additional information available	
Wood dust, all soft and hard woods (Not applicable)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m ³ (inhalable particles)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	0.75 mg/m ³ (50 mppcf) (Total Dust)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	1 mg/m ³
Phenol-formaldehyde polymer (9003-35-4)	
No additional information available	
Glass, oxide, chemicals (65997-17-3)	
No additional information available	
Bisphenol A-epichlorohydrin polymer (25068-38-6)	
No additional information available	

Exterior Grade – Marine Grade, Exterior Core, and Sheathing

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Pentaerythritol tetraacrylate (4986-89-4)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e, there is not leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Lumber.
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability	: May form combustible dust concentrations in air. Capable of catching fire.
Vapour pressure	: No data available
Relative vapour density at 20°C / 68 °F	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available

Exterior Grade – Marine Grade, Exterior Core, and Sheathing

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. May form combustible dust concentrations in air.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials. Avoid dust formation.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Toxic fumes. Nitrogen oxides. Aldehydes. Oxides of sulfur.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Phenol-formaldehyde polymer (9003-35-4)

LD50 oral rat	> 5 g/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat	> 5 mg/l air Animal: rat, Guideline: other:, Remarks on results: other:

Glass, oxide, chemicals (65997-17-3)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
---------------	---

Bisphenol A-epichlorohydrin polymer (25068-38-6)

LD50 oral rat	11400 mg/kg
---------------	-------------

Exterior Grade – Marine Grade, Exterior Core, and Sheathing

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Bisphenol A-epichlorohydrin polymer (25068-38-6)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal rabbit	20 ml/kg (Toxnet)
ATE CA (oral)	11400 mg/kg bodyweight

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: May cause cancer.

Wood dust, all soft and hard woods (Not applicable)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes

Bisphenol A-epichlorohydrin polymer (25068-38-6)	
NOAEL (chronic, oral, animal/male, 2 years)	15 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
NOAEL (chronic, oral, animal/female, 2 years)	100 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)

Reproductive toxicity	: Not classified.
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Not classified.

Phenol-formaldehyde polymer (9003-35-4)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: other:

Aspiration hazard	: Not classified.
Symptoms/effects after inhalation	: Dust may cause respiratory tract irritation.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Dust may cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause cancer by inhalation.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
-------------------	---

Exterior Grade – Marine Grade, Exterior Core, and Sheathing

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Phenol-formaldehyde polymer (9003-35-4)	
EC50 - Crustacea [1]	172 mg/l Test organisms (species): Daphnia pulex
Bisphenol A-epichlorohydrin polymer (25068-38-6)	
LC50 - Fish [1]	1.2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	≈ 2 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Exterior Grade – Marine Grade, Exterior Core, and Sheathing	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Exterior Grade – Marine Grade, Exterior Core, and Sheathing	
Bioaccumulative potential	Not established.
Phenol-formaldehyde polymer (9003-35-4)	
Partition coefficient n-octanol/water	3.564 (at 25 °C (at pH 4.6)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14: Transport information

In accordance with DOT / TDG

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (TDG) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

Exterior Grade – Marine Grade, Exterior Core, and Sheathing

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

TDG

Transport hazard class(es) (TDG) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable

Packing group (TDG) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Wheat flour

CAS-No. 130498-22-5

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories

15.2. International regulations

No additional information available

15.3. US State regulations

 **WARNING:** Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to www.P65Warnings.ca.gov/wood. This product can expose you to Bisphenol A, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date : 10/06/2023

Other information : Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com



Full text of H-statements

Carc. 1A Carcinogenicity, Category 1A

Comb. Dust Combustible Dust

Exterior Grade – Marine Grade, Exterior Core, and Sheathing

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Full text of H-statements	
Skin Sens. 1	Skin sensitisation, Category 1

SDS HazCom 2012 - WHMIS 2015 (Nexreg) 2023

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.