

Roseburg DuraTemp® Real Wood Siding

OVERVIEW

DuraTemp® is a panelized plywood siding product that offers a beautiful and durable solution for existing siding repairs, backyard storage, inspired hideaways, and more. Its plywood construction means the back requires no further finishing when used in an uninsulated application like a shed or barn. Plywood siding is also stronger and lighter than most competitive siding products. DuraTemp can be applied directly to studs 16" OC and its textured, tempered hardboard face offers excellent protection against the elements when properly finished.

FEATURES

- Plywood construction
- Lighter than most competitive siding products
- NAUF (no added urea formaldehyde) resin
- Available raw or with a factory-applied primer
- 50-year limited warranty
- Easy installation and painting
- Face is free of patches and repairs

SPECIFICATIONS

Lengths: 7', 8', 9', 10'

Width: 4'

Thickness: 3/8", 15/32", 19/32"

Grades: APA - PS 1-09 Specifications

Face Veneer: Thick, tempered hardboard

Core Veneer: Western Softwood

Back Veneer: C grade or better western softwood

Adhesive: NAUF exterior, water resistant phenolic glue

Primed: Optional

Surface: Textured

Patching: Patch-free

Edge: Shiplap

Groove Patterns:

Channel - Shallow, Medium, Deep
"V"

12" RB&B

Flame Spread Rating: Spread index of 126.2
(allowable 75-200)

Glue Bond Testing: All Roseburg plywood has been through rigorous tests for exposure 1 performance, including a 9-cycle boil test. Routine vacuum-pressure tests and 2-cycle boil tests are performed by APA

Shear Values: Meets allowable shear values for wind and seismic forces according to the UBC

FINISHING

For detailed installation and finishing instructions, please visit: www.roseburg.com/product/duratemp-siding/

- Finish as soon as possible after installation
- DuraTemp® is available pre-primed with an exterior latex primer
- Do not stain or use vinyl acrylic exterior paint
- Apply quality exterior gloss or semi-gloss latex house paint formulated for wood as recommended by your paint supplier
- Paint application by brush or roller provides the best results - when spraying, back brushing may be required, especially in the grooves

INSTALLATION Consult APA for complete application instructions

THICKNESS	SPAN RATING (IN.)	MAXIMUM STUD SPACING	NAIL SIZE	NAIL SPACING	
				Panel Edges	Intermediate Supports
		Long Dimension Vertical*	(use nonstaining box, siding or casing nails)		
3/8" - 4", 8" Patterns	16 OC	16 OC	6d for siding max. 1/2" thick; 8d for thicker siding	6	12
15/32" - 4", 8" Patterns	16 OC	16 OC		6	12
19/32" - 4", 8" Patterns	16 OC	16 OC		6	12
19/32" - RBB 12"	16 OC	16 OC		6	12

*DuraTemp should always be installed in a vertical orientation

CERTIFICATIONS

- Manufactured to meet APA - The Engineered Wood Association performance standards outlined in Product Standard 1-09 for: veneer grades, glue and bond durability, thickness requirements, testing procedures, finished plywood tolerances, and identification and stamping guidelines
- Approved by ICBO/ICCES Report No. ESR-2586, HUD-UM-40C
- DuraTemp APA Report PR-C302

MANUFACTURING LOCATION

- Riddle, Oregon