# Medite Premium

MDF

PEMBROKE, ONTARIO

TECHNICAL DATA		
Widths*	4, 5 & 6 ft	1.22, 1.52 & 1.83 m
Lengths*	up to 16 ft	up to 4.88 m
Thicknesses	1/4 – 1 in	6.35 – 25.40 mm
Density	45.3 lbs/ft³	726 kg/m³
Internal Bond	110 psi	0.76 N/mm <sup>2</sup>
Modulus of Rupture/MOR	4,350 psi	30 N/mm²
Modulus of Elasticity/MOE	507,000 psi	3,500 N/mm <sup>2</sup>
Screw Holding - Face**	300 lbf	1,334 N
Screw Holding - Edge**	250 lbf	1,112 N
Thickness Swell	≤ 11.0%	
Linear Expansion	≤ 0.33%	
Moisture Content	4 - 6%	
Flame Spread Rating	Class C (3)	
Dimensional Tolerances:		
Length/Width Squareness Thickness – panel average from specified	±0.080 in ±0.036 in/ft ±0.005 in	±2.0 mm ±3.0 mm/m ±0.125 mm
Thickness – variance from panel average	±0.005 in	±0.125 mm

Values represent averages for 3/4" panels. Mechanical properties are tested in accordance with ASTM D1037.

Customer-specified grades are available by request and subject to minimum order quantities.

\*Actual length and width panel dimensions are one inch longer than stated size

# MEDIUM DENSITY FIBERBOARD

Premium-grade MDF panels with improved strength and machining capabilities.

# **COMMON APPLICATIONS**

- Cabinetry (wood veneer or HPL)
- Furniture
- Signs
- Lamination (TFL or wood veneer)
- · Wall cladding/wainscot
- Countertop substrate
- · Decorative ceiling panels
- · Commercial casework











<sup>\*\*</sup>Note: panels less than 3/8" are not tested for Screw Holding.

# Medite Premium

MDF

PEMBROKE, ONTARIO

# STANDARDS & CERTIFICATIONS

# Formaldehyde Emissions Regulations – Third party certified (TPC-1) to meet the requirements of:

- EPA Formaldehyde Emission Regulation, TSCA Title VI\*
- Standards Council of Canada Formaldehyde Emissions Standard for Composite Wood Products CAN/CSA 0160-16\*
- California Air Resources Board (CARB) ATCM 93120\*

## **Recycled Content**

95% pre-consumer recycled content in accordance with ISO 14021 requirements\*

## Forest Stewardship Council®

Scientific Certification Systems Certified (SCS-COC/CW-00300) - FSC-C017580 FSC® Mix and FSC® Controlled Wood - AVAILABLE OPTION\*

#### **Eco-Certified Composite Grademark Program**

CPA ECC Sustainability Standard\*

\*Certificates and documentation available at Roseburg.com

## **GREEN BUILDING SUPPORT:**

For LEED® and other green building support documentation, visit roseburg.com/product/medite-premium









