

Shelving



Roseburg shelving is available in a variety of sizes, cores, and edge shape and treatment options with a finished face, back and up to all four edges. Our MelaGard particleboard shelving offers a Duramine® Thermally Fused Laminate surface.

MAKING LIVES BETTER FROM THE GROUND UP.

 **Roseburg**

Shelving

TECHNICAL DATA

Surfaces	MelaGard – Thermally fused laminate Raw
Cores	UltraBlend Particleboard (TSCA Title VI) SkyBlend Particleboard (ULEF)
Edge Profile	Square or Bullnose
Edge Treatment	Unfinished, Edge-banded, Square-edge banded up to 3 edges
Face Profile	Drilled 1 side or 2 sided
Widths*	11.25", 11.75", 12", 15.25", 15.75", 16", 23.25", 23.75", 24"
Lengths*	36", 48", 72", 97", 121", 145"
Thickness	3/4" standard (5/8" is available)

*Actual length and width panel dimensions are one inch longer than stated size

INSTRUCTIONS FOR USE


Maintenance: Except for natural unfinished particleboard, Roseburg shelving can be easily cleaned with warm water and mild soaps. Do not use cleaners containing abrasives, acids or alkalis.

Machining Sawing Tips: With the proper selection and maintenance of power cutting tools, Roseburg shelving can be easily machined. Carbide-tipped cutting tools are recommended for sawing, drilling, routing, joining, fastening and edge-machining. Remember: a portable 7-1/4" saw can chip the upper side of the panel (saw face down), and a table or radial-arm saw can chip the bottom edge (saw face up). In all instances, the saw should be maintained so as to ensure low vibration and smooth runout, clean collars, and sharp, properly ground teeth.

Handling and Storage:

- Store indoors in a dry, clean, well ventilated area.
- Separate units with clean, dry spacers of uniform thickness aligned carefully. Use a minimum of three spacers for panels up to 8' long and four or five spacers for longer panels, to prevent warp.
- Avoid temperature and moisture extremes.
- Keep units off the floor to prevent moisture absorption.
- Before processing, allow panels to equalize to surrounding moisture and temperature conditions for a minimum of 72 hours.
- For appropriate shelving design and installation guidelines refer to CPA Technical Bulletin.

DESIGN OPTIONS



291 White TFL



Raw Particleboard



White or Raw Available with a Bullnose Edge

FEATURES AND BENEFITS

Manufactured with a variety of cores and available either raw or with a finished face, back and edges. All components come in standard sizes that are perfect for designing any storage application. Roseburg shelving is ready to install. Each piece is pre-cut and drilled to convenient widths and lengths for easy installation. The strength of composite panels creates a sturdy and durable product that is perfect for a multitude of residential and commercial applications.

COMMON APPLICATIONS

- Kitchens
- Pantries
- Closets
- Craft rooms
- Childrens rooms
- Laundry rooms
- Garages

STANDARDS & CERTIFICATIONS

- EPA Formaldehyde Emission Regulation, TSCA Title VI compliant
- CPA ECC Sustainability Standard
- Produced using 100% pre-consumer recycled wood fiber