# **UltraBlend**

# **PARTICLEBOARD**

MISSOULA, MT

| TECHNICAL DATA   |   |                 |
|--|---|-----------------|
|  | UltraBlend  | UltraBlend Plus |
| Widths   | 4 & 5 ft  | 4 & 5 ft        |
| Lengths  | up to 12 ft   | up to 12 ft     |
| Thicknesses  | 5/8 – 3/4 in  | 1/2 – 1-1/8 in  |
| Density  | 44 lbs/ft³  | 46 lbs/ft³      |
| Internal Bond  | 65 psi  | 80 psi          |
| Modulus of Rupture/MOR   | 1,600 psi   | 1,900 psi       |
| Modulus of Elasticity/MOE  | 325,000 psi   | 400,000 psi     |
| Screw Holding - Face   | 225 lbs   | 250 lbs         |
| Screw Holding - Edge   | 160 lbs   | 180 lbs         |
| Linear Expansion   | 0.40%   |                 |
| Flame Spread Rating  | Class C (3)   |                 |
| Dimensional Tolerances: Length/Width Squareness Thickness – panel average from specified Thickness – variance from | ±0.080 in<br>±0.036 in/ft<br>±0.008 in<br>+0.004 in |                 |
| panel average  |   |                 |

Values represent averages for 3/4" panels. Mechanical properties are tested in accordance with ASTM D1037.

Customer-specified grades are available by request and subject to minimum order quantities.

## **PARTICLEBOARD**

Composite western softwoods particle panel with superior lamination and machining characteristics.

# **COMMON APPLICATIONS**

- Laminating
- Countertops
- Cabinets
- Furniture
- Shelving
- · Stair treads













# **PARTICLEBOARD**

MISSOULA, MT

## STANDARDS & CERTIFICATIONS

Roseburg UltraBlend and UltraBlend Plus Particleboard is tested and certified to meet or exceed the following standards and certifications

**ANSI A208.1** – American National Standard – Particleboard for Interior Applications

✓ Meets or exceeds general requirements of ANSI A208.1

Formaldehyde Emissions Regulations - Third-Party Certified (TPC-1) to meet the requirements of:

✓ EPA Formaldehyde Emission Regulation, TSCA Title VI\*

Standards Council of Canada Formaldehyde Emissions Standard for Composite Wood Products – CAN/CSA 0160-16\*

✓ California Air Resources Board (CARB) ATCM 93120\*

# **Recycled Content**

√ 90% pre-consumer recycled content in accordance with ISO 14021 requirements\*

#### Forest Stewardship Council®

Scientific Certification Systems Certified (SCS-COC/CW-00300) – FSC-C017580 FSC® Mix and FSC® Controlled Wood - AVAILABLE OPTION\*

### **Environmental Product Declaration**

✓ Type III Product Specific EPD certified by UL Environment\*

#### **Eco-Certified Composite Grademark Program**

✓ CPA ECC Sustainability Standard\*

\*Certificates and documentation available at Roseburg.com

#### **GREEN BUILDING SUPPORT:**

For LEED® and other green building support documentation, visit roseburg.com/product/ultrablend-particleboard









