

## Acceptable Sealants for Use with Senergy® Wall Systems

TECHNICAL BULLETIN  
1025735

The following sealants have been tested by the sealant manufacturer and are acceptable for use on above grade application of Senturion™, Senerflex®, Senerthik®, Senergy Stucco, Senergy Cement-Board Stucco™ Wall Systems and all Senergy Surfacing Systems:

1. Sonolastic 150 with VLM Technology / Sonneborn Primer 2000
2. Dow 791/1200 Prime Coat
3. Dow 795/1200 Prime Coat
4. Dow 790/1200 Prime Coat
5. GE SilPruf
6. GE SilPruf LM

GE sealants may require Primer SS4004P; please consult with GE for recommendations.

### SEALANT NOTES

Apply primer/sealant per manufacturer's instructions to dry Senergy reinforced Base Coat, Senergy ASAP or COLOR COAT that has been applied to dry Senergy reinforced Base Coat.

Sealant joint sizing, type, and configuration are the responsibility of the design professional.

Sealants and bond breakers or backer rods (closed cell or soft non gassing backer rod; do not use open cell backer rod.) shall be used and installed as per the sealant manufacturer's specifications and recommendations concerning application/installation of all primary and/or secondary sealants as well as bond breakers and backer rods. Consult sealant manufacturer for recommendations regarding the application of sealant to plastic or metal.

If a sealant isn't listed above, consult the sealant manufacturer for their recommendation and approval.

See current Senergy specifications, details, product and technical bulletins for additional information on Senergy Wall Systems. BASF Wall Systems makes no warranty, express or implied, concerning the use of sealants.

Field test applications of sealants should be performed per sealant manufacturer's recommendations prior to start of project and on a regular basis during the project.

### TECHNICAL INFORMATION

Consult our Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy website, [www.senergy.basf.com](http://www.senergy.basf.com), for additional information about products and systems and for updated literature.

# Acceptable Sealants for Use with Senergy® Wall Systems

## Note

BASF Wall Systems is an operating unit of BASF Construction Chemicals, LLC. (herein after referred to as "BASF Wall Systems")

## Residential Policy

On one and two-family residential framed construction, BASF Wall Systems requires that the wall system selected be one that includes provisions for water drainage. The choices include Senturion® line of water drainage EIFS, commercial Senerflex® Channeled Adhesive or Channeled Insulation Design, Senergy Stucco Wall System, and Senergy Cement-Board Stucco™ Systems. There are no exceptions to this policy. Under no circumstances will BASF Wall Systems warrant the use of any other system on this type of construction without expressed written authorization from BASF Wall Systems [Residential construction using EIFS on masonry (CMU) or poured concrete does not require the additional water drainage provisions described above. Senergy Exterior Surfacing Systems for insulating concrete forms are also acceptable.] See the Senergy Residential Policy Bulletin for a more detailed discussion of this topic. Consult BASF Wall Systems Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy website, [www.senergy.basf.com](http://www.senergy.basf.com) for additional information about products and systems and for updated literature.

## Disclaimer

This information and all further technical advice are based on BASF Wall Systems' present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, BASF Wall Systems disclaims any and all CONDITIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. BASF WALL SYSTEMS SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF Wall Systems reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

## BASF Wall Systems

3550 St. Johns Bluff Road South  
Jacksonville, FL 32224-2614  
Phone 800 • 221 • 9255  
Fax 904 • 996 • 6300  
[www.senergy.basf.com](http://www.senergy.basf.com)