

AnticoGlaze™ CS

COLORS

Available in 8 standard colors:

- Venetian Red
- Coral Siena
- Desert Earth
- Midnight Mist
- Sunset Gold
- Castillo Garden
- Silver Lake
- Sicilian Sand

Variation of the final look can be achieved by using different colored finish and textures of the finish.

PACKAGING

16 lbs. (7.25 kg) per 2-gallon pail

COVERAGE

1000 ft² per 2 gallon

*Coverage rates are for estimation only and will vary according to application techniques.

SHELF LIFE

Two (2) years when properly stored in original container.

DESCRIPTION

A convenient stain or glaze product consisting of a 100% acrylic polymer clear base that is distributor tinted. AnticoGlaze CS produces beautiful aesthetics with varied degrees of mottling, coloration and glaze.

USES

AnticoGlaze CS is an antiquing stain product used to impart an 'old world' mottled look to stucco and EIFS exterior wall systems that are surfaced with an acrylic or elastomeric textured finish.

ADVANTAGES

Array of colors available

Excellent weather resistance

Silicone enhanced

A perfect balance of base to pigment, allowing for color highlighting, but not hiding of the substrate

Fast drying

MIXING

Mix the contents of the AnticoGlaze CS pail with a paddle and low speed drill until thoroughly blended. Ensure all the pigment is well dispersed within the liquid. Periodic mixing with a gentle stirring action is recommended while using the product. If the product sits overnight, remix for one minute with the drill mixer before using.

- Do not over mix as this will create excessive air.
- Additives are not permitted.
- Close container when not in use.
- Clean tools with soap and water immediately after use.

SURFACE PREPARATION AND CONSIDERATIONS

Finish surface must be clean, dry, sound and free of loose material, paint, efflorescence, contaminants and other coatings.

- Minimum application temperature is 50°F (10°C) and rising to maximum of 90°F (32°C)
- Ensure that windows and surrounding areas are masked, if contact occurs on windows, remove immediately with a damp cloth before sealer dries.
- AnticoGlaze CS is a freestyle product that produces a look that is greatly influenced by the application technique. It is best to apply the material thinly and repeat the application if necessary to create depth rather than removing excess product.
- A mock up is recommended to ensure a desired look is achieved based on chosen application technique.

APPLICATION

RANDOM SPONGE TECHNIQUE

Dip a clean damp sponge into the AnticoGlaze CS product and apply the product to the wall in a random fashion, achieving a swirled or sponged-on look. Color, depth and contrast are achieved by distributing the product randomly with the final appearance in mind.

SPRAY TECHNIQUE

Airless sprayer equipment recommendation:

- 1 GPM or 0.54 GPM airless sprayer.
- Tip size: .15 - .17
- Pump pressure and tip size per spray applicator preference
- Refer to manufacturer's instructions and tip offering.

Lightly and randomly spray the product on the wall with a low pressure sprayer.

Back float the product using a float as needed to remove or soften the look of the color application. Frequently squeeze or rinse with water any excess product from the sponge float.

DRY TIME

Approximately 3 hours at 73°F (23°C) but may vary depending upon the ambient weather conditions. Protect newly applied material from rain and temperatures less than 45°F (7°C) for at least 24 hours after application

LIMITATIONS

1. Not for use on damp surfaces, below grade applications or on surfaces subject to water immersion.
2. Apply only when air and surface temperature is between 50°F and 90°F (10°C and 32°C). Do not apply if surface or ambient temperature is expected to fall below 45°F (7°C) within 24 hours after application unless supplemental heat is provided during installation and drying period for at least 24 hours after installation and until dry.
3. Protect work from precipitation until dry.
4. Do not apply to frozen surfaces.
5. Not for application over Tersus products.
For questions regarding application over other products, contact technical services.

SHIPPING & STORAGE

- Protect materials during transportation to avoid physical damage. Store in a cool, dry place protected from freezing, extreme heat and direct sun. Store at no less than 40°F (4°C) and not greater than 85°F (29°C)
- Do not stack pallets.

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting mbcc.sika.com/en-us, e-mailing your request to mbsbscst@mbcc-group.com or calling +1 (800) 433-9517. Use only as directed.

IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.

TECHNICAL SUPPORT

Consult Master Builders Solutions Technical Services Department at +1 (800) 589-1336 for specific recommendations concerning all other applications. Consult the Wall Systems website at mbcc.sika.com/en-us, for additional information about products and systems and for updated literature.

LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including

but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.

For the most current version of this literature, please visit our website at mbcc.sika.com/en-us.