

Revision date: 2018/02/15 Page: 1/11
Version: 3.0 (30516515/SDS\_GEN\_US/EN)

## 1. Identification

### Product identifier used on the label

## **AURORA TC100 BUTTE**

#### Recommended use of the chemical and restriction on use

Recommended use\*: for industrial and professional users

## Details of the supplier of the safety data sheet

Company:

BASF CORPORATION 100 Park Avenue Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

### **Emergency telephone number**

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification
Chemical family: Coating

## 2. Hazards Identification

## According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

### Classification of the product

Skin Sens. 1 Skin sensitization

STOT RE 1 (by inhalation) Specific target organ toxicity — repeated

exposure

## Label elements

Pictogram:

<sup>\*</sup> The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Revision date : 2018/02/15 Page: 2/11 Version: 3.0 (30516515/SDS\_GEN\_US/EN)



Signal Word: Danger

Hazard Statement:

H317 May cause an allergic skin reaction.

H372 Causes damage to organs (Lung) through prolonged or repeated

exposure (inhalation).

Precautionary Statements (Prevention):

P280 Wear protective gloves.

P260 Do not breathe dust/gas/mist/vapours.

P270 Do not eat, drink or smoke when using this product.

P264 Wash with plenty of water and soap thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P314 Get medical advice/attention if you feel unwell.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or

doctor/physician.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection

point.

## Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

## 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

| CAS Number | <u>Weight %</u>   | Chemical name                    |
|------------|-------------------|----------------------------------|
| 14808-60-7 | >= 50.0 - < 75.0% | crystalline silica               |
| 1309-37-1  | >= 1.0 - < 3.0%   | Iron oxide                       |
| 1332-58-7  | >= 1.0 - < 3.0%   | Kaolin                           |
| 13463-67-7 | >= 1.0 - < 3.0%   | Titanium dioxide                 |
| 34375-28-5 | >= 0.1 - < 0.2%   | Ethanol, 2-(hydroxymethylamino)- |

## 4. First-Aid Measures

## **Description of first aid measures**

#### General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

Revision date: 2018/02/15 Page: 3/11 Version: 3.0 (30516515/SDS\_GEN\_US/EN)

#### If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

#### If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

#### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

#### If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting.

## Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see

section 2) and/or in section 11.

Hazards: No applicable information available.

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no

known specific antidote.

## 5. Fire-Fighting Measures

## **Extinguishing media**

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

### Advice for fire-fighters

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

## Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

Revision date : 2018/02/15 Page: 4/11 Version: 3.0 (30516515/SDS\_GEN\_US/EN)

## 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

## **Environmental precautions**

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

## 7. Handling and Storage

## Precautions for safe handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

## Conditions for safe storage, including any incompatibilities

No applicable information available.

Suitable materials for containers: High density polyethylene (HDPE)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

Protect from temperatures below: 0 °C

The packed product must be protected from temperatures below the indicated one.

Protect from temperatures below: 32 °F

The packed product must be protected from temperatures below the indicated one.

### 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

| Iron oxide | OSHA PEL | PEL 10 mg/m3 fumes/smoke; TWA value 10 |
|------------|----------|--|
|            |          | mg/m3 fumes/smoke ;                    |
|            | 4000     |  |

ACGIH TLV TWA value 5 mg/m3 Respirable fraction;

Kaolin OSHA PEL PEL 5 mg/m3 Respirable fraction ; PEL 15

 $\,$  mg/m3  $\,$  Total dust  $\,$  ; TWA value  $\,$  5 mg/m3  $\,$  Respirable fraction  $\,$  ; TWA value  $\,$  10 mg/m3  $\,$ 

Total dust;

ACGIH TLV TWA value 2 mg/m3 Respirable fraction;

The value is for particulate matter containing no

asbestos and <1% crystalline silica.

Titanium dioxide OSHA PEL PEL 15 mg/m3 Total dust : TWA value 10

mg/m3 Total dust ;

ACGIH TLV TWA value 10 mg/m3;

Revision date : 2018/02/15 Page: 5/11 Version: 3.0 (30516515/SDS\_GEN\_US/EN)

crystalline silica OSHA PEL TWA value 0.1 mg/m3 Respirable dust ; TWA

value 2.4 millions of particles per cubic foot of air

Respirable;

The exposure limit is calculated from the

equation, 250/(%SiO2+5), using a value of 100% SiO2. Lower percentages of SiO2 will yield higher

exposure limits.

TWA value 0.1 mg/m3 Respirable; The exposure limit is calculated from the

equation, 10mg/m3)/(%SiO2+2), using a value of 100% SiO2. Lower percentages of SiO2 will yield

higher exposure limits.

ACGIH TLV TWA value 0.025 mg/m3 Respirable fraction;

#### Advice on system design:

No applicable information available.

#### Personal protective equipment

#### Respiratory protection:

Wear appropriate certified respirator when exposure limits may be exceeded.

#### Hand protection:

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

#### Eye protection:

Safety glasses with side-shields.

## **Body protection:**

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

#### General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

## 9. Physical and Chemical Properties

Form: paste

Odour: ammonia-like, slight odour

Odour threshold: No applicable information available.

Colour: various colours

pH value: 9 - 10

Melting point:

Boiling point:

No applicable information available.

No applicable information available.

No applicable information available.

Revision date : 2018/02/15 Page: 6/11 Version: 3.0 (30516515/SDS\_GEN\_US/EN)

Flash point: A flash point determination is

unnecessary due to the high water

content.

Flammability: not determined

Upper explosion limit: No applicable information available. Autoignition: Study does not need to be conducted. Vapour pressure: The product has not been tested.

Density: approx. 15.5 lb/USg

(20°C)

Relative density: 1.86

(20°C)

Vapour density: No applicable information available. Partitioning coefficient n- No applicable information available.

octanol/water (log Pow):

Self-ignition not self-igniting temperature:

Thermal decomposition: No decomposition if stored and handled as

prescribed/indicated.

Viscosity, dynamic: No applicable information available. Viscosity, kinematic: No applicable information available.

Solubility in water: soluble

Solubility (quantitative): No applicable information available. Solubility (qualitative): No applicable information available. Evaporation rate: No applicable information available.

Other Information: If necessary, information on other physical and chemical

parameters is indicated in this section.

## 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

## Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

#### **Conditions to avoid**

See MSDS section 7 - Handling and storage.

### Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

### **Hazardous decomposition products**

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

Revision date : 2018/02/15 Page: 7/11
Version: 3.0 (30516515/SDS\_GEN\_US/EN)

## 11. Toxicological information

## Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### **Acute Toxicity/Effects**

### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Virtually nontoxic by inhalation. The product has not been tested. The statement has been derived from the properties of the individual components.

#### Oral

No applicable information available.

#### Inhalation

No applicable information available.

#### Dermal

No applicable information available.

#### Assessment other acute effects

No applicable information available.

## Irritation / corrosion

Assessment of irritating effects: May cause slight irritation to the eyes. May cause slight irritation to the skin. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### Sensitization

Assessment of sensitization: May cause sensitization by skin contact.

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: This product contains crystalline silica (quartz). Prolonged or repeated inhalation of respirable crystalline silica may result in silicosis.

#### Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from the properties of the individual components.

#### Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from the properties of the individual components.

### Information on: crystalline silica

Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. In long-term animal studies in which the substance was given by inhalation in high doses, a carcinogenic effect was observed. The substance and its compounds in the form of respirable dusts/aerosolsis classified by the German MAK commision as a category 1 carcinogen (substances that cause cancer to humans). A carcinogenic effect cannot safely be ruled out. The inhalation uptake of the alveolar fraction of the fine dust may

Revision date : 2018/02/15 Page: 8/11 Version: 3.0 (30516515/SDS\_GEN\_US/EN)

cause damage to the lungs. The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

NTP listed carcinogen

Information on: Titanium dioxide

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

\_\_\_\_\_

#### Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from the properties of the individual components.

### **Teratogenicity**

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from the properties of the individual components.

#### Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from products of a similar structure and composition.

#### Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

## 12. Ecological Information

## **Toxicity**

Aquatic toxicity

Assessment of aquatic toxicity:

At the present state of knowledge, no negative ecological effects are expected. There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

## Persistence and degradability

## Assessment biodegradation and elimination (H2O)

Inherently biodegradable. The insoluble fraction can be removed by mechanical means in suitable waste water treatment plants.

### Bioaccumulative potential

Assessment bioaccumulation potential

Revision date: 2018/02/15 Page: 9/11 Version: 3.0 (30516515/SDS\_GEN\_US/EN)

No data available.

Discharge into the environment must be avoided.

### Mobility in soil

Assessment transport between environmental compartments

No data available.

#### **Additional information**

Other ecotoxicological advice:

There is a high probability that the product is not acutely harmful to aquatic organisms. Do not discharge product into the environment without control. The product has not been tested. The statement has been derived from the properties of the individual components.

Ecological data are not available. Do not allow to enter soil, waterways or waste water channels.

## 13. Disposal considerations

#### Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

## Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

## 14. Transport Information

## Land transport

**USDOT** 

Not classified as a dangerous good under transport regulations

#### Sea transport

**IMDG** 

Not classified as a dangerous good under transport regulations

## Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

## 15. Regulatory Information

#### **Federal Regulations**

#### Registration status:

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

Revision date : 2018/02/15 Page: 10/11 Version: 3.0 (30516515/SDS\_GEN\_US/EN)

| <b>CERCLA RQ</b> | CAS Number         | Chemical name  |
|------------------|--------------------|--|
| 5000 LBS         | 67-64-1; 71-36-3;  | Acetone; n-butanol; acrylic acid; cumene             |
|                  | 79-10-7; 98-82-8   |  |
| 1000 LBS         | 80-62-6; 1336-21-  | Methyl methacrylate; Ammonium hydroxide;             |
|                  | 6; 100-41-4; 1310- | ethylbenzene; Sodium Hydroxide                       |
|                  | 73-2               |  |
| 100 LBS          | 1330-20-7; 7664-   | Xylene; ammonia; 2-methylpropan-2-ol; dibutyl ether; |
|                  | 41-7; 75-65-0;     | 1,4-dioxane  |
|                  | 142-96-1; 123-91-  |  |
|                  | 1                  |  |
| 10 LBS           | 75-21-8            | Ethylene Oxide                                       |

#### **State regulations**

| State RTK | CAS Number | Chemical name      |
|-----------|------------|--------------------|
| PA        | 13463-67-7 | Titanium dioxide   |
|           | 14808-60-7 | crystalline silica |
|           | 1332-58-7  | Kaolin             |
|           | 1309-37-1  | Iron oxide         |
| MA        | 14808-60-7 | crystalline silica |
|           | 1332-58-7  | Kaolin             |
|           | 1309-37-1  | Iron oxide         |
|           | 13463-67-7 | Titanium dioxide   |
| NJ        | 13463-67-7 | Titanium dioxide   |
|           | 1332-58-7  | Kaolin             |
|           | 1309-37-1  | Iron oxide         |
|           | 14808-60-7 | crystalline silica |

## Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

**WARNING:** This product can expose you to chemicals including ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

## **NFPA Hazard codes:**

Health: 2 Fire: 1 Reactivity: 0 Special:

## 16. Other Information

#### SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2018/02/15

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Revision date: 2018/02/15 Page: 11/11
Version: 3.0 (30516515/SDS\_GEN\_US/EN)

PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. END OF DATA SHEET