



Belgian Lace Finish

PRODUCT BULLETIN
1017591

DESCRIPTION

Factory-mixed, 100% acrylic polymer finish coat with advanced technology to improve long-term performance and dirt pick-up resistance. BELGIAN LACE Finish has a fine "worm-holed" or rilled appearance which is achieved by the random aggregate sizes in the finish. The small "worm-holed" look can be circular, random, vertical or horizontal.

PACKAGING

31.7-kg per 19-liter pail
(70-lbs per 5-gallon pail)

COVERAGE

(Approximate) 14.8 m²
(160 ft²) per pail

COLORS

Available in a wide variety of standard and custom colors.

USES

1. BELGIAN LACE Finish provides an aesthetically pleasing surface color and texture for the Senenergy® Wall Systems.
2. BELGIAN LACE Finish can also be utilized as a textured coating for poured concrete or unit masonry, conventional; stucco, Senenergy Stucco Wall System, Senenergy Cement-Board™ Stucco, certain insulating concrete forms, and veneer plaster or gypsum wallboard (interior applications only).

Features	Benefits
100% Acrylic polymer chemistry	Long-term durability and weather resistance
Integral color	Reduced maintenance and recoating
Weather resistant	Repels water and resists wind-driven rain
Seals existing, non-moving hairline cracks	Protects
Breathable	Doesn't blister, peel or flake

Belgian Lace Finish

TECHNICAL INFORMATION

Consult the Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy website, www.senergy.basf.com, for additional information about products and systems and for updated literature.

MIXING

1. Thoroughly mix the factory-prepared BELGIAN LACE Finish with a mixer until thoroughly blended.
2. A small amount of clean, potable water may be added to adjust workability.
3. Additives are not permitted.
4. Close container when not in use.
5. Clean tools with soap and water immediately after use.

APPLICATION

1. Substrate shall be dry, clean, sound and free of releasing agents, paint or other residue or coatings. Verify substrate is flat, free of fins or planar irregularities greater than 6.4 mm in 3 m (1/4" in 10').
2. Apply BELGIAN LACE Finish directly to the Senergy Base Coat/Reinforcing Mesh with a clean, stainless steel trowel.
Note: In order to minimize the possibility of Base Coat read-through with 330 Maxi-White in BELGIAN LACE, we recommend the use of TINTED PRIMER. Base Coat read-through with BELGIAN LACE Finish in maxi-white is very applicator dependent.
3. Apply and level BELGIAN LACE Finish during the same operation to minimum obtainable thickness consistent with uniform coverage.
4. Maintain a wet edge on BELGIAN LACE Finish by applying and texturing continually over the wall surface.
5. Work BELGIAN LACE Finish to corners, joints or other natural breaks and do not allow material to set up within an uninterrupted wall area.
6. Float BELGIAN LACE Finish to achieve final texture.

LIMITATIONS

1. Protect Senergy materials during transportation and installation to avoid physical damage.
2. Store Senergy materials in a cool, dry place protected from freezing. Store at no less than 4°C (40°F). Protect from extreme heat and direct sunlight. Shelf life is two years when unopened and stored as directed.
3. Do not apply Senergy materials in ambient temperatures below 4°C (40°F). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4°C (40°F) prevail.
4. Do not apply Senergy materials to frozen surfaces.
5. Samples of BELGIAN LACE Finish are available from Senergy for color approval only. Samples for job approval must be made in the field by the applicator, and approved prior to ordering.

HEALTH AND SAFETY

Caution

May be harmful if vapors or mist are inhaled, if absorbed through skin, or if swallowed. May cause eye, skin and respiratory tract irritation. Swallowing this product can cause kidney damage.

Precautions

Avoid getting in eyes, on skin, or on clothing. Avoid breathing vapors or mist. Wear safety glasses or goggles, impervious gloves, and clothing with long sleeves and pants. If TLV or PEL can be exceeded, wear respirator selected by a technically qualified person. Wash thoroughly after handling. Wash contaminated clothing before reuse.

Spills

Wipe up small spills with rags. Absorb larger spills with sand, vermiculite, or kitty litter; sweep up and place in a suitable container for disposal.

First Aid

1. For eye contact, rinse eyes with water. Remove any contact lenses, and continue flushing with plenty of water for several minutes. SEEK MEDICAL ATTENTION if irritation develops and persists.
2. For skin contact, wash affected areas with plenty of water, and soap if available, for several minutes. SEEK MEDICAL ATTENTION if irritation develops and persists.
3. If inhaled, remove from area to fresh air. SEEK MEDICAL ATTENTION if respiratory irritation develops or if breathing becomes difficult.
4. If swallowed, give 3–4 glasses of water, but do not induce vomiting unless directed to do so by a physician. Do not give anything by mouth to an unconscious or convulsing person. SEEK MEDICAL ATTENTION.

Read Material Safety Data Sheets before using these products.

Note

BASF Wall Systems is an operating unit of BASF Construction Chemicals, LLC. (herein after referred to as "BASF Wall Systems")

Residential Policy

On one and two-family residential framed construction, BASF Wall Systems requires that the wall system selected be one that includes provisions for moisture drainage. The choices include Senturion® line of water managed EIFS, commercial Senerflex® Wall Systems integrating moisture management features, Senergy Stucco Wall System, and Senergy Cement-Board Stucco™ Systems. Senergy Exterior Surfacing Systems for insulating concrete forms are also acceptable. There are no exceptions to this policy. Under no circumstances will BASF Wall Systems warrant the use of any other system on this type of construction without expressed written authorization from BASF Wall Systems [Residential construction using EIFS on masonry (CMU) or poured concrete does not require the additional water management provisions described above.] See the Senergy Residential Policy Bulletin for a more detailed discussion of this topic. Consult BASF Wall Systems Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy web-site, www.senergy.cc for additional information about products and systems and for updated literature.

Disclaimer

This information and all further technical advice are based on BASF Wall Systems' present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, BASF Wall Systems disclaims any and all CONDITIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. BASF WALL SYSTEMS SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF Wall Systems reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

BASF Wall Systems

3550 St. Johns Bluff Road South
Jacksonville, FL 32224-2614
Phone 800 • 221 • 9255
Fax 904 • 996 • 6300
www.senergy.basf.com