

# Metallic Finish

100% acrylic polymer finish coat

## COLORS

Available in a wide range of standard and custom colors.

## TEXTURE

Fine

## PACKAGING

5 gallon pail (19 liter pail)

## COVERAGE

125 to 135 ft<sup>2</sup> (11.6 - 12.5 m<sup>2</sup>) per pail

## SHELF LIFE

2 years when stored in conditions described above.

## STORAGE

Store in original containers at temperatures at least 4 °C (40 °F) and not greater than 43 °C (110 °F). Store out of direct sunlight. Do not stack pallets



## DESCRIPTION

Metallic Finish is a 100% acrylic trowel-grade textured finish. It features an optimized combination of aggregates and metalescent pigments that combine the visual appeal of metal with the ease of application of a textured finish.

## FEATURES

Metal pigmentation

Optimized aggregate size

Abrasion resistant

Integral color

## BENEFITS

Provides a metal sheen

Enhanced metallic appearance, ease of application, hides minor surface imperfections

Durability

Reduced maintenance

---

## USES

1. Provides a protective, weather-resistant Metallic appearance to Master Builders Solutions Wall Systems.
2. Can also be used as a textured finish for poured concrete, stucco, unit masonry, certain insulating concrete forms, and interior veneer plaster or gypsum wallboard.

---

## MIXING

1. Thoroughly mix the factory-prepared Metallic Finish with a mixer until thoroughly blended.
2. A small amount of clean, potable water may be added to adjust workability.
3. Additives are not permitted.
4. Close container when not in use.
5. Clean tools with soap and water immediately after use.

---

## DRYING TIME

Approximately 12 hours to firm set, depending upon the ambient weather conditions, substrate absorbency and applied film thickness. Protect newly applied finish from rain and temperatures less than 4 °C (40 °F) for at least 24 hours after application.

---

## APPLICATION

1. Substrate shall be dry, clean, sound of free of releasing agents, paint or other residue or coatings. Verify substrate is flat, and free of fins or planar irregularities greater than 6.4 mm in 3 m (1/4" in 10').
2. Apply Metallic Finish directly to the Master Builders Solutions Base Coat/Reinforcing Mesh with a clean, stainless steel trowel.
3. Apply and level Metallic Finish during the same operation to minimum obtainable thickness consistent with uniform coverage.
4. Maintain a wet edge on Metallic Finish by applying and texturing continually over the wall surface.
5. Work Metallic Finish to corners, joints or other natural breaks and do not allow material to set up within an uninterrupted wall area.
6. Float Metallic Finish to achieve final texture.

---

## LIMITATIONS

1. Do not use on horizontal surfaces.
2. Protect materials during transportation and installation to avoid physical damage.
3. Store materials in a cool, dry place protected

from freezing. Store at no less than 4 °C (40 °F). Protect from extreme heat and direct sunlight. Shelf life is two years when unopened and stored as directed.

4. Do not apply Master Builders Solutions materials in ambient temperatures below 4 °C (40 °F). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4 °C (40 °F) prevail.
5. Do not apply Master Builders Solutions materials to frozen surfaces.
6. Samples of Metallic Finish are available from Master Builders Solutions for color approval only. Samples for job approval must be made in the field by the applicator, and approved prior to ordering.

---

## TECHNICAL SUPPORT

Consult Master Builders Solutions Technical Services Department at +1 (800) 589-1336 for specific recommendations concerning all other applications. Consult the Wall Systems website at [Master Builders Solutions.master-builders-solutions.com/en](http://MasterBuildersSolutions.master-builders-solutions.com/en), for additional information about products and systems and for updated literature.

---

## HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting [www.master-builders-solutions.com/en-us](http://www.master-builders-solutions.com/en-us), e-mailing your request to [mbsbscst@mbcc-group.com](mailto:mbsbscst@mbcc-group.com) or calling +1 (800) 433-9517. Use only as directed.

**IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.**

---

## VOC CONTENT

< 50 g/L less water and exempt solvents.

---

## LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products

but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

**FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.**

For the most current version of this literature, please visit our website at [www.master-builders-solutions.com/en-us](http://www.master-builders-solutions.com/en-us).