

# Poly 1

## 100% Acrylic Admixture

### COLOR

Milk white

### PACKAGING

18.1 kg per 19-liter pail  
(40 lbs per 5-gallon pail)

### COVERAGE

Approximate coverage for Class PM base coat:

- 10 m<sup>2</sup> (110 ft<sup>2</sup>) per mixed batch at 6 mm (1/4") thickness
- 6.9 m<sup>2</sup> (73 ft<sup>2</sup>) per mixed batch at 9.5 mm (3/8") thickness

### SHELF LIFE

One year when opened and stored as directed

### DESCRIPTION

100% acrylic admixture for use with stucco or Portland cement plaster mixes.

### USES

Poly 1 is an acrylic polymer modifier designed to enhance adhesion, workability, durability and the physical properties of unmodified stucco or Portland cement plaster mixes.

**Note: Not for use with cement plaster mixes that contain air entrainment agents.**

### SURFACE PREPARATION

1. All surfaces must be clean, dry, and free of dust, grease and contaminants.
2. New concrete, stucco, and masonry must be clean and cured a minimum of 28 days.

### MIXING

#### FIELD MIX STUCCO

1. The normal ratio of Poly 1 to clean potable water is 1 part Poly 1 to 3 parts water (1:3). Where increased physical and chemical resistance is required, increase the Poly 1 content in the mixing liquid to a 1:2 or to a 1:1 Poly 1 to water ratio. Use the following as a guide:
  - As a scrub coat applied before patching or overlays, use straight Poly 1.
  - Heavy build or thick applications such as stucco, use 1:2 in mild climates and 1:1 in cold to freezing climates.
  - For cement plasters or repair mortars, 1:3 or 1:2 should suffice for added strength.
2. Always mechanically mix. Do not over mix or mix at a high speed.

#### POLY 1 BASE FOR CLASS PM SYSTEM

1. Prepare in a container, which is clean and free of foreign substances. Do not use a container that has contained or been cleaned with a petroleum-based product.
2. Mix one bag (42.64 kg / 94 lbs) Portland Cement, 68-90.7 kg (150-200 lbs) silica sand, and one package .45 kg (1 lb) FIBERFILL with 1 pail of Poly 1 18.1 kg (40 lbs). Mix for three to five minutes to a homogeneous consistency.
3. Clean, potable water may be added to adjust workability.

### APPLICATION

1. For stucco plasters, place the mix into the lath as normal and avoid over troweling. The trowel should be cleaned frequently, kept wet, and used with minimal pressure.
2. For Class PM Base Coats, please follow instructions in current BASF Wall Systems literature for Class PM EIFS.
3. Maximum time for placement of a mix should not exceed 20 minutes. Higher air and surface temperatures will decrease working and placement time.

---

#### LIMITATIONS

1. Do not use Poly 1 with cement plaster mixes that contain air entrainment agents.
2. Protect materials during transportation and installation to avoid physical damage.
3. Store materials in a cool, dry place, protected from freezing. Store at no less than 4 °C (40 °F).
4. Protect from extreme heat and direct sunlight.
5. Do not apply materials in ambient temperatures below 4 °C (40 °F). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4 °C (40 °F) prevail.
6. Do not apply materials to frozen surfaces.

---

#### HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting [www.master-builders-solutions.com/en-us](http://www.master-builders-solutions.com/en-us), e-mailing your request to [mbsbscst@mbcc-group.com](mailto:mbsbscst@mbcc-group.com) or calling +1 (800) 433-9517. Use only as directed.

**IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.**

---

#### PROPOSITION 65

This product contains materials listed by the state of California as known to cause cancer, birth defects or other reproductive harm.

---

#### VOC CONTENT

0 g/l, or 0 lbs/gal less water and exempt solvents.

---

#### LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

**FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.**

For the most current version of this literature, please visit our website at [www.master-builders-solutions.com/en-us](http://www.master-builders-solutions.com/en-us).