

**LEED v4 & 4.1****Senerflex Acrylic Finishes**

LEED® BD+C: NC, CS, SCHOOLS, RETAIL, DATA CENTERS, WAREHOUSES & DISTRIBUTION CENTERS, HOSPITALITY, HEALTHCARE			
<b>CSI Division</b>	07 24 00	<b>Product Manufacturer</b>	Sika Corporation
<b>Product Name</b>	Senerflex Acrylic Finishes		
<b>Product Description</b>	Senerflex Acrylic Finishes are an 100% acrylic polymer finish with advanced technology to improve long term performance and dirt pick up resistance. It provides enhanced protection for an aesthetically pleasing surface color and texture for Senergy Wall Systems, poured concrete or unit masonry, conventional stucco, properly prepared insulating concrete forms and interior veneer plaster or gypsum wallboard(primer required over interior surfaces). This document covers Senergy Senerflex Acrylic Fine, Sahara, Texture, and Classic finishes.		

CREDIT CATEGORY	CREDITS				
MATERIALS AND RESOURCES (MR)	ENVIRONMENTAL PRODUCT DECLARATIONS:				
	Option 1. Environmental Product Declarations	EPD availability			No
	Option 2. Embodied Carbon/LCA Optimization	Carbon Optimization Report availability			No
	MATERIAL INGREDIENTS				
	Option 1. Material Ingredient Reporting	Manufacturer Inventory availability or Health Product Declaration availability			No
	Option 2. Material Ingredient Optimization	Material Ingredient Optimization Report availability			No
	SOURCING OF RAW MATERIALS				
	Extended producer responsibility program				No
	Bio-based materials				No
	Recycled content				Pre 0%    Post 0%
INDOOR ENVIRONMENTAL QUALITY (EQ)	LOW EMITTING MATERIALS				
	VOC emissions evaluation	California Department of Public Health (CDPH) v1.2 Emissions Test availability			No
	VOC content evaluation	Has a Volatile Organic Compound (VOC) content of	<37 g/L	Building Envelope Coating/Flats	



#### VOC Disclaimers

- VOC emissions evaluations follow guidance from: California Department of Public Health (CDPH) standard method V1.2-2017 and complies with limits in Table 4-1 of the method
- VOC content evaluation follow: Adhesives and Sealants: SCAQMD Rule 1168, OR Paints and Coatings: CARB 2007 (SCM) for Architectural Coatings and (SCAQMD) Rule 1113
- The VOC content is measured according to EPA Method 24 or ASTM D2369 standard methods
- Sika Corporation applies the worst-case scenario testing method for compliance with the requirements of CDPH standard method v.1.2-2017 for products formulated using the same set of raw materials

#### Legal Disclaimers

- Disclaimer: Information provided herein is for illustrative and general information purposes only, and is not intended to provide specific advice, and should not be relied upon in that regard.
- User is responsible for determining whether the Sika products and information in this document are appropriate for the intended use of the products and that such use and materials are in compliance with applicable laws and other government regulations. Prior to each use of any products of Sika, or Sika affiliates, user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet.
- NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY SIKA. ALL IMPLIED WARRANTIES, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. Sika, and its affiliates, assume no obligation or liability for the information contained in this document.

#### **Sika Corporation**

201 Polito Avenue,  
Lyndhurst, NJ 07071  
Phone : +1-800-933-7452  
Fax : +1-201-933-6225

[usa.sika.com](http://usa.sika.com)

