

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2020
2.0	05/06/2021	000000541699	Date of first issue: 10/26/2020

SECTION 1. IDENTIFICATION

Product name : SENERFLEX TERSUS M1.5 COL DK

Product code : 000000000050304466

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity
- repeated exposure (Inhalation) : Category 1 (Lungs)

Specific target organ toxicity
- repeated exposure (Inhalation) : Category 2 (Kidney, Immune system)

GHS label elements

Hazard pictograms : The image shows two GHS hazard pictograms side-by-side. The first is a red diamond with a black silhouette of a person with a star on their chest, representing Health Hazard. The second is a red diamond with a black exclamation mark, representing Irritant or Harmful.

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H350 May cause cancer by inhalation.
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.
H373 May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version 2.0 Revision Date: 05/06/2021 SDS Number: 000000541699 Date of last issue: 10/26/2020
Date of first issue: 10/26/2020

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.

Storage:
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards
None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Preparation based on:
inorganic compounds

Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO ₂)	14808-60-7	>= 25 - < 50
Cellulose	9004-34-6	>= 1 - < 3
Mica group minerals	12001-26-2	>= 1 - < 3
Kieselguhr, soda ash flux-calcined	68855-54-9	>= 1 - < 3
2-(Hydroxymethylamino)ethanol	34375-28-5	>= 0.2 - < 0.3

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.
Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,
remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2020
2.0	05/06/2021	000000541699	Date of first issue: 10/26/2020

and soap.
Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.

In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
May cause cancer by inhalation.
Causes damage to organs through prolonged or repeated exposure if inhaled.
Prolonged or repeated inhalation of respirable crystalline silica (quartz) may result in silicosis.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : water jet

Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.

Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides

Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.

Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version 2.0 Revision Date: 05/06/2021 SDS Number: 000000541699 Date of last issue: 10/26/2020
Date of first issue: 10/26/2020

- Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.
Wear eye/face protection.
If exposed to high vapour concentration, leave area immediately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
- Recommended storage temperature : > 32 °F / > 0 °C
- Further information on storage stability : PROTECT FROM FREEZING.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
------------	---------	------------------------	----------------------------------	-------

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version 2.0 Revision Date: 05/06/2021 SDS Number: 000000541699 Date of last issue: 10/26/2020
Date of first issue: 10/26/2020

		exposure)	concentration	
Cellulose	9004-34-6	TWA value	10 mg/m3	ACGIHTLV
		REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	ACGIH
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
Mica group minerals	12001-26-2	TWA value (Respirable fraction)	3 mg/m3	ACGIHTLV
		REL value (Respirable)	3 mg/m3	NIOSH
		TWA value (Respirable dust)	3 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	3 mg/m3	NIOSH REL
		TWA (respirable dust fraction)	3 mg/m3	OSHA P0
Quartz (SiO2)	14808-60-7	TWA (Res-	0.05 mg/m3	OSHA Z-1

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version 2.0 Revision Date: 05/06/2021 SDS Number: 000000541699 Date of last issue: 10/26/2020
Date of first issue: 10/26/2020

		pirable dust)		
		TWA (respirable)	10 mg/m3 / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m3	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
Kieselguhr, soda ash flux-calcined	68855-54-9	REL value	6 mg/m3	NIOSH
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA value	0.8 mg/m3	29 CFR 1910.1000 (Table Z-3)
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001-1050
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001-1050
		TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m3 (Silica)	NIOSH REL

Engineering measures : Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2020
2.0	05/06/2021	000000541699	Date of first issue: 10/26/2020

- | | | |
|--------------------------|---|---|
| Skin and body protection | : | Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit. |
| Protective measures | : | Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended. |
| Hygiene measures | : | When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks). |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- | | | |
|--|---|--|
| Appearance | : | viscous liquid |
| Color | : | off-white |
| Odor | : | mild, acrylic-like |
| Odor Threshold | : | not determined |
| pH | : | 8.5 - 9.5 (74 °F / 23 °C) |
| Melting point | : | No data available |
| Boiling point | : | No data available |
| Flash point | : | > 200.1 °F / > 93.4 °C

Method: Standard Method of Test for Flash Point by Setaflash Closed Tester |
| Evaporation rate | : | No data available |
| Flammability (liquids) | : | Not classified as a flammability hazard |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower | : | No data available |

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2020
2.0	05/06/2021	000000541699	Date of first issue: 10/26/2020

flammability limit

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 15.4 lb/USg (74 °F / 23 °C)

Solubility(ies)

Water solubility : partly miscible

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : Based on the water content the product does not ignite.

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No data available

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2020
2.0	05/06/2021	000000541699	Date of first issue: 10/26/2020

Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC	Group 1: Carcinogenic to humans Quartz (SiO ₂) (Silica dust, crystalline)	14808-60-7
	Group 1: Carcinogenic to humans Kaolin (Silica dust, crystalline)	1332-58-7
	Group 1: Carcinogenic to humans Distillates (petroleum), solvent-dewaxed heavy paraffinic (Mineral oils, untreated or mildly treated)	64742-65-0
	Group 2B: Possibly carcinogenic to humans Titanium dioxide	13463-67-7
OSHA	OSHA specifically regulated carcinogen Quartz (SiO ₂) (crystalline silica)	14808-60-7
NTP	Known to be human carcinogen Quartz (SiO ₂) (Silica, Crystalline (Respirable Size))	14808-60-7
	Known to be human carcinogen Kaolin (Silica, Crystalline (Respirable Size))	1332-58-7
	Known to be human carcinogen Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2020
2.0	05/06/2021	000000541699	Date of first issue: 10/26/2020

(Mineral Oils: Untreated and Mildly Treated)

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.
May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2020
2.0	05/06/2021	000000541699	Date of first issue: 10/26/2020

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with national, state and local regulations.
Residues should be disposed of in the same manner as the substance/product.
Do not discharge into drains/surface waters/groundwater.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.
- Packs that cannot be cleaned should be disposed of in the same manner as the contents.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

Quartz (SiO ₂)	14808-60-7
Mica group minerals	12001-26-2
Kieselguhr, soda ash flux-calcined	68855-54-9
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
ammonia	7664-41-7
ammonia, aqueous solution	1336-21-6

New Jersey Right To Know

Quartz (SiO ₂)	14808-60-7
Mica group minerals	12001-26-2
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version 2.0 Revision Date: 05/06/2021 SDS Number: 000000541699 Date of last issue: 10/26/2020
Date of first issue: 10/26/2020

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz (SiO₂), which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:


TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1000 (Table Z-3) : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2020
2.0	05/06/2021	000000541699	Date of first issue: 10/26/2020

1910.1000
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
29 CFR 1910.1000 (Table Z-3) / TWA value : Time Weighted Average (TWA):
29 CFR 1910.1001-1050 / OSHA Action level : OSHA Action level:
29 CFR 1910.1001-1050 / TWA value : Time Weighted Average (TWA):
ACGIH / TWA : 8-hour, time-weighted average
ACGIH TLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations;

SAFETY DATA SHEET

SENERFLEX TERSUS M1.5 COL DK



Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2020
2.0	05/06/2021	000000541699	Date of first issue: 10/26/2020

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/06/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN