

Senergy ASAP

100% acrylic-based coating

COLORS

Available in 128 standard colors and custom colors.

PACKAGING

24.9-kg per 19-liter pail
(55-lbs per 5-gallon pail)

COVERAGE

Approximate coverage rate:
69.6–116.1 m² (750–1,250 ft²) per pail
(one-coat application). Coverage rates may vary depending on the texture of the existing surface. Applications over concrete and masonry require two coats.

DESCRIPTION

100% acrylic-based coating with sand. Designed for coating EIFS textured finishes, with minimum change in finish texture or sheen.

USES

Senergy ASAP is intended for use as a coating for exterior wall surfaces such as concrete, stucco, unit masonry, acrylic base coat in sealant joints and to change the color of compatible textured finish.

Note: Senergy ASAP is not intended for use as a finish directly over Senergy Base Coat and is not recommended for touch-up.

SURFACE PREPARATION

Substrates must be clean, dry, sound and free of loose material, releasing agents, paint, efflorescence, contaminants and other coatings. Cracks or voids must be filled with MasterProtect® FL 746/ FL 748 or appropriate, compatible material to provide a solid substrate prior to application of Senergy ASAP. Ensure patching material is dry prior to application of Senergy ASAP.

CONCRETE:

1. Allow concrete to cure a minimum of 28 days prior to application of Senergy ASAP.
2. Remove all projections and form lines.

3. When needed, apply Master Builders Solutions Tinted Primer to cured concrete with a sprayer, 3/8" (10mm) nap roller or good-quality latex paint brush at a rate of approximately 150–250 ft² per gallon (3.6–6.1 m² per 3.8 liter). Master Builders Solutions Tinted Primer shall be dry to the touch before proceeding to the Senergy ASAP application.

UNIT MASONRY:

1. Allow unit masonry to cure prior to application of Senergy ASAP
2. Remove all loose mortar and projections.
3. When needed, apply a leveling coat of Master Builders Solutions Base Coat to provide a smooth surface prior to application of Senergy ASAP.

MIXING

1. Mix the contents of the Senergy ASAP pail with a low speed drill and paddle mixer until thoroughly blended.
2. A small amount of clean, potable water may be added to adjust workability, but is generally unnecessary since a thick consistency is desired.

FEATURES

100% Acrylic chemistry
Formulated to match the sheen of Senergy finishes
Slightly textured coating

BENEFITS

Provides optimal performance against elements
Minimizes changes in the aesthetics of the building
Makes minimal change to the texture of the wall

3. Additives are not permitted.
4. Close container when not in use.
5. Clean tools with soap and water immediately after use.

APPLICATION

GRAPHICS/COLOR CHANGE:

1. Apply Senergy ASAP with a 10 mm (3/8") nap roller. If necessary, cut in the edges with a high-quality, latex-type paint brush.
2. Brush or roll out in all directions, maintaining a wet edge at all times.
3. Senergy ASAP must be worked continuously until a uniform appearance is obtained over the entire wall surface.
4. For two-coat applications:
Allow the first coat to dry prior to application of the second coat in the same manner as above.
-OR-
Apply the first coat as a tack coat; while maintaining a wet edge, double-back with the second coat.

Note: Do not spray apply ASAP.

TO PREPARE A SEALANT JOINT FOR SEALANT APPLICATION:

1. Apply Senergy ASAP to the Base Coat in the joint with a high-quality, latex-type paint brush.
2. Senergy ASAP must be worked continuously until a uniform appearance is obtained.
3. Allow Senergy ASAP to dry thoroughly (approximately 24 hours) prior to application of sealant primer and sealant.

LIMITATIONS

1. Do not spray apply.
2. Protect Senergy materials during transportation and storage.
3. Store Senergy materials in a cool, dry place protected from freezing. Store at no less than 40 °F (4 °C). Protect from extreme heat and direct sunlight. Shelf life is two years when unopened and stored as directed.
4. Do not apply Senergy materials in ambient temperatures below 40 °F (4 °C). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 40 °F (4 °C) prevail.
5. Protect work from precipitation until dry.
6. Do not apply Senergy materials to frozen surfaces.

For the most current version of this literature, please visit our website at senergy.master-builders-solutions.com/en.

VOC CONTENT

72–152 g/l, or 0.60–1.27 lbs/gal less water and exempt solvents.

TECHNICAL SUPPORT

Consult Master Builders Solutions Technical Services Department at +1 (800) 589-1336 for specific recommendations concerning all other applications. Consult the Wall Systems website at www.master-builders-solutions.com/en-us, for additional information about products and systems and for updated literature.

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting www.master-builders-solutions.com/en-us, e-mailing your request to mbsbcst@mbcc-group.com or calling +1 (800) 433-9517. Use only as directed.

IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.

LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this

product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.