

Senergy® Base Coats / Adhesives Uses and Applications

TECHNICAL BULLETIN
1017554

	SENERQUICK	NC-II	ALPHA DRY	STANDARD BASE	ALPHA BASE	ALPHA GENIE	XTRA-STOP	COOL-SET ALPHA DRY ADHESIVE
For use with the Senerflex Wall Systems to adhere expanded polystyrene insulation board to new and untreated exposure 1 exterior grade plywood and exposure 1 OSB substrates.	Yes	Yes	Yes, conditioning of plywood and OSB with SENERPRIME is required.					
For use with the Senerflex Wall Systems to adhere expanded polystyrene insulation board to the following acceptable substrates: unpainted and unglazed concrete or unit masonry, Dens-Glass Gold (ASTM C1177), PermaBase cement-board or other Type A Exterior cement board (ASTM C1325), Fiberock Aqua-Tough Sheathing, or Exterior gypsum sheathing (ASTM C79/ASTM C1396).	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
For use with the Senerflex Channeled Adhesive Design/ Channeled Insulation Design Option to adhere expanded polystyrene insulation board to acceptable substrates that have been protected with an application of SENERSHIELD or SENERSHIELD-R (protection includes joint and wall penetration treatments).	No	No	Yes	Yes	Yes	Yes	Yes	Yes
To adhere expanded polystyrene insulation board to expanded polystyrene insulation board.	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
For use with Senerflex, Senturion, Cement-Board Stucco, Wall Systems and Senergy Exterior Surfacing Systems to embed Senergy CORNER MESH and REINFORCING MESH.	No	Yes	Yes	Yes	Yes	Yes	Yes	No
For leveling masonry, stucco, and other cementitious substrates to a maximum thickness of 6 m (1/4").	No	No	No	No	No	Yes	No	No

Senerwrap® Base Coats/Adhesives

Uses and Applications

Note

BASF Wall Systems is an operating unit of BASF Construction Chemicals, LLC. (herein after referred to as "BASF Wall Systems")

Residential Policy

On one and two-family residential framed construction, BASF Wall Systems requires that the wall system selected be one that includes provisions for water drainage. The choices include Senturion® line of water drainage EIFS, commercial Senerflex® Channeled Adhesive or Channeled Insulation Design, Senergy Stucco Wall System, and Senergy Cement-Board Stucco™ Systems. There are no exceptions to this policy. Under no circumstances will BASF Wall Systems warrant the use of any other system on this type of construction without expressed written authorization from BASF Wall Systems [Residential construction using EIFS on masonry (CMU) or poured concrete does not require the additional water drainage provisions described above. Senergy Exterior Surfacing Systems for insulating concrete forms are also acceptable.] See the Senergy Residential Policy Bulletin for a more detailed discussion of this topic. Consult BASF Wall Systems Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy website, www.senergy.basf.com for additional information about products and systems and for updated literature.

Disclaimer

This information and all further technical advice are based on BASF Wall Systems' present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, BASF Wall Systems disclaims any and all CONDITIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. BASF WALL SYSTEMS SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF Wall Systems reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

BASF Wall Systems

3550 St. Johns Bluff Road South
Jacksonville, FL 32224-2614
Phone 800 • 221 • 9255
Fax 904 • 996 • 6300
www.senergy.basf.com