

# Senergy® Drainage Mat

PRODUCT BULLETIN  
**1017563**

## Uses

For use with the Senturion™ III, Senerflex® Channeled Insulation Design and Senerflex® Pressure Equalized Design System to provide an avenue for flow and drainage of incidental moisture from the wall assembly.

## Technical Information

Consult the BASF Wall Systems Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy website, [www.senergy.basf.com](http://www.senergy.basf.com), for additional information about products and systems and for updated literature.

## Application

1. General: Substrate must be flat and free of planar irregularities greater than 6.4 mm in 3 m (1/4" in 10')
2. Apply SENERGY DRAINAGE MAT horizontally or vertically over secondary moisture protection barrier. SENERGY DRAINAGE MAT should be free of wrinkles.
3. Abut all vertical and horizontal edges.
4. Secure SENERGY DRAINAGE MAT to substrate with sufficient building staples or galvanized nails to remain in place prior to application of insulation board.
5. Apply Senergy Wall System materials in accordance with corresponding Senturion® III, Senerflex® Channeled Insulation Design and Senerflex® Pressure Equalized Design System specifications and details.

## Limitations

1. Protect SENERGY DRAINAGE MAT during transportation and installation to avoid physical damage.
2. Store SENERGY DRAINAGE MAT off ground, under cover, protected from direct sunlight, weather and construction activities.
3. See Senergy specifications and details for complete information on installation of Senergy Wall Systems.

## Description

Three-dimensional drainage system core component consisting of fused, entangled filaments.

## Packaging

991 mm x 76.2 m  
(39" x 250') per roll

100 mm x 76.2 m  
(4" x 250') per roll

Weight approx. 13.6 kg  
(30 lbs) per 39" roll

Features	Benefits
Lightweight	Easy to handle
Non-scratch nylon construction	Provides flexibility, enhances easy application
Entangled filament construction	Creates optimal drainage plane while retaining flexibility

# Senergy® Drainage Mat

## Note

BASF Wall Systems is an operating unit of BASF Construction Chemicals, LLC. (herein after referred to as "BASF Wall Systems")

## Residential Policy

On one and two-family residential framed construction, BASF Wall Systems requires that the wall system selected be one that includes provisions for water drainage. The choices include Senturion® line of water drainage EIFS, commercial Senerflex® Channeled Adhesive or Channeled Insulation Design, Senergy Stucco Wall System, and Senergy Cement-Board Stucco™ Systems. There are no exceptions to this policy. Under no circumstances will BASF Wall Systems warrant the use of any other system on this type of construction without expressed written authorization from BASF Wall Systems [Residential construction using EIFS on masonry (CMU) or poured concrete does not require the additional water drainage provisions described above. Senergy Exterior Surfacing Systems for insulating concrete forms are also acceptable.] See the Senergy Residential Policy Bulletin for a more detailed discussion of this topic. Consult BASF Wall Systems Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy website, [www.senergy.basf.com](http://www.senergy.basf.com) for additional information about products and systems and for updated literature.

## Disclaimer

This information and all further technical advice are based on BASF Wall Systems' present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, BASF Wall Systems disclaims any and all CONDITIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. BASF WALL SYSTEMS SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF Wall Systems reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

## BASF Wall Systems

3550 St. Johns Bluff Road South  
Jacksonville, FL 32224-2614  
Phone 800 • 221 • 9255  
Fax 904 • 996 • 6300  
[www.senergy.basf.com](http://www.senergy.basf.com)