

Senerprime

100% acrylic-based sheathing primer

Product Bulletin

DESCRIPTION

Black-tinted, 100% acrylic-based sheathing primer

PACKAGING

20.4 kg per 19-liter pail
(45 lbs per 5-gallon pail)

COVERAGE

(Approximate) 92–185 m²
(1,000–2,000 ft²) per pail,
may vary greatly due
to porosity and condition
of substrate.

USES

SENERPRIME is used as an adhesive intermediary between acceptable Senerflex Wall System substrates of new and untreated Exposure 1 or Exterior Grade Plywood Sheathing (Grade C-D or better), or Exposure 1 OSB.

MIXING

1. Stir SENERPRIME thoroughly prior to use.
2. Do not add water or admixtures of any type.
3. Close container when not in use.
4. Clean tools with soap and water immediately after use.

APPLICATION

1. Substrate shall be dry, clean, sound and free of releasing agents, paint, contaminants or other types residue or coatings. Verify substrate is flat, free of fins or planar irregularities greater than 6.4 mm in 3 m (1/4" in 10').
2. Apply SENERPRIME to substrate with 10 mm (3/8") nap roller, good-quality latex paint brush, or spray apply at a rate of 18.5–37.1 m² per liter (200–400 ft² per gallon).
3. SENERPRIME shall be dry to the touch before proceeding to the Senergy Base Coat/insulation board application.

Note: Apply SENERPRIME only to areas that will receive the EPS insulation board application the same day.

LIMITATIONS

1. Protect Senergy materials during transportation and installation to avoid physical damage.
2. Store Senergy materials in a cool, dry place protected from freezing. Store at no less than 4°C (40°F). Protect from extreme heat and direct sunlight. Shelf life is two years when unopened and stored as directed.
3. Do not apply Senergy materials in ambient temperatures below 4°C (40°F). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4°C (40°F) prevail.
4. Do not apply Senergy materials to frozen surfaces.

TECHNICAL INFORMATION

Consult our Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy website, www.senergy.basf.com, for additional information about products and systems and for updated literature.

Features	Benefits
Water-based acrylic	No VOC's; water clean-up
Tinted black	Easy to see application, ensuring even coverage
Properly prepares Exterior Grade or Exposure 1 wooden substrates	Allows the use of cementitious adhesives to adhere the EPS boards

Senerprime

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting www.senergy.basf.com. Use only as directed.

VOC Content

0 g/l, or 0 lbs/gal less water and exempt solvents.

For medical emergencies only call chemtrec at (800) 424-9300.

WARRANTY

BASF warrants this product to be free from manufacturing defects and to meet the technical properties on the current Product Bulletin, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. BASF MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of BASF. In the absence of an extended warranty issued by BASF, any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. BASF WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. BASF reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

For the most current version of this literature, please visit our website at www.senergy.basf.com.