

Revision date: 2019/05/29 Page: 1/10 Version: 10.0 (30368384/SDS GEN CA/EN)

1. Identification

Product identifier used on the label

SENERSHIELD R

Recommended use of the chemical and restriction on use

Recommended use*: Product for construction chemicals Recommended use*: for industrial and professional users

Details of the supplier of the safety data sheet

Company:

BASF Canada Inc. 100 Milverton Drive Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

CHEMTREC: 1-800-424-9300

BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification
Chemical family: Coating

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Skin Sens. 1 Skin sensitization Carc. 1A (by inhalation) Carcinogenicity

STOT RE 2 (by inhalation) Specific target organ toxicity — repeated

exposure

STOT RE 1 (by inhalation) Specific target organ toxicity — repeated

exposure

^{*} The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Revision date: 2019/05/29 Page: 2/10 Version: 10.0 (30368384/SDS GEN CA/EN)

Label elements

Pictogram:



Signal Word: Danger

Hazard Statement:

H317 May cause an allergic skin reaction. H350 May cause cancer by inhalation.

H373 May cause damage to organs (Kidney, Immune system) through

prolonged or repeated exposure (inhalation).

H372 Causes damage to organs (lung) through prolonged or repeated

exposure (inhalation).

Precautionary Statements (Prevention):

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P201 Obtain special instructions before use. P260 Do not breathe dust/gas/mist/vapours.

P202 Do not handle until all safety precautions have been read and

understood.

P270 Do not eat, drink or smoke when using this product.

P264 Wash with plenty of water and soap thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P314 Get medical advice/attention if you feel unwell.

P308 + P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage): P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection

point.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Labeling of special preparations (GHS):

Product contains the following components and may cause an allergic skin reaction: mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

The substance may cause sensitization of the skin in particularly sensitive individuals. Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Revision date: 2019/05/29 Page: 3/10 Version: 10.0 (30368384/SDS GEN CA/EN)

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

CAS Number	Weight %	Chemical name
68585-34-2	>= 0.1 - < 0.2%	sodium lauyl ether sulfate
4719-04-4	>= 0.1 - < 0.2%	2,2',2"-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol
2634-33-5	>= 0.0 - < 0.1%	1,2-benzisothiazol-3(2H)-one
55965-84-9	>= 0.0 - < 0.1%	mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
14808-60-7	>= 0.0 - < 50.0%	Quartz (SiO2)
1317-65-3	>= 10.0 - < 20.0%	Limestone
68855-54-9	>= 1.0 - < 3.0%	Kieselguhr, soda ash flux-calcined
13463-67-7	>= 1.0 - < 3.0%	Titanium dioxide

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air. If symptoms persist, seek medical advice.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Revision date: 2019/05/29 Page: 4/10 Version: 10.0 (30368384/SDS GEN CA/EN)

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons: water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Advice for fire-fighters

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing dust/fume/gas/mist/vapours/spray. Wear eye/face protection. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of. Dispose of absorbed material in accordance with regulations.

For large amounts: Pick up with suitable appliance and dispose of. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling

Avoid inhalation of dusts/mists/vapours. Avoid skin contact. Ensure adequate ventilation. No special measures necessary provided product is used correctly.

Protection against fire and explosion:

The product is neither self-ignitable, nor an explosion hazard, nor does it promote fires.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Suitable materials for containers: High density polyethylene (HDPE)

Revision date: 2019/05/29 Page: 5/10 Version: 10.0 (30368384/SDS GEN CA/EN)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight. Protect from temperatures below: 0 °C

The packed product must be protected from temperatures below the indicated one.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Limestone OSHA PEL PEL 5 mg/m3 Respirable fraction; PEL 15

mg/m3 Total dust; TWA value 5 mg/m3 Respirable fraction; TWA value 15 mg/m3

Total dust;

Titanium dioxide OSHA PEL PEL 15 mg/m3 Total dust ; TWA value 10

mg/m3 Total dust;

ACGIH TLV TWA value 10 mg/m3;

Kieselguhr, soda ash flux-

calcined

OSHA PEL TWA value 20 millions of particles per cubic foot

of air; TWA value 0.8 mg/m3;

The exposure limit is calculated from the equation, 80mg/m3)/(%SiO2), using a value of 100% SiO2. Lower percentages of SiO2 will yield

higher exposure limits.

OSHA Action level 0.025 mg/m3 (Respirable dust); TWA value 0.05 mg/m3 (Respirable dust);

Quartz (SiO2) OSHA PEL TWA value 0.05 mg/m3 (Respirable dust);

OSHA Action level 0.025 mg/m3 (Respirable

dust);

ACGIH TLV TWA value 0.025 mg/m3 Respirable fraction;

Advice on system design:

No applicable information available.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) respirator as necessary.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Do not inhale dust/fumes/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink

Revision date: 2019/05/29 Page: 6/10 Version: 10.0 (30368384/SDS GEN CA/EN)

or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks). When using do not eat or drink.

9. Physical and Chemical Properties

Form: viscous
Odour: slight odour

Odour threshold: No applicable information available.

Colour: grey pH value: 8 - 9.5 (23 °C)

Melting point: No applicable information available.

Boiling point: not applicable

Sublimation point:

No applicable information available.

Flash point:

A flash point determination is

unnecessary due to the high water

content.

Flammability: not determined

Lower explosion limit: No applicable information available. Upper explosion limit: No applicable information available. Autoignition: Based on the water content the

product does not ignite.

Vapour pressure: not applicable Density: 1.47 g/cm3

(23 °C)

Relative density: No applicable information available.

Bulk density: not applicable

Vapour density: No applicable information available.

Partitioning coefficient n- not applicable

octanol/water (log Pow):

Thermal decomposition: No decomposition if stored and handled as

prescribed/indicated.

Viscosity, dynamic: No applicable information available. Viscosity, kinematic: No applicable information available.

Solubility in water: soluble, miscible

Solubility (quantitative): No applicable information available. Solubility (qualitative): No applicable information available. Evaporation rate: No applicable information available.

Other Information: If necessary, information on other physical and chemical

parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Not an oxidizer.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

Revision date: 2019/05/29 Page: 7/10 Version: 10.0 (30368384/SDS GEN CA/EN)

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. Based on available Data, the classification criteria are not met.

Oral

No applicable information available.

<u>Inhalation</u>

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

No applicable information available.

<u>Irritation / corrosion</u>

Assessment of irritating effects: Based on available Data, the classification criteria are not met.

Sensitization

Assessment of sensitization: May cause sensitization by skin contact.

The product contains a mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1) (CAS-No.:55965-84-9). The substance may cause sensitization of the skin in particularly sensitive individuals. Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration Hazard

No aspiration hazard expected.

Revision date: 2019/05/29 Page: 8/10 Version: 10.0 (30368384/SDS GEN CA/EN)

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated or prolonged exposure may result in liver or kidney damage. This product contains crystalline silica (quartz). Prolonged or repeated inhalation of respirable crystalline silica may result in silicosis.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: May cause cancer.

Information on: Titanium dioxide

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Based on available Data, the classification criteria are not met. There is a high probability that the product is not acutely harmful to aquatic organisms.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Revision date: 2019/05/29 Page: 9/10 Version: 10.0 (30368384/SDS GEN CA/EN)

Not readily biodegradable (by OECD criteria).

Bioaccumulative potential

Assessment bioaccumulation potential

Discharge into the environment must be avoided.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Observe national and local legal requirements. The waste code in accordance with the European waste catalog (EWC) must be specified in cooperation with disposal agency/manufacturer/authorities. Residues should be disposed of in the same manner as the substance/product.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

14. Transport Information

Land transport

TDG

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Revision date: 2019/05/29 Page: 10/10 Version: 10.0 (30368384/SDS_GEN_CA/EN)

Chemical DSL, CA released / listed

NFPA Hazard codes:

Health: 2 Fire: 1 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2019/05/29

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET