

# TERSUS COLOR COAT TB DP

Version **Revision Date:** SDS Number: Date of last issue: 08/26/2020 10/07/2022 000000610263 Date of first issue: 08/26/2020 1.1

**SECTION 1. IDENTIFICATION** 

Product name TERSUS COLOR COAT TB DP

Product code 00000000050374148 00000000050374148

Manufacturer or supplier's details

Company name of supplier Master Builders-Construction Systems

US, LLC

Address 23700 CHAGRIN BLVD

Beachwood OH 44122

ChemTel: +1-813-248-0585 Emergency telephone

National Emergency Tele-

phone Number

USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use Functional surface coating

Restrictions on use Reserved for industrial and professional use.

# **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization Category 1

Carcinogenicity (Inhalation) Category 1A

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1 (Lungs)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Kidney, Immune system)

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

**GHS** label elements

# **MBCC** GROUP

# TERSUS COLOR COAT TB DP

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/26/2020

 1.1
 10/07/2022
 000000610263
 Date of first issue: 08/26/2020

Hazard pictograms





Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure if inhaled.

H373 May cause damage to organs (Kidney, Immune system)

through prolonged or repeated exposure if inhaled.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary Statements** 

#### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing must not be allowed out of

the workshope

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

# Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

## Storage:

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

## Other hazards

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Aqueous solution

### Components

Chemical name	ICAS-No.	Concentration (% w/w)
ICHEHIICAI HAIHE	ICAS-NO.	



# TERSUS COLOR COAT TB DP

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/26/2020

 1.1
 10/07/2022
 000000610263
 Date of first issue: 08/26/2020

Quartz (SiO2)	14808-60-7	>= 1 - < 5
cristobalite	14464-46-1	>= 1 - < 5
Silicon dioxide	7631-86-9	>= 1 - < 5
1,3,5-Triazine-1,3,5(2H,4H,6H)- triethanol	4719-04-4	>= 0.1 - < 1
diuron	330-54-1	< 0.1
carbendazim	10605-21-7	< 0.1
3-iodo-2-propynyl butylcarbamate	55406-53-6	< 0.1

Actual concentration is withheld as a trade secret

### **SECTION 4. FIRST AID MEASURES**

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Remove contact lenses, if present.

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do NOT induce vomiting.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Prolonged or repeated inhalation of respirable crystalline silica

(quartz) may result in silicosis.

Notes to physician : Treat symptomatically.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

# MBCC GROUP

# TERSUS COLOR COAT TB DP

Version **Revision Date:** SDS Number: Date of last issue: 08/26/2020 000000610263 Date of first issue: 08/26/2020 1.1 10/07/2022

Hazardous combustion prod: :

ucts

harmful vapours nitrogen oxides fumes/smoke carbon black carbon oxides

Further information The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

Special protective equipment :

for fire-fighters

Wear a self-contained breathing apparatus.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: Use personal protective equipment.

tive equipment and emer-

gency procedures

Prevent product from entering drains. **Environmental precautions** 

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

## **SECTION 7. HANDLING AND STORAGE**

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Keep only in the original container in a cool, dry, well-Conditions for safe storage

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.



# TERSUS COLOR COAT TB DP

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/26/2020

 1.1
 10/07/2022
 000000610263
 Date of first issue: 08/26/2020

Further information on stor-

PROTECT FROM FREEZING DURING THE COLD-SEASON

age stability (BELOW 40°F / 5°C).

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2)	14808-60-7	TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
cristobalite	14464-46-1	TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable dust fraction)	0.05 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million parti- cles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
		TWA	6 mg/m3 (Silica)	NIOSH REL
diuron	330-54-1	TWA TWA	10 mg/m3 10 mg/m3	ACGIH NIOSH REL
		TWA	10 mg/m3	OSHA P0

**Engineering measures** : Ensure adequate ventilation.



# TERSUS COLOR COAT TB DP

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/26/2020

 1.1
 10/07/2022
 000000610263
 Date of first issue: 08/26/2020

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Use NIOSH approved respiratory protection.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen depending on activity and

possible exposure, e.g. head protection, apron, protective

boots, chemical-protection suit.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : viscous liquid

Color : off-white

Odor : mild

Odor Threshold : No data available

pH : No data available

Melting point : No data available

Boiling point : No data available



# TERSUS COLOR COAT TB DP

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/26/2020

 1.1
 10/07/2022
 000000610263
 Date of first issue: 08/26/2020

Flash point : approx.  $> 200.1 \, ^{\circ}\text{F} / > 93.4 \, ^{\circ}\text{C}$ 

Method: Flashpoint test using closed cup, determination of

flashpoint., closed cup

Evaporation rate : No data available

Flammability (liquids) : not flammable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 1.39 g/cm3 (73 °F / 23 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

not applicable for mixtures

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No data available

Molecular weight : Not applicable

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

# **MBCC** GROUP

# TERSUS COLOR COAT TB DP

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/26/2020

 1.1
 10/07/2022
 000000610263
 Date of first issue: 08/26/2020

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

Not classified based on available information.

### Skin corrosion/irritation

Not classified based on available information.

## Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitization

## Skin sensitization

May cause an allergic skin reaction.

### Respiratory sensitization

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

(Silica dust, crystalline)

Group 1: Carcinogenic to humans

cristobalite 14464-46-1

(Silica dust, crystalline)

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

(Silica, Crystalline (Respirable Size))

Known to be human carcinogen

cristobalite 14464-46-1

(Silica, Crystalline (Respirable Size))



# TERSUS COLOR COAT TB DP

Version **Revision Date:** SDS Number: Date of last issue: 08/26/2020 10/07/2022 000000610263 Date of first issue: 08/26/2020 1.1

## Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled. May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

## **Aspiration toxicity**

Not classified based on available information.

#### **Further information**

### **Product:**

Remarks Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

### **Product:**

# **Ecotoxicology Assessment**

Acute aquatic toxicity Harmful to aquatic life.

Chronic aquatic toxicity Harmful to aquatic life with long lasting effects.

### **Components:**

### diuron:

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic

10

toxicity)

### carbendazim:

M-Factor (Acute aquatic tox- :

10

icity)

M-Factor (Chronic aquatic

10

toxicity)

### 3-iodo-2-propynyl butylcarbamate:

M-Factor (Acute aquatic tox- :

# TERSUS COLOR COAT TB DP

Version Revision Date: SDS Number: Date of last issue: 08/26/2020 1.1 10/07/2022 000000610263 Date of first issue: 08/26/2020

icity)

M-Factor (Chronic aquatic

toxicity)

: 1

## Persistence and degradability

No data available

## **Bioaccumulative potential**

No data available

# Mobility in soil

No data available

### Other adverse effects

#### **Product:**

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

## **Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

### **SECTION 14. TRANSPORT INFORMATION**

## International Regulations

## **UNRTDG**

Not regulated as a dangerous good

### IATA-DGR

Not regulated as a dangerous good

### **IMDG-Code**

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

**49 CFR** 



# TERSUS COLOR COAT TB DP

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/26/2020

 1.1
 10/07/2022
 000000610263
 Date of first issue: 08/26/2020

Not regulated as a dangerous good

### **SECTION 15. REGULATORY INFORMATION**

### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
carbendazim	10605-21-7	10	27777

## **US State Regulations**

# Pennsylvania Right To Know

Quartz (SiO2)	14808-60-7
cristobalite	14464-46-1
Silicon dioxide	7631-86-9
diuron	330-54-1
ammonia, aqueous solution	1336-21-6
ammonia	7664-41-7

## **New Jersey Right To Know**

Quartz (SiO2) 14808-60-7 cristobalite 14464-46-1

## California Prop. 65

WARNING: This product can expose you to chemicals including Quartz (SiO2), which is/are known to the State of California to cause cancer, and

methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

## The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : This product contains one or more components not listed on

the Canadian DSL or NDSL. All other components are on the

Canadian DSL.

# **Canadian lists**

The following substance(s) is/are subject to a Significant New Activity Notification: carbendazim 10605-21-7

## **SECTION 16. OTHER INFORMATION**


### **Further information**

## TERSUS COLOR COAT TB DP

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/26/2020


 1.1
 10/07/2022
 000000610263
 Date of first issue: 08/26/2020

#### NFPA 704:



Special hazard

### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Admin-



# TERSUS COLOR COAT TB DP

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/26/2020

 1.1
 10/07/2022
 000000610263
 Date of first issue: 08/26/2020

istration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 10/07/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN