

# PRODUCT DATA • SIKA® ENDURO® 600



## ADVANTAGES OF SIKA ENDURO 600 FIBERS:

- Non-magnetic
- Rustproof
- Alkali proof
- Requires no minimum amount of concrete cover
- Always positioned in compliance with codes
- Safe and easier to use than traditional reinforcement.
- Saves time
- Packaged for easy dosing into the concrete mix

## SIKA ENDURO 600 MACRO-SYNTHETIC FIBER

SIKA ENDURO 600 is the latest high performance macro-synthetic fiber developed from the innovative HPP technology which was pioneered and patented by Fibermesh - A Sika Brand. ENDURO 600 has been specifically designed to satisfy the demanding requirements of modern day concrete and shotcrete reinforcement and equipment. Specifically engineered and manufactured in an ISO 9001 certified manufacturing facility for use as concrete reinforcement.

## FEATURES & BENEFITS

- Geometrically engineered to resist matrix pullout
- Increases flexural toughness
- Reduces rebound
- Increases cohesion and reduces segregation
- Increases impact and shatter resistance
- Non-magnetic
- Rustproof
- Chemically inert and alkali proof
- Reduced wear on concrete pumps and hoses
- Safe and easy to handle
- Simplified logistics
- Economical alternative to steel wire mesh and/or steel fibers

## PRIMARY APPLICATIONS

- Sprayed concrete
- Precast
- Mining
- Tunnel linings
- Channel Linings
- Slope stabilization
- Slab on ground
- Pavement

## COMPLIANCE

- Complies with ASTM C 1116/C1116M Type III Fiber Reinforced Concrete
- Complies with European Standard EN 14889-2: 2006 Fibres for Concrete Part 2: Class II and carries CE marking
- ISO 9001 Quality Assured Facility

## CHEMICAL AND PHYSICAL PROPERTIES

Absorption	Nil	Ignition Point	759.2 °F (404 °C)
Acid & Salt Resistance	High	Melt Point	320 °F (160 °C)
Alkali Resistance	Alkali Proof	Specific Gravity	0.91
Electrical Conductivity	Low	Thermal Conductivity	Low
Fiber Length*	2 in (51 mm)	Equivalent Diameter	0.032 in (0.81 mm)

\* Available in other cut lengths

# WE ARE THE CONCRETE FIBER EXPERTS™

[WWW.FIBERMESH.COM](http://WWW.FIBERMESH.COM)

# PRODUCT DATA • SIKA® ENDURO® 600

## PRODUCT USE

**MIXING:** The specified dosage per m<sup>3</sup> or yd<sup>3</sup> should be added to the mixer after batching the other concrete materials. After the addition of the fibers, the concrete should be mixed for sufficient time (batch plant: minimum 5 minutes or 70 revolutions) at full mixing speed to ensure uniform distribution of the fibers throughout the concrete mix. Mixing times may vary, please contact Sika Fiber representative.

**PLACING:** ENDURO 600 macro synthetic polyolefin fibers can be pumped, sprayed or placed using conventional equipment.

**FINISHING:** Conventional techniques and equipment can be used when finishing ENDURO 600 fiber concrete.

**APPLICATION RATE:** The application rate for ENDURO 600 macro-synthetic fibers will vary depending on the application, mix design and the toughness requirements of each particular project. Typically, ENDURO 600 macrosynthetic fibers dosage will be in the range of 4 pcy to 15 pcy (2.4 kg/m<sup>3</sup> to 9 kg/m<sup>3</sup>) of concrete. When used in conjunction with Sika Fibermesh 150 fibers the dosage rate and the performance of the sprayed concrete can be optimized economically. For specific performance and dosage recommendations see your local Sika Fiber representative.

## COMPATIBILITY

ENDURO 600 fibers are compatible with all concrete admixtures and performance enhancing chemicals.

## SAFETY

No special handling is required with ENDURO 600 macrosynthetic fibers. Full Safety Data Sheets are available upon request.

## PACKAGING

ENDURO 600 macrosynthetic fibers are collated in degradable water soluble wrapped bundles (pucks), packaged in a range of box weights from 15 to 22 lb (7 to 10 kg). Other packaging options are available such as bulk bags. Store materials in a cool dry place. Do not store in direct sunlight.

## TECHNICAL SERVICES

Trained Sika Fiber specialists are available worldwide to assist and advise in specifications and field service. Sika Fiber representatives do not engage in the practice of engineering or supervision of projects and are available solely for service and support of our customers.

## REFERENCE DOCUMENTS

- ACI 304 Guide for Measuring, Mixing, Transporting and Placing Concrete
- ACI 506 Guide for Shotcrete
- ASTM C1116/C1116M Standard Specification for Fiber-Reinforced Concrete and Shotcrete
- ASTM C 1436 Standard Specification for Materials for Shotcrete
- ASTM C 1550 Standard Test Method for Flexural Toughness of Fiber Reinforced Concrete (Using Centrally Loaded Round Panel)
- ASTM C 1609 /C 1609M Standard Test Method for Flexural Performance of Fiber-Reinforced Concrete (Using Beam With Third-Point Loading).
- Concrete Society (UK) Technical Report 65 Guidance on the use of Macro-synthetic Fibre Reinforced Concrete
- Concrete Society (UK) Technical Report 66 External In-situ Concrete Paving
- EFNARC European Specification for Sprayed Concrete
- European Standard EN 14889-2: 2006 Fibres for Concrete

## SPECIFICATION CLAUSE

Fibers for concrete shall be SIKA ENDURO 600 polyolefin high performance macro-monofilament fiber conforming to ASTM C1116 Type III and manufactured specifically for the reinforcement of concrete

or

Fibers for concrete shall be SIKA ENDURO 600 polyolefin high performance macro-monofilament fiber conforming to EN14889-2: 2006 Class II and manufactured specifically for the reinforcement of concrete

The fibers shall be manufactured in an ISO 9001 certified manufacturing facility. Unless otherwise stated, SIKA ENDURO 600 macro-synthetic fibers shall be mixed at the batch plant, at the recommended rate of ... lbs/yd<sup>3</sup> (... kgs/m<sup>3</sup>), and mixed for sufficient time (minimum 5 minutes) to ensure uniform distribution of the fibers throughout the concrete mix. Fibrous concrete reinforcement shall be manufactured by Sika Fibers, LLC, 4019 Industry Drive, Chattanooga, TN. 37416 USA, tel: 833.236.1255, web site: www.Fibermesh.com.

Sika Fibers, LLC • 4019 Industry Drive • Chattanooga, TN 37416 • SIKAFIBERS@US.SIKA.COM  
NORTH AMERICA: +1.833.236.1255 • EUROPE: +44.1246.564200 • AUSTRALIA: +61.0.2.9965.3792 • LATIN AMERICA: +1.813.285.2287

Fibermesh®, Fibercast®, Enduro®, Novomesh®, Novocon® are registered trademarks of Sika Fibers, LLC.

This publication should not be construed as engineering advice. While information contained in this publication is accurate to the best of our knowledge, Sika Fibers, LLC does not warrant its accuracy or completeness. The ultimate customer and user of the products should assume sole responsibility for the final determination of the suitability of the information and the products for the contemplated and actual use. The only warranty made by Sika Fibers, LLC for its products is set forth in our product data sheets for the product, or such other written warranty as may be agreed by Sika Fibers, LLC and individual customers. Sika Fibers, LLC specifically disclaims all other warranties, express or implied including without limitation, warranties of merchantability or fitness for a particular purpose, or arising from provision of samples, a course of dealing or usage of trade.

© Sika Fibers, LLC

PCS-1157E-004 (04/2019)