

**SECTION 1. IDENTIFICATION**

| | | |
|---|---|--|
| Product name | : | Sika AnchorFix®-3001 Part A |
| Company name | : | Sika Corporation 201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com |
| Telephone | : | (201) 933-8800 |
| Telefax | : | (201) 804-1076 |
| E-mail address | : | ehs@sika-corp.com |
| Emergency telephone | : | CHEMTREC: 800-424-9300 INTERNATIONAL: +1-703-527-3887 |
| Recommended use of the chemical and restrictions on use | : | For further information, refer to product data sheet. |

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

| | | |
|--------------------|---|-------------|
| Skin irritation | : | Category 2 |
| Eye irritation | : | Category 2A |
| Skin sensitization | : | Category 1 |

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.Precautionary Statements : **Prevention:**
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing must not be allowed out of



the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

| Chemical name | CAS-No. | Classification | Concentration (% w/w) |
|---|------------|--|-----------------------|
| bisphenol-A-(epichlorhydrin) epoxy resin | 25068-38-6 | Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317 | ≥ 50 - < 70 |
| bisphenol-F-(epichlorhydrin) epoxy resin | 9003-36-5 | Skin Irrit. 2; H315 Skin Sens. 1; H317 | ≥ 20 - < 30 |
| Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) | 16096-31-4 | Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317 | ≥ 10 - < 20 |
| Talc | 14807-96-6 | | ≥ 1 - < 5 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.



- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.

- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.

- Most important symptoms and effects, both acute and delayed : irritant effects
sensitizing effects
Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.

- Environmental precautions : Do not flush into surface water or sanitary sewer system.
Local authorities should be advised if significant spillages cannot be contained.

- Methods and materials for : Soak up with inert absorbent material (e.g. sand, silica gel,



containment and cleaning up : acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|------------|-------------------------------------|--|-----------|
| Talc | 14807-96-6 | TWA (Dust) | 20 Million particles per cubic foot | OSHA Z-3 |
| | | TWA (respirable dust fraction) | 2 mg/m3 | OSHA P0 |
| | | TWA (Respirable particulate matter) | 2 mg/m3 | ACGIH |
| | | PEL (respirable) | 0.05 mg/m3 | OSHA CARC |

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

- Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro-



cess enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : off-white, white
- Odor : slight
- Odor Threshold : No data available
- pH : Not applicable substance/mixture is non-soluble (in water)
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : > 95 °F / > 35 °C
- Flash point : > 212 °F / 100 °C
(Method: closed cup)



| | | |
|--|---|--|
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapor pressure | : | 0.01 hpa |
| Relative vapor density | : | No data available |
| Density | : | ca. 1.25 g/cm ³ (68 °F / 20 °C) |
| Solubility(ies) | | |
| Water solubility | : | insoluble |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Autoignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity | | |
| Viscosity, dynamic | : | No data available |
| Viscosity, kinematic | : | > 20.5 mm ² /s (104 °F / 40 °C) |
| Explosive properties | : | No data available |
| Oxidizing properties | : | No data available |
| Volatile organic compounds (VOC) content | : | 5 g/l A+B Combined |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|---|
| Reactivity | : | No dangerous reaction known under conditions of normal use. |
| Chemical stability | : | The product is chemically stable. |
| Possibility of hazardous reactions | : | Stable under recommended storage conditions. |
| Conditions to avoid | : | No data available |
| Incompatible materials | : | No data available |
| Hazardous decomposition | : | No decomposition if stored and applied as directed. |



products

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

bisphenol-A-(epichlorhydrin) epoxy resin:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Not applicable

OSHA OSHA specifically regulated carcinogen
Talc (Mg₃H₂(SiO₃)₄) 14807-96-6
(crystalline silica)

NTP Not applicable

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified based on available information.



SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

bisphenol-A-(epichlorhydrin) epoxy resin:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
aquatic invertebrates Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
May be harmful to the environment if released in large quantities.
Water polluting material.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR



Sika AnchorFix®-3001 Part A

Revision Date 04/08/2022

Print Date 04/08/2022

UN/ID No. : UN 3082
 Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
 (epoxy resin)
 Class : 9
 Packing group : III
 Labels : Miscellaneous
 Packing instruction (cargo : 964
 aircraft)
 Packing instruction (passen- : 964
 ger aircraft)

IMDG-Code

UN number : UN 3082
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
 N.O.S.
 (epoxy resin)
 Class : 9
 Packing group : III
 Labels : 9
 EmS Code : F-A, S-F
 Marine pollutant : yes

Domestic regulation

49 CFR

UN/ID/NA number : UN 3082
 Proper shipping name : Environmentally hazardous substances, liquid, n.o.s.
 (bisphenol-A-(epichlorhydrin) epoxy resin)
 Class : 9
 Packing group : III
 Labels : CLASS 9
 ERG Code : 171
 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization



Skin corrosion or irritation
 Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Talc, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

| | | |
|-----------------|---|--|
| ACGIH | : | USA. ACGIH Threshold Limit Values (TLV) |
| OSHA CARC | : | OSHA Specifically Regulated Chemicals/Carcinogens |
| OSHA P0 | : | USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values) |
| OSHA Z-3 | : | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts |
| ACGIH / TWA | : | 8-hour, time-weighted average |
| OSHA CARC / PEL | : | Permissible exposure limit (PEL) |
| OSHA P0 / TWA | : | 8-hour time weighted average |
| OSHA Z-3 / TWA | : | 8-hour time weighted average |

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Safety Data Sheet

Sika AnchorFix®-3001 Part A



Revision Date 04/08/2022

Print Date 04/08/2022

100000004056
US / Z8